

Material Safety Data Sheet

Date Prepared 3/2000

Product Number: 6600 - *Mason Stain*

Section 1: Manufacturer Identification

Mason Color Works, Inc.
250 East 2nd Street/P.O. Box 76
East Liverpool, OH 43920-5076

Phone: (330) 385-4400
Fax: (330) 385-4488

H=3
F=0
R=0

Section 2: Identification of Product

Chemical Family: Inorganic
Product Names: Black 6600
Chemical Abstract Number (CAS): 67186-97-0
Chemical Name: Cobalt Chromite Black - Spinel
Chemical Formula: (Co,Fe) (Fe,Cr)₂ O₄

Section 3 & Section 4: Hazardous ingredients Identity/Information and Overexposure Symptoms

	ACGIH-TLVs	OSHA PELs	NOISHA RELs
1 Chrome Oxide (Cr₂O₃) Cas # 1313-13-2	0.5 mg/m ³	0.5 mg/m ³	0.5 mg/m ³

ACGIH: Not classifiable as a human carcinogen: Inadequate data on which to classify the agent in terms of carcinogenicity in humans/animals.

Symptoms of overexposure:

Inhalation: Repeated prolonged exposure to trivalent compounds may cause delayed effects involving the respiratory system.

Eye Contact: mechanical irritation to the eye may occur such as watering, reddening do to exposure to fines.

Skin Contact: Expected to be non irritating.

Ingestion: Considered to be non-irritating , non-toxic if swallowed.

2 Cobalt Oxide (Co₃O₄) Cas # 1396-06-1	0.02 mg/m ³	0.5 mg/m ³	N/A
-------------------------------------------------------------------------------	------------------------	-----------------------	-----

ACGIH: Animal carcinogen: Agent is carcinogenic in experimental animals at dose levels, by route (s) of administration at site, or histologic type, or by mechanism considered relevant to workers exposure. Available epidemiologis studies do not confirm an increased risk of cancer in humans except under common levels of exposure.

Symptoms of Overexposure:

Inhalation: Prolonged inhalation of dust or metal dust, and fume or mist containing cobalt may cause serious respiratory illness. May cause an irritation of respiratory organs of sensitive persons resulting in obstruction of airways with shortness of breath.

Eye Contact: May cause serious eye irritation.

Skin Contact: Prolonged exposure may produce irritation.

Ingestion: Large amounts may cause irritation of the gastrointestinal tract, nausea, vomiting and diarrhea.

3 Iron Oxide (Fe₂O₃) Cas # 1309-37-1	5 mg/m ³	10 mg/m ³	5 mg/m ³
-----------------------------------------------------------------------------	---------------------	----------------------	---------------------

Section 7: Physical and Chemical Characteristics

Boiling Point: N/A
Solubility in water: trace
Vapor Pressure (mmHg): N/A
Vapor Density (air=1): N/A
Appearance: black powder

Odor: odorless
Specific Gravity (water=1): N/A
Evaporation rate: None
% Volatile by volume: None

Section 8: Reactivity Data

Stability: Stable
Hazardous Polymerization: will not occur
Incompatibility: None
Hazard Decomposition of product: N/A

Section 9: Fire and Explosive Data

Flash point: N/A
Unusual Fire and Explosion Hazard: None expected
Extinguishing Media: Carbon dioxide, dry chemical or water
Special Fire Fighting Procedures: Wear self contained breathing apparatus when large quantities involved.

Flammable Limits: None

Section 10: Spill or Leak Procedures:

Contain spillage and scoop or vacuum. Avoid making dust, put in appropriate container for disposal.
Waste disposal method in accordance with Federal, State and Local Laws.

This product is a blend of various metal oxides, salts and some compounds which are interfused by high calcination to form the finished product. Section III, Hazardous Ingredients Identity/Information, and Section IV, Symptoms of Overexposure, pertain to individual components. Section V through Section X are in reference to the finished product.

*****Attention All Retailers of Mason Stains*****

ALL retailers of this product are REQUIRED by law to supply their customers with a copy of this material safety data sheet with initial purchase.

***SARA 313

This product contains certain oxides and compounds which are subject to reporting requirements of Superfund Amendment and Reauthorization Act (SARA) of 1986, Section 313 of the Emergency Planning and Community Right to Know Act and of 40 CRF, Part 372.

The information contained in this Material Safety Data Sheet must be provided to every employee who is exposed to this product in any way. We recommend the user reads and understands the contents herein before using this material.

PLEASE KEEP ON FILE FOR FUTURE REFERENCE. DO NOT THROW AWAY! MATERIAL SAFETY DATA SHEETS ARE REQUIRED FOR FIRST SHIPMENT, AND WILL BE SENT AGAIN WHEN REVISED UPON YOUR NEXT ORDER OF PRODUCT OR BY REQUEST.

DISCLAIMER

Mason Color Works, Inc. believes the information contained in this material safety data sheet is believed to be accurate and reliable as of the date of publication or revision but makes no warranty that it is. This information provided should be made available as required by the Federal OSHA Hazard Communication Standard 1910.1200 to ANYONE who handles, uses, stores, transports or will otherwise be exposed to this product. Mason Color Works, Inc. Accepts no Responsibility for the health or safety of any individual who misuses this product by not complying with manufacturer's instructions contained herein or additional /other measures that may be required under particular conditions.

Last issued: 11/97
Updated : 3/2000