

File

MATERIAL SAFETY DATA SHEET

NPCA 1

FOR COATINGS, RESINS AND RELATED MATERIALS

(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20)

DATE OF PREP. 6-82

Section I

MANUFACTURER'S NAME AMF INCORPORATED (DISTRIBUTOR) **AMF BOWLING**

STREET ADDRESS 151 MARTIN DRIVE CITY, STATE, AND ZIP CODE **8800 AMF DRIVE**
RICHMOND, VA 23111

EMERGENCY TELEPHONE NO. CHEMTREC 1-800-424-9300

INFORMATION TELEPHONE NO. (419) 347-5522

PRODUCT CLASS Solvent Cleaner MANUFACTURERS CODE IDENTIFICATION 2J5901

TRADE NAME AMF Magic Triangle Pre-finishing Cleaner AMF# 039-005-901

Section II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT	TLV		LEL	VAPOR PRESSURE mmHg@20°C
		PPM	mg/M ³		
Xylene	> 9	100		1.0	6
Butanol	> 9	50		1.4	5.5

Section III - PHYSICAL DATA

BOILING RANGE 225°-290° F VAPOR DENSITY HEAVIER LIGHTER THAN AIR

VAPORATION RATE FASTER SLOWER THAN ETHER PERCENT VOLATILE BY VOLUME 100% WEIGHT PER GALLON 7.0#/gal.

Section IV - FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CATEGORY Flammable FLASH POINT 79° F (TCC) LEL see sec. II

EXTINGUISHING MEDIA Foam, CO₂, Dry Chemical, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS
None

SPECIAL FIRE FIGHTING PROCEDURES
Use water with caution. Wear self-contained breathing apparatus.

Section V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE see section II
EFFECTS OF OVEREXPOSURE Liquid may cause eye burns. Prolonged skin contact with liquid may produce irritation. Eye, nose and throat irritation may result from exposure to vapor. Narcotic effects occur at higher concentrations of vapor.

EMERGENCY AND FIRST AID PROCEDURES Eyes: Wash with plenty of water for 15 minutes. Get medical attention. SKIN: Wash thoroughly with soap and water. INHALATION: Remove from exposure, treat symptomatically and get medical attention. INGESTION: If swallowed, call physician immediately. DO NOT induce vomiting.

Section VI - REACTIVITY DATA

STABILITY UNSTABLE STABLE CONDITIONS TO AVOID ~~#####~~ N/A
INCOMPATIBILITY (Materials to avoid) strong oxidizers
HAZARDOUS DECOMPOSITION PRODUCTS CO, CO₂

HAZARDOUS POLYMERIZATION MAY OCCUR WILL NOT OCCUR
CONDITIONS TO AVOID N/A

Section VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Absorb with inert absorbant.

WASTE DISPOSAL METHOD Dispose of in accordance with Federal, State And Local regulations.

Section VIII - SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION A NIOSH - approved respirator for organic vapors should be worn if needed.

VENTILATION local exhaust desirable
General mechanical recommended

PROTECTIVE GLOVES should be worn
EYE PROTECTION goggles or safty glasses
OTHER PROTECTIVE EQUIPMENT eye bath

Section IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING Keep away from heat, sparks and flame.
A Keep container closed

OTHER PRECAUTIONS
DO NOT TAKE INTERNALLY
KEEP OUT OF REACH OF CHILDREN
FOR INDUSTRY USE ONLY