

FEB 17 2009

19123449

MATERIAL SAFETY DATA SHEET  
29 CFR 1910.1200 OSHA Hazard  
Communication Rule Format  
Chem-Tel 24 Hour Emergency # 1-800-255-3924

MINE SAFETY APPLIANCES COMPANY  
P.O. Box 426  
Pittsburgh, PA 15230  
PHONE (412) 967-3000

MSA P/N 10048280

This product contains carbon monoxide, methane, hydrogen sulfide, oxygen and nitrogen, substances subject to the Pennsylvania Worker and Community Right-To-Know Act.

**PRODUCT IDENTITY**

LABEL IDENTITY - MSA P/N 10048280 Calibration Check Gas, 60 ppm Carbon Monoxide, 1.45 % Methane, 15% Oxygen, 20 ppm Hydrogen Sulfide, Balance Nitrogen

CHEMICAL NAME - Carbon Monoxide, Methane, Oxygen, Hydrogen Sulfide, Nitrogen Mixture

ADDITIONAL IDENTITIES - MSA P/N 10048280 Calibration Gas

FORMULA -  $CO + CH_4 + O_2 + H_2S + N_2$

**APPLICABLE CHEMICAL CONTENTS**

	%	TWA	STEL
Carbon Monoxide (CAS 630-08-0) (ACGIH 2005)	0.0060	25 ppm	
Methane (CAS 74-82-8)	1.45	1000 ppm*	
Oxygen (CAS 7782-44-7)	15	None	
Hydrogen Sulfide (CAS 7783-06-4)	0.0020	10 ppm	15 ppm
Nitrogen (CAS 7727-37-9)	Balance	None	

\*Methane as an alkane (ACGIH 2005)

NOTE: Gas under Pressure, 500 PSIG at 70°F. Approx. 34 Liters Gas at Atmospheric Pressure

**PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE AND ODOR - Colorless, Malodorous Gas

BOILING POINT - N/A\*

VAPOR PRESSURE - N/A

VAPOR DENSITY (AIR = 1) - Approx. 1

SOLUBILITY IN WATER - Carbon Monoxide - 3.5 cm<sup>3</sup>/100 ml (0°C)  
Methane - 9 cm<sup>3</sup>/100 ml (20°C)  
Oxygen - 3.2 cm<sup>3</sup>/100 ml (25°C)  
Hydrogen Sulfide - 437 cm<sup>3</sup>/100 ml (0°C)  
Nitrogen - 2.3 cm<sup>3</sup>/100 ml (0°C)

SPECIFIC GRAVITY (H<sub>2</sub>O = 1) - N/A

PERCENT VOLATILE BY VOLUME - N/A

\*N/A - Not Applicable

**PHYSICAL HAZARD INFORMATION**

PHYSICAL HAZARD - Compressed gas, 500 PSIG at 70°F

CONDITIONS OR MATERIALS TO AVOID - None

FLASH POINT - N/A LEL - N/A UEL - N/A

EXTINGUISHING MEDIA - This gas mixture is not flammable.

SPECIAL FIRE FIGHTING PROCEDURES - See next item.

UNUSUAL FIRE AND EXPLOSION HAZARDS - Gas under pressure, 500 PSIG at 70°F. Do not exceed 120°F.

**HEALTH HAZARDS**

HEALTH HAZARDS - Methane as an alkane (ACGIH 2005). Carbon monoxide TCLO (Human) is reportedly 650 ppm/45 minutes; LC<sub>10</sub> (Human) 5000 ppm/5 minutes. Hydrogen sulfide LC<sub>10</sub> = 800 ppm/5 minutes. No effects known below 10 ppm.

SIGNS AND SYMPTOMS OF EXPOSURE - Methane as an alkane CNS depression and cardiac sensitization. Exposure to 500-1000 ppm Carbon Monoxide may cause headache, rapid breathing, nausea, weakness, dizziness and confusion. Hydrogen sulfide is an irritant of the eyes and respiratory tract.

PRIMARY ROUTES OF ENTRY - Inhalation, eyes.

TARGET ORGANS - Methane CNS and heart. Carbon monoxide: Lungs, Blood, and Tissues. Carbon monoxide at toxic concentrations causes tissue hypoxia (lack of oxygen) by preventing blood from transporting sufficient oxygen. Hydrogen sulfide is an irritant of the eyes and respiratory tract.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE -Pre-existing respiratory conditions may be aggravated by over-exposure to this gas mixture. Carbon monoxide can aggravate some diseases of the cardiovascular system, such as coronary artery disease and angina pectoris. Because of the presence of Hydrogen Sulfide, eye disorders or skin problems may be aggravated by over-exposure to this gas mixture.

EXPOSURE LIMITS - Methane as an alkane 1000 ppm (ACGIH 2005). Carbon Monoxide TWA 25 ppm (ACGIH 2005), TWA 35 ppm (OSHA). Hydrogen sulfide TWA 10 ppm, STEL 15 ppm (ACGIH 2005).

CARCINOGENICITY DATA - NIOSH RTECS, OSHA, NTP or IARC does not list Component gases.

EMERGENCY AND FIRST AID PROCEDURES - Remove from exposure. Administer oxygen. Consult physician immediately.

**SAFE HANDLING AND USE**

HYGIENIC PRACTICES - Avoid breathing gas

PROTECTIVE MEASURES DURING REPAIR AND MAINTENANCE OF CONTAMINATED EQUIPMENT - N/A

PROCEDURES FOR SPILL OR LEAK CLEANUP - Ventilate area.

WASTE DISPOSAL - Do not puncture or incinerate cylinder. Before discarding cylinder, slowly release contents to a safe exhaust. Dispose of cylinder in accordance with local, state and federal regulations

STORAGE - Store in a cool, dry, well-ventilated area. Do not exceed 120°F.

**CONTROL MEASURES**

PERSONAL PROTECTIVE EQUIPMENT - Due to the limited amount of gas in the cylinder, and the low release rate employed in instrument calibration, respiratory protection is not indicated under conditions of intended use.

ENGINEERING CONTROLS - Mechanical ventilation is suitable.

WORK PRACTICES - Avoid breathing gas. Use in well-ventilated areas. Follow the calibration procedure detailed in the MSA instruction manual provided with the instrument under calibration.

DATE OF PREPARATION - Rev. 1, December 2006

WARNING: This is a hazardous chemical product. By following the directions and warnings provided with this product, the hazards associated with the use of this product can be greatly reduced but never entirely eliminated. Mine Safety Appliances Company makes no warranties, expressed or implied, with respect to this product and EXPRESSLY DISCLAIMS THE WARRANTY OF MERCHANTABILITY AND ANY WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. Users

MSA P/N 10048280

assume all risks in handling, using or storing this product.