

1-20-06

CBF
PINT 57000
57032
57690

MATERIAL SAFETY DATA SHEET

The Coastal Corporation

Coastal Oil New York, Inc.
Coastal Oil New England, Inc.
Coastal Fuels marketing, Inc.
Coastal Mobile Refining Company
Coastal Derby Refining Company
Coastal Eagle Point Oil Company
Coastal Mart, Inc.
Coastal Refining & Marketing, Inc.

Coastal States Crude Gathering Co.
Coastal States Trading, Inc.
Coastal Unilube, Inc.
Coscol Marine Corporation
Coscol Petroleum Corporation
Pacific Refining Company
Western Fuel Oil Company
Coastal Fuel Terminals, Inc.

Address: 9 Greenway Plaza
Houston, TX 77046

Info Phone: (901) 525-2300
Emergency Phone: (713) 877-1400

PRODUCT IDENTIFICATION

Trade Name: ~~CarQuest Power Steering Fluid~~

Date Revised: August 1, 2000

Synonyms/product Code: N.A.

Chemical Name: Petroleum Mineral Oil

ly Description: A complex combination of hydrocarbons from a petroleum fraction obtained by solvent crystallization plus additives.

DOT Hazard Class: Not Applicable

COMPOSITION

Occupational Exposure Limits*

Product	CAS Number	Wt%	Occupational Exposure Limits*			Units
			OSHA PEL	ACGIH TLV	Other	
CarQuest Power Steering Fluid***	Mixture	100	N.A.	N.A.		

Ingredient(s):

Severely Hydrotreated Heavy Naphthenic Distillate	64742-52-2	>99	5	5	10 STEL	mg/m***
Additives containing Zinc salt of dialkyl-dithiophosphate (ZDDP), 2,6-di-t-butylphenol and polymers	N.A. -P	<1	N.A.	N.A.		

* = 8-Hr. TWA unless otherwise specified.
 ** = As mineral oil Mist
 *** = All ingredients in this product are listed in the T.S.C.A. Inventory.
 N.A. = Not Available
 STEL = Short Term Exposure Limit; 15 minutes.
 N.A. -P = Information for this component is claimed proprietary by supplier

PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point 760 mmHg:	N.A.	Melting Point:
Vapor Pressure mmHg @ 100F:	N.A.	Vapor Density (air=1): N.A.
Solubility in H ₂ O %:	Nil.	pH: N.A.
Specific Gravity (H ₂ O):	0.922	Evaporation Rate (ethyl ether =1): N.A.
% Volatile by Volume:	N.A.	Odor: Slight hydrocarbon odor
Viscosity (method, temp):	32 cSt @ 40C	Appearance: Pale Liquid

N.A. = Not Available

FIRE AND EXPLOSION DATA

Flash Point:	350 F
Flammable Limits in Air % by Vol.	Lower: N.A. Upper: N.A.
Autoignition Temperature:	N.A.
Extinguishing Media:	Dry chemical, foam, carbon dioxide or water spray.
Special Fire Fighting Procedure:	Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool. Firefighters should wear self-contained breathing apparatus.
Unusual Fire or Explosion Hazard:	May ignite when sufficient heat is applied.

REACTIVITY DATA

Stability:	Stable
Hazardous Polymerization:	Will not occur.
Conditions to Avoid/Incompatibility:	Strong oxidizing agents, heat, spark, flame and build-up of static electricity.
Hazardous Decomposition Products:	Hydrogen sulfide, carbon monoxide, carbon dioxide, aldehydes, ketones, and combustion products of sulfur and nitrogen.

HEALTH HAZARD DATA

This product has not been tested as a whole to determine its specific health hazards. The information provided in this section is based on health hazard information on the product components.

Carcinogenicity: NTP: No	IARC Monographs: No	OSHA Regulated: No
Occupational Exposure Limits:	See <u>COMPOSITION</u> section.	

Effects of Overexposure:

<u>Acute:</u>	
Eyes:	The heavy paraffinic petroleum distillate fraction of this product is believed to be minimally irritating.

- Skin:** The heavy paraffinic petroleum distillate fraction of this product is believed to be minimally irritating.
- Inhalation:** The inhalation hazards of this products components are negligible to minimally irritating if airborne concentrations are kept below permissible occupational exposure limits.
- Ingestion:** Ingestion hazards range from practically non-toxic to minimally toxic for the components of this product. If vomiting occurs, product is an aspiration hazard.

Chronic: Frequent or prolonged contact may cause skin irritation.

Additional Medical and Toxicological Information: May aggravate pre-existing dermatitis. The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity in experimental animals of used oil.

EMERGENCY FIRST AID PROCEDURES

- Eye Contact:** Flush thoroughly with water for at least 15 minutes. Get medical attention.
- Skin Contact:** Remove contaminated clothing. Wash affected areas with soap and water. If irritation occurs, get medical help.
- Inhalation:** Remove to fresh air. Apply artificial respiration if not breathing. Get medical attention.
- Ingestion:** Do not induce vomiting. If spontaneous vomiting occurs hold the victim's head lower than hips to prevent aspiration.

SPECIAL PROTECTION INFORMATION

- Eye Protection:** Remove contact lenses and wear chemical safety goggles where contact with liquid or mist may occur.
- Skin Protection:** Wear impervious gloves when contact with skin may occur. Use face shields where splashing may occur.
- Inhalation:** Use approved respiratory protective equipment for cleaning large spills or entry into large tanks, vessels or other confined spaces or in situations where exposure may exceed occupational exposure levels.
- Ventilation:** Provide adequate ventilation to keep mist or vapors below occupational exposure levels.

SPILL OR LEAK AND DISPOSAL PROCEDURES

- Spill Procedures:** Remove sources of heat or ignition including internal combustion engines and power tools. Remove spill with vacuum trucks or pump and soak up residue with and absorbent. Use approved respirator where occupational exposure limits may be exceeded.

CarQuest Power Steering Fluid

Page 4 of 4

Waste Disposal: Dispose through a licensed waste disposal company. Follow federal, state and local regulation.

SPECIAL PRECAUTIONS AND COMMENTS

Storage Requirements: Store in tightly closed containers in an dry cool place, away from sources of heat, ignition or strong oxidizers. Ground and bond all transfer and storage equipment and equip with self closing valves, pressure vacuum bungs and flame arrestors.

SARA TITLE III INFORMATION

<u>Acute</u>	<u>Chronic</u>	<u>Fire</u>	<u>Pressure</u>	<u>Reactive</u>
X	X			

SARA Hazardous Substances

<u>Ingredient</u>	<u>CAS NO.</u>	<u>% WT</u>	<u>Sec 313</u>	<u>Sec 302</u>	<u>RQ, lb</u>	<u>TPQ, lb</u>
Zinc Compound	N.A.	<1	X			

Key: Sec 313 = Toxic Chemicals, Section 313
 Sec 302 = Extremely Hazardous Substances (EHS)
 RQ = Reportable Quantity of EHS
 TPQ = Threshold Planning Quantity of EHS

CALIFORNIA PROPOSITION 65 WARNING

Chemicals known to the State of California to cause cancer, birth defects or other reproductive harm may be found in the petroleum products. Although it is possible to sufficiently refine the petroleum products to remove the potential for cancer, we are advising that one or more of the listed chemicals may be present in some detectable quantities. Read and follow directions and use care when handling these petroleum products.

THIS INFORMATION RELATES ONLY TO THE SPECIFIC MATERIAL DESIGNATED AND MAY NOT BE VALID FOR SUCH MATERIAL USED IN COMBINATION WITH ANY OTHER MATERIALS OR IN ANY PROCESS. SUCH INFORMATION IS TO THE BEST OF THIS COMPANY'S KNOWLEDGE AND BELIEVED ACCURATE AND RELIABLE AS OF THE DATE INDICATED. HOWEVER, NO REPRESENTATION, WARRANTY OR GUARANTEE IS MADE AS TO THE ACCURACY, RELIABILITY OR COMPLETENESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY HIMSELF AS TO THE SUITABLENESS AND COMPLETENESS OF SUCH INFORMATION FOR HIS OWN PARTICULAR USE.