



CITGO Petroleum Corporation
P.O. Box 3758
Tulsa, Oklahoma 74102

Material Safety Data Sheet

Trade Name: CITGO Non-Detergent Oil, SAE 30
Commodity Code: 20-703
Synonyms: Lubricating Oil Date: January 25, 1993
CAS No.: Mixture Technical Contact: (918) 495-5933
(Refer to Section 1) Medical Emergency: (918) 495-5700
CHEMTREC Emergency: (800) 424-9300
Citgo Index No.: 0006

Material Hazard Evaluation

(Per OSHA Hazard Communication
Standard [29 CFR Part 1910.1200]) (OHCS)

Health: Final Product Low Hazard.

Precautionary Statement: Avoid prolonged skin contact with used motor oils. Do not inhale mists or fumes.

HMIS Rating¹: Health 0 Flammability 1 Reactivity 0

1.0 Generic Composition / Components

<u>Components</u>	<u>CAS #</u>	<u>%</u>	<u>Hazard Data</u>
Refined Petroleum Oils	64742-65-0 64742-01-4 64741-88-4 64742-53-6 64742-52-5 64741-89-5 8052-42-4	> 96	Oral LD50(rat): > 5g/kg
Additives containing Detergent Inhibitors, Pour Point Depressants and VI Improvers	Mixture	< 3	Oral LD50(rat): > 5g/kg Eye: Irritant Skin: Low irritant

¹ Hazard Rating: least-0; slight-1; moderate-2; high-3; extreme-4
CITGO assignment based on our evaluation per NFPA and NPCA guidelines.

2.0 Physical Data

Physical Hazard Classification (Per 29 CFR Part 1910.1200)

No	Combustible	No	Flammable	No	Pyrophoric
No	Compressed Gas	No	Organic Peroxide	No	Reactivity
No	Explosive	No	Oxidizer	Yes	Stable

Boiling Point, 760 mmHg, °C(°F): ~ 344(~ 652)
 Specific Gravity (60/60°F) (H₂O = 1): 0.91
 Vapor Density (Air = 1): > 1
 % Volatiles by Volume: Negligible
 Melting Point, °C(°F): NA
 Vapor Pressure, mmHg (25°C): < 1x10⁻³
 Solubility in H₂O., % by Weight: Negligible
 Evaporation Rate (Butyl Acetate = 1): < 1
 pH of Undiluted Product: NA
 Appearance and Odor: Amber liquid - bland odor.

3.0 Fire and Explosion Data

Flash Point, COC, °C(°F)	257(495)
Flash Point, PM, °C(°F)	206(403)
Fire Point, COC, °C(°F)	ND
NFPA Rating ²	Health: 0 Flammability: 1 Reactivity: 0
Flammable Limits (% by volume in air)	Lower: ND Upper: ND
Extinguishing Media	CO ₂ , dry chemical, foam, water fog
Special Fire Fighting Procedure	None.
Unusual Fire or Explosion Hazard	Water may cause frothing.

4.0 Reactivity Data

Stability: Stable.
Conditions Contributing to Instability: None.
Incompatibility: Strong oxidants, strong acids, caustics.
Hazardous Decomposition Products: CO₂, (CO under incomplete combustion),
(thermal, unless otherwise specified)
Conditions Contributing to Hazardous Polymerization: None.

² Hazard Rating: least-0; slight-1; moderate-2; high-3; extreme-4
 CITGO assignment based on our evaluation per NFPA guidelines.

5.0 Spill or Leak Procedures

Procedures if Material is Spilled:

- Remove sources of heat or ignition.
- Provide adequate ventilation.
- *Small Spills:* Take up with noncombustible absorbant such as fullers earth or sand. Place into containers for later disposal.
- *Large Spills:* Contain spill in earthen dikes for later recovery. Control ignition sources around spill area. Report spills as required to appropriate authorities.

Waste Disposal:

- It is the responsibility of the user to determine if the material is a hazardous waste at the time of disposal.
- Check before disposing to be sure you are in compliance with all applicable laws and regulations.
- Treat used oil according to current rules and regulations.
- RCRA Emergency Hotline Number: 800-424-9346.

Protective Measures During Repair and Maintenance of Contaminated Equipment:

- Refer to Section 7.0 - Special Protection Information.
- Wash exposed skin thoroughly with soap and water.
- Remove soiled clothing.
- Use polymer gloves if extended, direct contact is expected.
- Avoid prolonged contact with used oil.

6.0 Health Hazard Data

Health Hazard Classification

(Per 29 CFR Part 1910.1200)

No	Carcinogen	No	Corrosive
No	Animal Carcinogen	No	Irritant
No	Suspect Carcinogen	No	Sensitizer
No	Mutagen	No	Teratogen
No	Highly Toxic	No	Target Organ
No	Toxic		

Product listed as Carcinogen or Potential Carcinogen by:

NTP No IARC No OSHA No Other No

Toxicity Summary: Practically non-toxic.

Major Route(s) of Entry: Inhalation of incidental mists or vapors.

Acute Exposure Symptoms

<i>Inhalation:</i>	Low risk at ambient temperatures. Mists or fumes may cause dizziness, headache, nausea, respiratory irritation, or chemical pneumonitis.
<i>Dermal Contact:</i>	Transient, slight irritation.
<i>Eye Contact:</i>	Practically non-irritant.
<i>Ingestion:</i>	Low toxicity. If less than one ounce is ingested, material may pass through the system without harm. On ingestion of large quantities slight GI discomfort, diarrhea, and headache may occur.
<i>Injection:</i>	Subcutaneous or intramuscular injection may cause irritation, erythema, edema.

Chronic Exposure

Dermal, prolonged and repeated exposure may cause drying of the skin.

Other Special Effects

None.

Medical Conditions Aggravated by Exposure

None.

First Aid and Emergency Procedures for Acute Effect

<i>Inhalation:</i>	Remove from exposure to incidental fumes and provide respiratory support if necessary.
<i>Dermal:</i>	Wash with soap and water.
<i>Eyes:</i>	Flush with large volumes of water.
<i>Ingestion:</i>	Induce vomiting and seek medical aid.
<i>Injection:</i>	Seek medical aid.

Notes to Physician: Following ingestion, at a Saybolt viscosity of approximately 700 SUS at 100°F, the risk of aspiration into the lungs is practically zero. For quantities above 1 oz., emesis or lavage may be considered. Subcutaneous injection requires prompt surgical debridement. If not familiar with technique, seek skilled advice.

7.0 Special Protection Information

Ventilation Requirements: Use in well ventilated area. In confined spaces, mechanical ventilation may be required to keep levels of certain components below mandated standards. Responsible individuals should evaluate air concentrations of specific regulated chemicals.

Permitted Threshold Air Concentrations:

Mineral Oil Mist	TLV-TWA	5 mg/m ³	OSHA-PEL	5/mg/m ³
	TLV-STEL	10 mg/m ³	OSHA-STEL	ND
	TLV-Ceiling	ND	OSHA-Ceiling	ND
			OSHA-Peak	ND

Specific Personal Protective Equipment:

Respiratory: If high vapor concentration is expected, use respirator approved for organic vapors.

Eyes: Safety goggles, or chemical splash goggles if splashing is anticipated.

Dermal: Oil impervious gloves if frequent or prolonged contact is expected.

Other Clothing or Equipment: Wear body-covering work clothes to avoid prolonged or repeated exposure. Launder soiled work clothes before reuse.

8.0 Transportation and Special Precautions

Storage: Keep container tightly closed and away from heat and flame.

Caution: Avoid prolonged skin contact with used motor oils. Continuous contact with used oil has caused skin cancer in laboratory animals. After draining oil, wash skin thoroughly with soap and water. Empty containers may contain product residue which could include flammable or explosive vapors.

Consult appropriate Federal, State and Local authorities before reusing, reconditioning, reclaiming, recycling or disposing of empty containers and/or waste residues of this product.

DOT Information

Proper Shipping Name:	Petroleum Lubrication Oil
Hazard Class:	Non-Hazardous
Hazard Identification Number:	None assigned
Placard:	None
Compatibility Category:	Group 33
CHRIS Code:	OLB

9.0 Environmental Data

Product Name CITGO Non-Detergent Oil, SAE 30
Commodity Code: 20-703

SARA TITLE III

Section 313 - Toxic Chemicals

This product does not contain toxic chemicals of Section 313 of Title III of Superfund Amendments and Re-authorization Act of 1986 (SARA) and 40 CFR Part 372.

<u>Components</u>	<u>CAS#</u>	<u>%</u>
None	NA	NA

Section 311 - Hazard Categories

<u>Yes</u> Not Applicable	<u>No</u> Fire Hazard
<u>No</u> Acute (Immediate Health Hazard)	<u>No</u> Sudden Release of Pressure Hazard
<u>No</u> Chronic (Delayed Health Hazard)	<u>No</u> Reactive Hazard

Section 302 (a) - Extremely Hazardous Substances

(RQ = Reportable Quantity)
(TPQ = Threshold Planning Quantity)

This product does not contain Extremely Hazardous Substances of Section 302(A).

<u>Component</u>	<u>CAS#</u>	<u>%</u>	<u>RQ lbs.</u>	<u>TPQ lbs.</u>
None	-	-	-	-

Clean Water Act

Under Section 311 (b) (4) of the Clean Water Act, discharges of crude oil and petroleum products in any kind or form to surface waters must be immediately reported to the National Response Center: 800-424-8802.

Comprehensive Environmental, Response, Compensation & Liability Act (CERCLA) - Section 102 Hazardous Substances

<u>Component</u>	<u>CAS#</u>	<u>%</u>	<u>RQ lbs.</u>
------------------	-------------	----------	----------------

Petroleum and petroleum fractions are excluded from the list of CERCLA hazardous substances by Section 101(14) of CERCLA.

New Jersey Worker and Community Right-to-Know Act

Petroleum Oil

CALIFORNIA Proposition 65

Tradename: CITGO Non-Detergent Oil, SAE 30

Contains components that occur on lists of:

Carcinogenic Materials	<u> </u> Yes	<u> x </u> No
Teratogenic Materials	<u> </u> Yes	<u> x </u> No

Federal Regulations

Reported in TSCA Inventory:

Product	<input type="checkbox"/> Yes	<input type="checkbox"/> No	<input checked="" type="checkbox"/> NA
Components	<input checked="" type="checkbox"/> Yes	<input type="checkbox"/> No	<input type="checkbox"/> NA

10.0 Labeling

NOTE

This product has been determined not to be a physical or a health hazard as defined by the OSHA Hazard Communication Standard.

Avoid prolonged skin contact with used motor oil. Continuous contact has caused skin cancer in laboratory animals. After draining oil, wash skin thoroughly with soap and water. Clean oil soaked clothing before reuse.

ALL STATEMENTS, INFORMATION, AND DATA PROVIDED IN THIS MATERIAL SAFETY DATA SHEET ARE BELIEVED TO BE ACCURATE AND RELIABLE, BUT ARE PRESENTED WITHOUT GUARANTEE, REPRESENTATION, WARRANTY, OR RESPONSIBILITY OF ANY KIND, EXPRESSED OR IMPLIED. ANY AND ALL REPRESENTATIONS AND/OR WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY DISCLAIMED. USERS SHOULD MAKE THEIR OWN INVESTIGATIONS TO DETERMINE THE SUITABILITY OF THE INFORMATION OR PRODUCTS FOR THEIR PARTICULAR PURPOSE. NOTHING CONTAINED HEREIN IS INTENDED AS PERMISSION, INDUCEMENT, OR RECOMMENDATION TO VIOLATE ANY LAWS OR TO PRACTICE ANY INVENTION COVERED BY EXISTING PATENTS, COPYRIGHTS OR INVENTIONS.