

SECTION 1 - MANUFACTURER INFORMATION

Manufacturer/Distr.	DBA Products Co., Inc. 22 Skokie Highway Lake Bluff IL 60044	Information #	1-708-234-8100
		Emergency #	1-800-255-3924 (Chem-Tel) 24 hours
		Emergency Inter'l #	1-813-979-0626 (Chem-Tel) 24 hours/Call Collect

SECTION 1A - PRODUCT IDENTIFICATION

Product name	DBA Bowling Lane Cleaner & Polish #501	LEGEND: Severe Hazard = 4 Serious Hazard = 3 Moderate Hazard = 2 Slight Hazard = 1 Minimal Hazard = 0	Hazardous Materials Identification System	
Product Description	Conditioner		HEALTH	1
Product #	120501	FLAMMABILITY	2	
Revision Date	10/1/93	REACTIVITY	0	
		PROTECTION	D	

SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL	CAS #	%	Exposure PPM	TLV MG/M3	SARA 313	NTP	IARC	65
Aliphatic Solvent	64742-89-8	n/i	500	n/i	n/i	n/i	n/i	n/i

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute & Chronic):

Swallowing: Can cause gastrointestinal irritation, nausea and vomiting.

Inhalation: May be harmful or irritating.

Eye: May cause eye irritation.

Dermal: May cause mild irritation of the skin.

Repeated Overexposure: Vapors harmful or irritating on prolonged or repeated exposure. Reports have associated prolonged and repeated occupational overexposure to solvent with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EMERGENCY FIRST AID PROCEDURES:

Swallowing: If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. Do not induce vomiting.

Inhalation: Provide fresh air and rest.

Eye: Flush with large amounts of water, raising upper and lower lids occasionally. Continue for 15 minutes. Get medical attention.

Dermal: Wash affected are with soap and water. An emollient cream or lotion is beneficial.

PRIMARY ROUTE OF ENTRY: n/i

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: n/i

SECTION 4 - PHYSICAL, FIRE, EXPLOSION DATA

Flashpoint (C):	40°C (104°F)	Evaporation rate:	n/i	Boiling Point:	193°C (380°F)
Vapor Density:	heavier than air	UEL:	n/i	Weight per gallon:	6.9 lbs.
Specific Gravity:	0.832	LEL:	n/i	% volatile by weight:	100

Appearance & odor: Water clear oily liquid Solubility in water: insoluble

EXTINGUISHING MEDIA: Use carbon dioxide all purpose chemical, alcohol foam. Polymer foam is preferred for large fires.

FIRE & EXPLOSION HAZARDS: Excessive heat to exposed containers may cause pressure build-up or possible explosion.

HAZARDOUS DECOMPOSITION PRODUCTS: If burned, will produce carbon monoxide and carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES: Firefighters should use air supplied breathing apparatus. Cool exposed containers with water spray to prevent pressure build-up or explosion.

SECTION 5 - REACTIVITY DATA

IS PRODUCT STABLE: Stable under normal conditions.

CONDITIONS TO AVOID FOR STABILITY: Avoid intensive heat, sparks or open flame.

INCOMPATIBILITY (Materials to Avoid): n/i

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID FOR POLYMERIZATION: n/i

SECTION 6 - EXPOSURE CONTROL DATA

VENTILATION: Local exhaust should be adequate.

RESPIRATORY PROTECTION: Use supplied air respirator for protection in confined or enclosed areas, if needed.

PROTECTIVE EQUIPMENT: Gloves: Use chemical resistant gloves to prevent prolonged or repeated skin contact.

Eye: Use splash shield or goggles to prevent eye contact. Use chemical resistant apron to prevent clothing contamination which could result in prolonged skin contact.

WORK PRACTICES: n/a

HYGIENIC PRACTICES: Use waterless hand cleaner to remove then wash thoroughly with soap and water.

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Avoid breathing vapors. Keep spectators away. place free liquid in covered metal containers for recovery or disposal. Use inert absorbent (sand, earth, sawdust, or vermiculite), to spill area. Place used absorbent in containers for disposal. Keep material out of sewers, streams, and groundwater. Advise authorities if material has entered sewers or waterway.

WASTE DISPOSAL METHODS: Dispose in accordance with federal, state, and local regulations. Dispose of used absorbent at EPA permitted disposal site.

SECTION 8 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Close containers after each use. Keep away from excessive heat, sparks, or open flame. Keep away from children.

OTHER PRECAUTIONS: Avoid breathing vapors, avoid prolonged or repeated contact with skin. Remove contaminated clothing, launder before reuse. Remove contaminated shoes and thoroughly dry before reuse.

SECTION 9 - SHIPPING INFORMATION

SHIPPING INFORMATION	U.S. D.O.T. INFORMATION	INTERNATIONAL INFORMATION
SHIPPING NAME	Combustible Liquid	Flammable Liquid NOS (contains Naphtha Solvent)
HAZARD CLASS	N/A	Class #3
U.N. NUMBER	N/A	UN 1993
PACKAGING GROUP	N/A	III
LABELS	N/A	Flammable Liquid

The information contained herein is based on the data considered to be accurate. While the information is believed to be reliable, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since the use of this information and the conditions and use of this product are controlled by the user, it is the user's obligation to determine the conditions of the safe use of the product.