

TRU-TEST MANUFACTURING -- EASY COLOR PRIMER-SEALER, JLP
MATERIAL SAFETY DATA SHEET
NSN: 803000N062263
Manufacturer's CAGE: TRUTE
Part No. Indicator: A
Part Number/Trade Name: EASY COLOR PRIMER/SEALER, JLP

General Information

Company's Name: TRU-TEST MANUFACTURING CO
Company's Street: 201 JANDUS RD
Company's City: CARY
Company's State: IL
Company's Country: US
Company's Zip Code: 60013
Company's Emerg Ph #: 800-228-5635
Company's Info Ph #: 708-639-5383
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SMJ
Date MSDS Prepared: 14DEC93
Safety Data Review Date: 03AUG95
MSDS Serial Number: BYGPL

Ingredients/Identity Information

Proprietary: NO
Ingredient: ETHYLENE GLYCOL (SARA 313) (CERCLA). VP:0.1 @ 20C.
Ingredient Sequence Number: 01
Percent: 2-4
NIOSH (RTECS) Number: KW2975000
CAS Number: 107-21-1
OSHA PEL: 50 PPM (MFR)
ACGIH TLV: 50 PPM, VAPOR, C

Proprietary: NO
Ingredient: SILICA, CRYSTALLINE - QUARTZ; (CRYSTALLINE SILICA)
Ingredient Sequence Number: 02
Percent: 3-5
NIOSH (RTECS) Number: VV7330000
CAS Number: 14808-60-7
OSHA PEL: 0.1 MG/M3 (MFR)
ACGIH TLV: 0.1 MG/M3 RDUST

Proprietary: NO
Ingredient: VOLATILE ORGANIC COMPOUNDS: <150 G/L.
Ingredient Sequence Number: 03
NIOSH (RTECS) Number: 9999999VO
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE

Physical/Chemical Characteristics

Appearance And Odor: NONE SPECIFIED BY MANUFACTURER.
Boiling Point: 212F,100C
Vapor Pressure (MM Hg/70 F): SEE ING 1
Vapor Density (Air=1): LTR/AIR
Specific Gravity: 1.23 (FP N)
Evaporation Rate And Ref: SLOWER THAN ETHER
Percent Volatiles By Volume: 70

Fire and Explosion Hazard Data

Flash Point: NOT APPLICABLE
Lower Explosive Limit: N/A

Extinguishing Media: FOAM, CO*2, DRY CHEMICAL, WATER FOG.
Special Fire Fighting Proc: USE NIOSH/MSHA APPRVD SCBA & FULL PROTECTIVE EQUIP (FP N). WATER MAY BE USED TO COOL CLSD CNTNRS TO PVNT PRESS BUILD UP & EXPLO WHEN EXPOSED TO EXTREME HEAT.
Unusual Fire And Expl Hazrds: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Reactivity Data

Stability: YES
Cond To Avoid (Stability): NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: NONE SPECIFIED BY MANUFACTURER.
Hazardous Decomp Products: NONE SPECIFIED BY MANUFACTURER.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT

Health Hazard Data

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: INHAL:VAPORS OR SPRAY MISTS MAY BE IRRITATING TO EYES, NOSE, THROAT & MUCOUS MEMBRANES OF RESPIRATORY TRACT.
SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. EYE:DIRECT CONTACT W/PAINT WILL RESULT IN IRRITATION.
Carcinogenicity - NTP: YES
Carcinogenicity - IARC: YES
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: SILICA, CRYSTALLINE-QUARTZ:IARC MONOGRAPHS, SUPP, VOL 7, PG 341, 1987:GRP 2A. NTP 7TH ANNUAL RPT ON CARCINS, (SUPP DATA)
Signs/Symptoms Of Overexp: SEE HEALTH HAZARDS.
Med Cond Aggravated By Exp: NONE KNOWN TO TRU-TEST MANUFACTURING COMPANY.
Emergency/First Aid Proc: INHAL:REMOVE TO FRESH AIR. SKIN:REMOVE W/ SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH BEFORE REUSE. EYE:FLUSH IMMEDIATELY W/LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SEE MD FOR MEDICAL TREATMENT. INGEST:GIVE 1-2 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMITING. CALL MD IMMEDIATELY.

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: DIKE & CONTAIN SPILL W/INERT MATERIAL (SAND, EARTH, ETC). TRANSFER LIQUID TO CONTAINERS FOR RECOVERY OR DISPOSAL. KEEP SPILL OUT OF SEWERS & OPEN BODIES OF WATER.
Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.
Waste Disposal Method: LIQUID MATERIAL & CONTAMINATED DIKING MATERIAL SHOULD BE LANDFILLED ACCORDING TO CURRENT LOCAL, STATE & FEDERAL REGULATIONS.
Precautions-Handling/Storing: "KEEP FROM FREEZING". AVOID PROLONGED CONTACT W/SKIN. DO NOT TAKE INTERNALLY.
Other Precautions: NONE SPECIFIED BY MANUFACTURER.

Control Measures

Respiratory Protection: WHEN BRUSHED OR ROLLED NONE REQUIRED IF GOOD VENTILATION MAINTAINED. DURING SPRAY APPLICATION, A NIOSH/MSHA APPROVED MECHANICAL FILTER RESPIRATOR TO REMOVE AIRBORNE PARTICLES OF OVERSPRAY.
Ventilation: SUFFICIENT VENT SHOULD BE PROVIDED TO KEEP AIR CONTAM CONC BELOW CURRENT APPLIC OSHA PEL OR ACGIH TLV LIMITS.
Protective Gloves: IMPERVIOUS GLOVES (FP N).
Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).
Other Protective Equipment: DELUGE SHOWER WHICH MEETS ANSI DESIGN CRITERIA (FP N). EYEWASH FACILITY, PROTECTIVE CLOTHING TO AVOID EXCESSIVE EXPOS.
Work Hygienic Practices: WASH HANDS BEFORE EATING, SMOKING OR USING

WASHROOM.

Suppl. Safety & Health Data: EXPLAN OF CARCIN:1994:ANTICIPATED TO BE
CARCINOGEN.

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES
Technical Review Date: 03AUG95
Label Date: 03AUG95
Label Status: G
Common Name: EASY COLOR PRIMER/SEALER, JLP
Chronic Hazard: YES
Signal Word: WARNING!
Acute Health Hazard-Slight: X
Contact Hazard-Moderate: X
Fire Hazard-None: X
Reactivity Hazard-None: X
Special Hazard Precautions: ACUTE:INHAL:VAPORS OR SPRAY MISTS MAY BE
IRRITATING TO EYES, NOSE, THROAT & MUCOUS MEMBRANES OF RESPIRATORY TRACT.
SKIN:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION. EYE:DIRECT CONTACT
W/PAINT WILL RESULT IN IRRITATION. CHRONIC:CANCER HAZARD. CONTAINS SILICA,
CRYSTALLINE-QUARTZ, WHICH IS LISTED AS AN ANIMAL LUNG CARCINOGEN (FP N).
Protect Eye: Y
Protect Skin: Y
Protect Respiratory: Y
Label Name: TRU-TEST MANUFACTURING CO
Label Street: 201 JANDUS RD
Label City: CARY
Label State: IL
Label Zip Code: 60013
Label Country: US
Label Emergency Number: 800-228-5635