

8-31-05



Lanier Worldwide, Inc.
2300 Parklake Dr., N. E.
Atlanta, GA 30345-2979

Emergency Telephone: (800) 526-4371

MATERIAL SAFETY DATA SHEET

Section 1: Chemical Product and Company Information

Identity:	6745 Black Developer	MSDS No.	CP-667
Product ID:	200-0183	Issued:	7/31/00
Synonyms & Common Names:	Developer, Black Developer	Supersedes:	02/09/1995
Uses:	Lanier 6745, 6735 Copier	Date:	07/31/2000
Chemical Formula:	Mixture	Prepared by:	EH&S Department, 770-496-9500
		Approved by:	Larry Choskey, Manager, CEH&S
		European Contact:	Walter Fricke, Manager, Safety & Environment, Lanier Worldwide, Inc. Im Taubental D-41468 Neuss, Germany +49-2131-387-177

Section 2: Composition / Information on Ingredients

	PERCENT	CAS No.	EXPOSURE LIMITS	SOURCE
Carbon black	0.5	1333-86-4	3.5mg/m ³ / 3.5mg/m ³	OSHA PEL / ACGIH TLV
Styrene acrylate copolymer	5.5	25036-16-2	Not listed	n/a
Iron oxide	94	1317-61-9	10mg/m ³ / 5mg/m ³	OSHA PEL / ACGIH TLV
Zinc oxide		1314-13-2	10mg/m ³ / 10mg/m ³	OSHA PEL / ACGIH TLV
Copper oxide		1317-38-0	Not listed	n/a

*PEL as the product: 15mg/m³ (total dust), 5mg/m³ (respirable dust)
*TLV as the product: 10mg/m³ (total dust), 5mg/m³ (respirable dust)

Section 3: Hazards Identification

Hazard Rating:

FIRE = 0	HEALTH = 0
REACTIVITY = 0	SPECIAL = none

Health Hazards (Acute, Chronic, Immediate and Potential): Minimum irritation to respiratory tract may occur as with exposure to any non-toxic dust. May cause gasping if inhaled. Inhalation should be avoided. May cause temporary eye discomfort.

Health Hazards of Long Term exposure (Chronic): A manufacturer sponsored chronic inhalation study in rats using a special test toner revealed there were no lung changes at all in the lowest exposure level (1mg/m³); the most relevant level to potential human exposures. A very slight degree of fibrosis was noted in 25% of the animals at the middle exposure level (4mg/m³), while a slight degree of fibrosis was observed at the highest exposure level (16mg/m³) in all animals. These findings are attributed to "Lung Overloading", a generic response to excessive amount of any dust retained in the lungs for a prolonged interval. The special test toner was ten times more respirable than commercially available toner to comply with EPA testing protocol and would not function properly in Xerographic equipment.

Section 4: First Aid Measures

Inhalation: Remove to fresh air if effects occur. Consult local medical personnel	Eye Contact: In case of contact, immediately flush eyes with water for 5 minutes.
Skin Contact: Wash with soap and water.	Ingestion: Rinse mouth with water. Call a physician.

MATERIAL SAFETY DATA SHEET

Section 5: Fire Fighting Measures

Suitable extinguishing media: CO2, dry chemical, foam or water.
Extinguishing media which may not be used for safety reasons: none

This material will burn in case of fire. The decomposition products are CO, CO2, and Nox. Avoid inhalation of smoke.
Special protective equipment for fire fighters: none
UEL: n/a LEL: n/a

Section 6: Accidental Release Measures

Sweep up or clean up with an approved toner vacuum.

Section 7: Handling and Storage

Special Handling: None
Special Storage: No special storage requirements for safety reasons. Store in a cool dry place.

Section 8: Exposure Control and Personal Protection Information:

Respiratory Protection: none required under normal use. Hand Protection: none required under normal use.
Eye Protection: none required under normal use. Skin Protection: none required under normal use.

Section 9: Physical and Chemical Properties

CHARACTERISTICS:

Table with 4 columns: Property, Value 1, Value 2, Value 3. Rows include Appearance (Black), Form (Fine powder), Odor (Practically odorless), Solubility in Water (Negligible), Specific gravity (5.6 - 6.8), Melting point (150°C), Vapor pressure (n/a), Vapor density (n/a), Evaporation rate (n/a), Boiling point (n/a).

Section 10: Stability and Reactivity

Conditions to avoid: none Materials to avoid: none Stability: Stable
Hazardous decomposition products: CO, CO2, and NOx when burned.

Section 11: Toxicological Information:

Acute oral toxicity (rat) LD50: Over 5.0 g/kg Ames Test result: Negative
Carcinogenicity: In 1996, the IARC reevaluated carbon black as a GROUP 2B carcinogen (possible human carcinogen). This evaluation is given to carbon black for which there is inadequate human evidence, but sufficient animal evidence. The latter is based upon the development of lung tumors in rats receiving chronic inhalation exposures to free carbon black at a level that induce particle overload of the lungs. Studies performed in mice have not demonstrated an association between carbon black and lung tumors. Moreover, a two-year cancer bioassay using a typical toner preparation containing carbon black demonstrated no association between toner and tumor development in rats.
NTP? = No IARC? = No OSHA Regulated? = No

Section 12: Environmental / Ecological Information

None

Section 13: Disposal Consideration

Waste material may be dumped or incinerated under conditions, which meet all federal, state and local environmental regulations.

Section 14: Transportation Information

None

Section 15: Regulatory Information

None

Section 16: Miscellaneous Information

MATERIAL SAFETY DATA SHEET

Page 3 of CP-667

On the basis of the data available to us, this developer is not a dangerous substance. One should, however, observe the usual precautionary measures for dealing with chemicals.