

DESOTO, INC.
MATERIAL SAFETY DATA SHEET

SECTION I

DESOTO, INC.
ADMINISTRATIVE AND RESEARCH CENTER

1700 S. MT. PROSPECT RD (BOX 5030)
DES PLAINES, ILLINOIS 60017

EMERGENCY TELEPHONE (312) 391-9000

CHEMTREC (800) 424-9300

PRODUCT CLASS

AEROSOL

MANUFACTURERS CODE IDENTIFICATION

6EA LINE

THIS LINE INCLUDES: 6EA00 (FLAT WHITE); 6EA32 (FLAT BLACK); 6EA33 (GLOSS BLACK); 6EA34 (GLOSS WHITE); 6EA35 (GREEN); 6EA36 (RED); 6EA37 (BLUE); 6EA40 (ORANGE); 6EA42 (YELLOW); 6EA44 (ALUMINUM); 6EA46 (GOLD); 6EA48 (CLEAR) 6EA49 (PRIMER) 6EA64 (BROWN)

TRADE NAME ALKYD ENAMEL SPRAY
PAINT

DATE OF PREPARATION 06/03/88

*****SECTION II-HAZARDOUS INGREDIENTS*****

INGREDIENT [CAS NUMBER]	% BY* WEIGHT	OSHA PEL-PPM	ACGIH TLV-PPM	LEL	VAPOR PRESSURE @ 20 DEG C
VM & P NAPHTHA [8030-30-6]	10.0	500	300	1.0	7.0
XYLENE [1330-20-7]	<5-10	100	100	1.1	10
TOLUENE [108-88-3]	0-30	200	100	1.2	35
ACETONE [67-64-1]	20-50	1,000	750	2.6	210
AROMATIC SOLVENT [64742-95-6]	< 5.0	NE	NE	1.0	3.0
PROPANE/BUTANE 50/50 BLEND	35.0	1,000	1,000 AS PROPANE	2.1	GAS

THIS PAINT MAY ALSO CONTAIN FILLERS SUCH AS TALC AND PIGMENTS SUCH AS TITANIUM DIOXIDE AND IRON OXIDE WHICH ARE NOT CONSIDERED HAZARDOUS IN PAINT.

* PERCENT BY WEIGHT:
TO NEAREST 5% FOR SUBSTANCES 5-95%;
<5.0 FOR SUBSTANCES 1.0-5.0%;

S=SKIN; C=CEILING LIMIT
NE = NOT ESTABLISHED
NA = NOT APPLICABLE

*****SECTION III-PHYSICAL DATA*****

PROPERTY	MEASUREMENT
BOILING RANGE @ 760 MM HG	-44.0 TO 308.0 DEG F. -42.0 TO 153.0 DEG C.
VAPOR DENSITY	(X) HEAVIER () LIGHTER THAN AIR
WEIGHT PER GALLON	7-8 LBS.
PERCENT VOLATILE BY VOLUME	91-93
EVAPORATION RATE	() FASTER (X) SLOWER THAN ETHER
APPEARANCE AND ODOR	LIQUID, SOLVENT ODOR

*****SECTION IV-FIRE AND EXPLOSION DATA*****

DOT CATEGORY FLAMMABLE LIQUID FLASH POINT <20.0 DEG F.

OSHA CATEGORY FLAMMABLE LIQUID-CLASS I A (CLOSED CUP) <-6.7 DEG C.

LOWER EXPLOSIVE LIMIT (LEL): SEE SECTION II

EXTINGUISHING MEDIA: USE NATIONAL FIRE PROTECTION ASSOCIATION CLASS B
EXTINGUISHERS (CARBON DIOXIDE, DRY CHEMICAL OR FOAM).

UNUSUAL FIRE AND EXPLOSION HAZARDS: VAPORS MAY ACCUMULATE IN INADEQUATELY VENTILATED OR CONFINED AREAS. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS MAY TRAVEL LONG DISTANCES. FLASHBACK OF FLAME TO THE HANDLING SITE MAY OCCUR. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

SPECIAL FIRE FIGHTING PROCEDURES: WATER SPRAY MAY BE INEFFECTIVE. COOL FIRE EXPOSED CONTAINERS WITH WATER. FOG NOZZLES ARE PREFERRABLE. WEAR NIOSH/MSHA APPROVED SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN AND EYES.

*****SECTION-V REACTIVITY DATA*****

STABILITY: () UNSTABLE (X) STABLE

INCOMPATIBILITY (MATERIALS TO AVOID):
NONE RECOGNIZED.

HAZARDOUS DECOMPOSITION PRODUCTS: PRODUCTS OF COMBUSTION ARE HAZARDOUS.

HAZARDOUS POLYMERIZATION: () MAY OCCUR (X) WILL NOT OCCUR

CONDITIONS TO AVOID:
NONE RECOGNIZED.

*****SECTION VI-WASTE DISPOSAL AND ENVIRONMENTAL RELEASES*****

ENVIRONMENTAL RELEASES: DEPENDING ON THE QUANTITY AND CIRCUMSTANCES, AN UNAUTHORIZED RELEASE OF THIS MATERIAL TO THE ENVIRONMENT MAY BE REPORTABLE UNDER FEDERAL LAW TO THE NATIONAL RESPONSE CENTER (800-424-8802). STATE AND LOCAL GOVERNMENTS MAY ALSO HAVE REPORTING REQUIREMENTS OF WHICH YOU SHOULD BE AWARE.

REMOVE ALL SOURCES OF IGNITION. WEAR PERSONAL PROTECTIVE EQUIPMENT TO AVOID BREATHING VAPORS AND SKIN AND EYE CONTACT WITH THE SPILLED MATERIAL. USE NON-SPARKING TOOLS. FOR SMALL SPILLS, DIKE AND ABSORB WITH INERT MATERIAL. USE EMERGENCY RESPONSE PROFESSIONALS IF MANAGING A RELEASE IS BEYOND THE CAPABILITY OF IN-HOUSE PERSONNEL.

WASTE DISPOSAL: THIS MATERIAL IS CLASSIFIED AS AN IGNITABLE HAZARDOUS WASTE. WHEN AFFECTING ITS DISPOSAL, INSURE THAT IT IS PACKAGED, STORED, TRANSPORTED AND OTHERWISE MANAGED IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL HAZARDOUS WASTE LAWS AND REGULATIONS. NO DISPOSAL METHOD IS TO USED WHICH WOULD POSE AN ENVIRONMENTAL OR HUMAN HEALTH THREAT, INCLUDING ANY WHICH WOULD CONTAMINATE GROUND OR SURFACE WATERS.

*****SECTION VII-HEALTH HAZARD DATA*****

THRESHOLD LIMIT VALUE: SEE SECTION II (NOT ESTABLISHED FOR PRODUCT)

EFFECTS OF OVEREXPOSURE:

INHALATION:

EXPOSURE MAY CAUSE NASAL AND RESPIRATORY IRRITATION AND ACUTE CENTRAL NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION OR UNCONSCIOUSNESS. ASPHYXIATION MAY RESULT FROM BREATHING OXYGEN DEFICIENT AIR.

SKIN CONTACT:

PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION, DEFATTING OR DERMATITIS.

EYE CONTACT:

PRIMARY IRRITATION.

INGESTION:

MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING AND DIARRHEA.

OTHER HEALTH EFFECTS: REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. EFFECTS INCLUDE CONCENTRATION DIFFICULTIES, DIMINISHED MANUAL DEXTERITY AND MEMORY LOSS.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION:

REMOVE FROM EXPOSURE TO FRESH AIR. GIVE ARTIFICIAL RESPIRATION OR CARDIOPULMONARY RESUSCITATION (CPR) IF REQUIRED. IF BREATHING IS DIFFICULT, GIVE OXYGEN. KEEP WARM AND QUIET. GET MEDICAL ATTENTION.

SKIN CONTACT:

WASH AFFECTED AREAS WITH SOAP AND WATER. DO NOT USE SOLVENTS.

REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REUSE. GET MEDICAL ATTENTION.

EYE CONTACT:

FLUSH WITH WATER FOR 15 MINUTES. GET MEDICAL ATTENTION.

INGESTION:

GET MEDICAL ATTENTION.

*****SECTION VIII-SPECIAL PROTECTION INFORMATION*****

RESPIRATORY PROTECTION: IN AREAS WHERE TLVS IN SECTION II MAY BE EXCEEDED OR IF SPRAY MIST IS PRESENT, USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION APPROPRIATE FOR INDICATED COMPONENTS. IN CONFINED AREAS USE NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATORS. FOLLOW RESPIRATOR MANUFACTURERS DIRECTIONS AND OSHA REGULATIONS (29 CFR 1910.134) FOR RESPIRATOR USE.

VENTILATION: WHERE EMPLOYEES MAY BE EXPOSED, PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOLUME AND PATTERN TO KEEP LEVEL OF HAZARDOUS INGREDIENTS IN SECTION II BELOW RECOMMENDED (ACGIH TLV) OR REGULATED (OSHA PEL) LIMIT. WHERE EMPLOYEES WILL NOT BE EXPOSED, KEEP LEVEL BELOW 25% OF LEL IN SECTION II.

PROTECTIVE GLOVES: WEAR CHEMICALLY RESISTANT GLOVES.

EYE PROTECTION: SAFETY GLASSES WITH SIDE SHIELDS OR GOGGLES

OTHER PROTECTIVE EQUIPMENT: AVOID SKIN CONTACT BY USE OF OTHER PROTECTIVE CLOTHING. A SAFETY SHOWER, AN EYE BATH AND WASHING FACILITIES SHOULD BE AVAILABLE.

*****SECTION IX-SPECIAL PRECAUTIONS*****

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
KEEP CONTAINER TIGHTLY CLOSED. KEEP AWAY FROM HEAT, SPARKS AND FLAME.

OTHER PRECAUTIONS:

EMPTY DRUMS MAY CONTAIN EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE OR WELD ON OR NEAR DRUM.

DO NOT TAKE INTERNALLY. DO NOT DELIBERATELY CONCENTRATE THIS PRODUCT AND INHALE THE VAPORS. PREVENT PROLONGED CONTACT WITH CONTAMINATED CLOTHING WASH CONTAMINATED CLOTHING BEFORE REUSE.

VAPORS OF THIS PRODUCT ARE HEAVIER THAN AIR AND MAY COLLECT IN LOW OR CONFINED AREAS. DO NOT ENTER SUCH AREAS WITH FOLLOWING APPROPRIATE PROCEDURES INCLUDING AIR MONITORING, USE OF SUPPLIED AIR IF NECESSARY AND THE PRESENCE OF AN OBSERVER FOR ASSISTANCE.

DO NOT SAND, FLAME CUT, BRAZE OR WELD THE DRY COATING WITHOUT NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

OBSERVE PRECAUTIONARY LABEL WARNINGS.

PREPARED BY S. M. STEVENSON
TECHNICAL INFORMATION SPECIALIST