72-62-7920-D1

## Ashland Chemical Company

DIVISION OF ASHLAND OIL, INC.

MATERIAL SAFETY

P. O. BOX 2219, COLUMBUS, OHIO 43218 • (614) 889-3333



**DATA SHEET** 

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

000042	AMMONIUM (	CHLORIDE UN	FREATED	PAGE: 1
THIS MSDS COMPLIES	WITH 29 CFR 1918.	1200 (THE	HAZARD COMMUNI	CATION STANDARD)
<b>张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张张</b>				
PRODUCT NAME: AMMONIUM CAS NUMBER: HAYS REPUBLIC ATIN: FRANK LES 225 N. ROESKE AV	CHLORIDE UNTREATION 12125 02 9 ENER	TED 0! D/ L/ PI	5 86 871 411 ATA SHEET NO:	2557-484 0004554-004 DATE: 03/86-86063
MICHIGAN CITY, I	N 46360	I	NVOICE DATE: D	7/14/86
		Т.	D:	
SECTION I-PRODUCT IDENTIFICATION				
GENERAL OR GENERIC ID: SALTS				
DOT HAZARD CLASSIFICATION: NOT APPLICABLE				
SECTION II-COMPONENTS				
		PEL	TLV	NOTE
INGREDIENT	N (BY WT)			1111
AMMONIUM CHLORIDE	>95		10 MG/M	3 ( 1)
CAS #: 12125-02-9				
( 1): AS FUMES			•	,
PEL NOT ESTABLISHED FOR THIS MATERIAL				
• .		•		
SECTION III-PHYSICAL DATA				
		EFINEMENT		MEASUREMENT
PROPERTY	2			
BOILING POINT	NOT APPLICABLE	•		
VAPOR PRESSURE	NOT APPLICABLE			
	NOT APPLICABLE			
SPECIFIC VAPOR DENSITY				1.530
SPECIFIC GRAVITY				9 68.00 DEG F ( 20.00 DEG C)
PERCENT VOLATILES	NOT APPLICABLE			
EVAPORATION RATE	NOT APPLICABLE	٠		
SECTION IV-FIRE AND EXPLOSION INFORMATION				
FLASH POINT NOT APPLIC	ABLE			
EXPLOSIVE LIMIT	NOT APPLICABLE			
EXTINGUISHING MEDIA: WATER FOG				
NFPA CODES: HEALTH		LITY- B	REACTIVITY- D	•
SECTION V-HEALTH HAZARD DATA				
THRESHOLD LIMIT VALUE	1 D	мб/мз		
NOT ESTABLISHED.				
EFFECTS OF ACUTE OVEREXPOSURE: FOR PRODUCT				
EYES - CAN CAUSE MODERATE IRRITATION, REDNESS, TEARING. SKIN - PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS. BREATHING - OF DUST CAN CAUSE IRRITATION OF NASAL AND RESPIRATORY PASSAGES. SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA.				
FIRST AID:				
CLOTHING. LAUNDER CONTAMINATED CLOTHING BEFORE RE-USE.  IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS				
IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.				

IF SWALLOWED: DO NOT INDUCE VOMITING. VOMITING WILL CAUSE FURTHER DAMAGE TO THE THROAT. DILUTE BY GIVING WATER. GIVE MILK OF MAGNESIA. KEEP WARM, QUIET. GET MEDICAL ATTENTION IMMEDIATELY.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

72-62-7920-01

## Ashland Chemical Company

DIVISION OF ASHLAND OIL, INC.

MATERIAL SAFETY
DATA SHEET

P. O. BOX 2219, COLUMBUS, OHIO 43216 • (614) 889-3333 24-HOUR EMERGENCY TELEPHONE (606) 324-1133



AMMONTUM CHLORIDE UNTREATED 000042 SECTION V-HEALTH HAZARD DATA (CONTINUED) PRIMARY ROUTE(S) OF ENTRY: INHALATION SKIN CONTACT SECTION VI-REACTIVITY DATA HAZARDOUS POLYMERIZATION: CANNOT OCCUR STABILITY: STABLE INCOMPATIBILITY: AVOID CONTACT WITH:, STRONG ALKALIES. SECTION VII-SPILL OR LEAK PROCEDURES STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SMALL SPILL: COVER WITH SODA ASH. MIX AND SCOOP INTO A BEAKER OF WATER. LARGE SPILL: COLLECT AND ADD SLOWLY TO LARGE VOLUME OF WATER. WASTE DISPOSAL METHOD: SMALL SPILL: DISSOLVE IN LARGE AMOUNT OF WATER AND ADD SODA ASH. NEUTRALIZE WITH 6M-HYDROCHLORIC ACID. FLUSH DOWN DRAIN WITH EXCESS WATER IN ACCORDANCE WITH APPLICABLE REGULATIONS. SPILL: COLLECT AND ADD TO LARGE CONTAINER OF WATER. STIR IN SLIGHT EXCESS OF SODA ASH. LET STAND 24 HOURS. DECANT INTO ANOTHER CONTAINER, NEUTRALIZE WITH 6M-HYDROCHLORIC ACID. FLUSH DOWN DRAIN WITH LARGE EXCESS OF WATER IN ACCORDANCE WITH APPLICABLE REGULATIONS. DEPOSIT SLUDGE IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED RESPIRATORY PROTECTION: IF NEEDED USE A NIOSH/MSHA JOINTLY APPROVED DUST RESPIRATOR.(ASK YOUR SAFETY EQUIPMENT SUPPLIER) VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S). PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS:, NEOPRENE EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER) OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS. SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED.SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED. THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.