

# ZROCK. MATERIAL SAFETY DATA SHEET MAY 2 3 1994

Product: AZROCK CLEAR THIN SPREAD

ADHESIVE

Internal ID: F6071, F6074 & F6306

Distributor: Azrock Industries Inc.

P.O. Box 696060

San Antonio, Texas 78269-6060

MSDS No: 700

Revision:

Date: January 1994

National Paint and Coating Association

Hazardous Material Identification System

HEALTH HAZARD	. 0
FLAMMABILITY HAZARD	0
REACTIVITY HAZARD	0
PERSONAL PROTECTION	В

### SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name:

AZROCK CLEAR THIN SPREAD ADHESIVE

Description: Adhesive

CAS: N/A

Shipping Name (49 CFR 172.101):

D.O.T. ID No. (49 CFR 172.101):

D.O.T. Hazard Class: N/A D.O.T. label required (49 CFR 172.101): N/A

EPA Hazard Class - if discarded (40 CFR 261): N/A

FOR 24 HOUR MEDICAL AND DOT EMERGENCY RESPONSE COMMUNICATIONS AND INFORMATION, PLEASE CALL 1-800-228-5635 Extension 079.

For installation and customer service information, please call 512-558-6400 between 8:00 AM and 5:00 PM CST Monday through Friday, except holidays.

#### SECTION II. INGREDIENTS AND HAZARDS

Ingredient Name:

CAS Number:

N/A

N/A

Percent:

Exposure Limits:

Water

7732-18-5

N/E

Petroleum Distillates

64742-89-8

1-5%

ACGIH 92-93: TWA, 300ppm

NJTSRN 80100364-5040P NJTSRN 80100364-5041P

NJTSRN 80100364-5042P

## MATERIAL SAFETY DATA SHEET

Distributor: Azrock Industries Inc. P.O. Box 696060 San Antonio, Texas 78269-6060 Product: AZROCK CLEAR THIN SPREAD

ADHESIVE

Internal ID: F6071, F6074 & F6306

MSDS No: 700

Revision:

Date: January 1994

#### PHYSICAL DATA SECTION III.

Appearance & Odor: Beige paste - Slight wood odor

Boiling point:> 200°F

Evaporation rate:

Vapor pressure: N/A Water solubility (%): Soluble Specific gravity (H20=1): 1.0 % volatile by volume: approx. 50.0%

Vapor density (air=1): N/A

VOC less water less exempt solvent (g/liter):

111.5 g/l

VOC material (g/liter): 63.6 g/l

#### FIRE AND EXPLOSION DATA SECTION IV.

Flash Point (method): N/A

LEL: N/A

N/A TIRL %:

Extinguishing Media: Foam, CO2, chemical and/or water spray

Unusual fire or explosion hazards: Can produce carbon monoxide and dioxide, formaldhehyde

and other unidentified organic products.

Complete protection equipment including a self-Special fire-fighting procedures:

contained breathing apparatus.

#### REACTIVITY DATA SECTION V.

None known Chemical incompatibilities:

Conditions to avoid: None known

Hazardous decomposition Products: None known

#### HEALTH HAZARD INFORMATION SECTION VI.

Medical conditions which may be aggravated by contact: None

Primary entry route(s): Inhalation, ingestion

Acute effects: None known

Prolonged exposure to high concentration of vapors may effect the Chronic effect(s): nervous system.

## MATERIAL SAFETY DATA SHEET

nistributor: Azrock Industries Inc. P.O. Box 696060 San Antonio, Texas 78269-6060 Product: AZROCK CLEAR THIN SPREAD

ADHESIVE

F6071, F6074 & F6306 Internal ID:

MSDS No: 700 Revision:

Date: January 1994

# HEALTH HAZARD INFORMATION continued from page 2

First aid:

Flush with large amounts of water for at least 20 minutes while Eye contact:

holding eyelids open. Get medical attention.

Wash with soap and water. Remove contaminated clothes. Get medical Skin contact:

attention if irritation shows.

Move to fresh air. Give artificial respiration if not breathing. Inhalation:

Get immediate medical attention.

Do not induce vomiting. Get immediate medical attention. Ingestion:

## SPILL, LEAK AND DISPOSAL PROCEDURES SECTION VII.

Contain by diking with soil or Spill / Leak procedures: Wear protective equipment. other non combustible absorbant materials and put into a DOT approved waste container.

Waste management / Disposal: Dispose in accordance with federal, state and local environmental regulations.

### SPECIAL PROTECTION INFORMATION SECTION VIII.

Personal protective equipment:

Goggles: Safety glasses are required

Impervious gloves Gloves:

Not required when used in a well ventilated area. If not, use an approved Respirator:

mask with cartridges for organic vapors is recommended.

Workplace considerations:

Use in a well ventilated area Ventilation:

Safety station is recommended, also be sure to have a firt aid worker Safety stations:

state and local in accordance with federal, Contaminated equipment: Dispose environmental regulations.

## MATERIAL SAFETY DATA SHEET

Distributor: Azrock Industries Inc. P.O. Box 696060 San Antonio, Texas 78269-6060 Product: AZROCK CLEAR THIN SPREAD

ADHESIVE

Internal ID: F6071, F6074 & F6306

MSDS No: 700 Revision:

Date: January 1994

## SECTION IX. SPECIAL PRECAUTIONS

Storage segregation:

Store away from incompatible materials.

Special handling / storage: Store at room temperature. Do not refrigerate. Other precautions: Freeze-thaw stable to 0°F.

DOT Class: See Section I.

This data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.