



MATERIAL SAFETY DATA SHEET

Product: AZROCK LUXURY VINYL TILE
ADHESIVE

Internal ID: F6021 and F6023

Distributor:
Azrock Industries Inc.
P.O. Box 696060
San Antonio, Texas 78269-6060

MSDS No: MD919
Revision: 1
Date: January 21, 1991

National Paint
and Coating
Association

Hazardous Material
Identification
System

HEALTH HAZARD	1 - Slight
FLAMMABILITY HAZARD	0 - Minimal
REACTIVITY HAZARD	2 - Moderate
PERSONAL PROTECTION	B - Gloves, Glasses

SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name: AZROCK LUXURY VINYL TILE ADHESIVE

Description: Synthetic Rubber, Poly Vinyl Acetate Emulsion

CAS:

Shipping Name (49 CFR 172.101): Adhesive, Combustible Liquid

D.O.T. ID No. (49 CFR 172.101): UN 1133

D.O.T. Hazard Class: Combustible

D.O.T. label required (49 CFR 172.101): NA

EPA Hazard Class - if discarded (40 CFR 261): NA

FOR 24 HOUR MEDICAL AND DOT
EMERGENCY RESPONSE COMMUNICATIONS
AND INFORMATION, PLEASE CALL
1-800-228-5635 Extension 079.

For installation and customer
service information, please call
512-558-6400 between 8:00 AM and
5:00 PM CST Monday through Friday,
except holidays.

SECTION II. INGREDIENTS AND HAZARDS

Ingredient Name:	CAS Number:	Percent:	Exposure Limits:
Toluene	108-88-3	<2	200 ppm OSHA PEL 100 ppm ACGIH TLV
Mineral Spirits	64742-88-7	<6	500 ppm OSHA PEL 100 ppm ACGIH TLV
Vinyl Acetate Monomer	108-05-4	< 0.2	20 ppm OSHA PEL 10 ppm ACGIH TLV

* These materials are subject to the reporting requirements under the Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III, Section 313 and CFR 372.

MATERIAL SAFETY DATA SHEET

Distributor:
Azrock Industries Inc.
P.O. Box 696060
San Antonio, Texas 78269-6060

Product: AZROCK LUXURY VINYL TILE
ADHESIVE

Internal ID: F6021 and F6023

MSDS No: MD919
Revision: 1
Date: January 21, 1991

SECTION III. PHYSICAL DATA

Appearance & Odor: White Paste with Mild Latex Odor.

Boiling point: 181°F
Evaporation rate: 1
Vapor pressure: Not known
Specific gravity (H₂O=1): 1.1
Water solubility (%): Completely Miscible
% volatile by volume: 44-48
Vapor density (air=1):

VOC less water less exempt solvent (g/liter): 199 g/L
VOC material (g/liter): 99 g/L

SECTION IV. FIRE AND EXPLOSION DATA

Flash Point (method): 100°F (SETA CC) Limits: NA UEL %: NA

Extinguishing Media: Foam, Chemical Foam, CO₂, Dry Chemical, Water Fog

Unusual fire or explosion hazards:

Special fire-fighting procedures: Wear self contained breathing gear when in confined area.

SECTION V. REACTIVITY DATA

Material is stable Hazardous Polymerization will not occur

Chemical incompatibilities: None known

Conditions to avoid: Excessive heat or cold

Hazardous Decomposition Products: When totally dry, may produce CO, H₂O, CO₂, and NXO from burning aromatic hydrocarbons.

SECTION VI. HEALTH HAZARD INFORMATION

Medical conditions which may be aggravated by contact:

Primary entry route(s):

Acute effects: May cause slight irritations to the eyes and skin. Inhalation of extremely high concentrations may asphyxiate.

Chronic effect(s):

MATERIAL SAFETY DATA SHEET

Distributor:
Azrock Industries Inc.
P.O. Box 696060
San Antonio, Texas 78269-6060

Product: AZROCK LUXURY VINYL TILE
ADHESIVE

Internal ID: F6021 and F6023

MSDS No: MD919
Revision: 1
Date: January 21, 1991

HEALTH HAZARD INFORMATION continued from page 2

First aid:

- Eye contact: Flush eyes with cold water for 10 to 15 minutes. If irritation continues, consult a physician.
- Skin contact: Wash skin with soap and water or hand cleaner. If irritation continues, consult a physician.
- Inhalation: Remove to fresh air, administer artificial respiration if necessary.
- Ingestion: Do not induce vomiting. Call a physician immediately.

SECTION VII. SPILL, LEAK AND DISPOSAL PROCEDURES

Spill / Leak procedures: Scoop into container and allow to dry. Provide adequate ventilation.

Waste management / Disposal: Dispose of in accordance with all local, state, and federal regulations.

SECTION VIII. SPECIAL PROTECTION INFORMATION

Personal protective equipment:

- Goggles: Protective goggles should be worn.
- Gloves: Rubber gloves should be worn.
- Respirator: Not required if ventilation is adequate.

Workplace considerations:

Ventilation: Maintain local ventilation by opening windows or using electric fan.

Safety stations:

Contaminated equipment: Use soap and water for clean up.

MATERIAL SAFETY DATA SHEET

Distributor:

Azrock Industries Inc.
P.O. Box 696060
San Antonio, Texas 78269-6060

Product: AZROCK LUXURY VINYL TILE
ADHESIVE

Internal ID: F6021 and F6023

MSDS No: MD919

Revision: 1

Date: January 21, 1991

SECTION IX. SPECIAL PRECAUTIONS

Storage segregation:

Special handling / storage: Store inside at temperature of 60°F - 80°F. Keep container closed when not in use.

Other precautions:

DOT Class: See Section I

This data is offered in good faith as typical values and not as a product specification. No warranty, either express or implied is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.