


VIII STORAGE AND HANDLING PRECAUTIONS													
<p>AEROSOL CONTAINER: Do NOT store in direct sunlight, near open flames, or at temperatures exceeding 120°F. Do NOT smoke while spraying. Use only as directed. Intentional misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.</p>													
IX SPILL LEAK AND DISPOSAL PRACTICES													
<p>STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED</p> <p>Ventilate area. Remove all sources of ignition. Clean up with inert materials and dispose of in accordance with all Local, State and Federal regulations.</p>													
WASTE DISPOSAL METHOD													
<p>AEROSOL CONTAINER: Do NOT puncture or incinerate. Empty containers may be disposed of through normal channels. Full or partially filled containers are considered HAZARDOUS WASTE.</p>													
X TRANSPORTATION													
<p>DOT HAZARD CLASSIFICATION</p> <p>ORM-D</p>	<p>SECTION 313 SUPPLIER NOTIFICATION This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372:</p> <table border="1"> <thead> <tr> <th>CAS #</th> <th>Chemical Name</th> <th>Percent by Weight</th> </tr> </thead> <tbody> <tr> <td>108-88-3</td> <td>Toluene</td> <td>8.0</td> </tr> <tr> <td>67-64-1</td> <td>Acetone</td> <td>39.0</td> </tr> <tr> <td>1330-20-7</td> <td>Xylene</td> <td>10.6</td> </tr> </tbody> </table> <p>This information must be included in all MSDSs that are copied and distributed for this material.</p>	CAS #	Chemical Name	Percent by Weight	108-88-3	Toluene	8.0	67-64-1	Acetone	39.0	1330-20-7	Xylene	10.6
CAS #		Chemical Name	Percent by Weight										
108-88-3		Toluene	8.0										
67-64-1		Acetone	39.0										
1330-20-7		Xylene	10.6										
<p>PLACARD REQUIRED</p> <p>None</p>													
<p>LABEL REQUIRED</p> <p>ORM-D</p>													
<p>NAME (print) PETER M. JANKOWSKI</p>													
<p>SIGNATURE </p>													
<p>TITLE TECHNICAL SERVICE CHEMIST</p>													
<p>DATE OF LAST REVISION May 12, 1992</p>													

A HAZARDOUS INGREDIENT IS ONE WHICH MEETS ONE OR MORE OF THE FOLLOWING CRITERIA:

- It is listed in the annual registry of toxic effects of chemical substances, or is known to be toxic within the parameters of that registry, and is present at a level of 1% or greater of the composition, except that chemicals identified as carcinogens under 29 CFR 1910.1200 (d) (4) shall be listed if the concentrations are 0.1% or greater.
- It has an OSHA established Permissible Exposure Limits or Ceiling Concentration (C) or an American Conference of Governmental Industrial Hygienists' (ACGIH) TLV or, C, and by the nature of the product or its known use, is likely to become airborne.
- It contributes to one or more of the following hazards to the product: A - Flashpoint below 200° F. (CC), or subject to spontaneous heating or decomposition; B - Causes skin burns (DOT); C - Strong oxidizing agent (DOT); D - Subject to hazardous polymerization.

Each hazardous ingredient should be listed by chemical, generic or proprietary name, its level in the product should be expressed as 1% or less, 1-10%, 11-30%, 31-50%, 51-70%, or greater than 70%, or by other means if such information is proprietary. Recommended ACGIH or registry of toxic effects of chemical substances TLV or C values are only listed with appropriate notation, where OSHA values are not available.




North American Professional Products
1500 McCannell Road, Woodstock, Illinois 60090-7310
Telephone 1-800-766-7655

HAZARD RATING

- 4 = Extreme
- 3 = High
- 2 = Moderate
- 1 = Slight
- 0 = Insignificant

HEALTH



REACTIVITY

SPECIFIC HAZARD

EMERGENCY NUMBER 1-800-255-3924 I IDENTIFICATION						
CHEMICAL NAME Mixture			FORMULATION NUMBER E-112 / 99-2004			
TRADE NAME & PRODUCT NUMBER Battery Terminal Coating #6005			DOT IDENTIFICATION NUMBER UN-1950			
SYNONYMS NA						
II PRODUCT AND COMPONENT DATA						
COMPONENT(S) CHEMICAL NAME	CAS REGISTRY NO.	% (APPROX.)	ACGIH-TLV TWA (ppm)	STEL	OSHA PEL (ppm)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(Z)
Acetone	67-64-1	31-50	750	-	750	No
Propane	74-98-6	11-30	Not Listed		1000	No
Isobutane	75-28-5	1-10	Not Listed	Not Established		No
Xylene	1330-20-7	1-10	100	150	100	No
Propylene Glycol Methyl Ether Acetate	108-65-6	1-10		Not Established		No
III PHYSICAL DATA						
APPEARANCE AND ODOR Yellow / Ketone Odor			SPECIFIC GRAVITY < 1			
BOILING POINT NA			VAPOR DENSITY IN AIR > 1			
VAPOR PRESSURE Aerosol Container @ 70°F 55-65 psig			% VOLATILE BY VOLUME > 80%			
EVAPORATION RATE (Ether = 1) < 1			SOLUBILITY IN WATER Neg.			
IV REACTIVITY DATA						
STABILITY Stable			CONDITIONS TO AVOID Open flames, sparks, electrical spark sources.			
INCOMPATIBILITY (materials to avoid) Strong oxidizing agents, strong acids or bases.						
HAZARDOUS DECOMPOSITION PRODUCTS Thermal decomposition may yield carbon monoxide and other toxic chemicals.						
HAZARDOUS POLYMERIZATION Will not occur.						

<u>V FIRE AND EXPLOSION HAZARD DATA</u>			
<u>FLASH POINT (Method used)</u> Aerosol -50°F T.C.C.	<u>FLAMMABLE LIMITS IN AIR</u>	<u>LEL</u> 1	<u>UEL</u> 15
<u>EXTINGUISHING AGENTS</u> Carbon dioxide, dry chemical, foam.			
<u>UNUSUAL FIRE AND EXPLOSION HAZARDS</u> Treat as cylinders of compressed gas. Firefighters should use a self-contained positive pressure breathing apparatus.			
<u>VI TOXICITY AND FIRST AID</u>			
<u>EXPOSURE LIMITS:</u> See Section II for exposure limits of each individual component.			
<u>MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE</u> Not established.			
<u>ACUTE TOXICITY:</u>			
<u>INHALATION:</u>	High vapor concentrations may result in dizziness, headaches, or unconsciousness.		
<u>INGESTION:</u>	Not likely.		
<u>EYE CONTACT:</u>	May cause irritation.		
<u>SKIN CONTACT:</u>	Prolonged contact will cause defatting of the skin leading to irritation and dermatitis.		
<u>SKIN ABSORPTION:</u>	Not likely to be absorbed in toxic amounts.		
<u>FIRST AID</u>	CALL A PHYSICIAN OR A POISON CONTROL CENTRE.		
<u>EYES:</u>	Flush with water for 15 minutes or until irritation subsides.		
<u>SKIN:</u>	Remove all contaminated clothing. Wash skin with soap and water.		
<u>INHALATION:</u>	Remove from exposure immediately. If breathing is stopped or irregular, begin artificial respiration and administer oxygen.		
<u>INGESTION:</u>	Do NOT induce vomiting. Drink plenty of water.		

<u>CHRONIC TOXICITY</u>	
<u>CARCINOGENICITY:</u>	None Known.
<u>TERATOGENICITY:</u>	Not Established.
<u>MUTAGENICITY:</u>	Not Established.
<u>TARGET ORGAN AFFECTED:</u>	Prolonged exposure above the OSHA permissible exposure limits may result in kidney and liver damage.
<u>VII PERSONAL PROTECTION AND CONTROLS:</u>	
<u>RESPIRATORY PROTECTION</u> Respiratory protection program should be in accordance with 29 CFR 1910.134.	
<u>VENTILATION</u> Local exhaust is adequate.	
<u>SKIN PROTECTION</u> Gloves: Polyethylene or Neoprene.	
<u>EYE PROTECTION</u> Safety glasses are recommended.	
<u>HYGIENE</u> Wash skin with soap and water.	
<u>OTHER CONTROL MEASURES</u> Protective clothing and equipment: See 29 CFR 1910. 133 & 132.	

NOTICE FROM NORTH AMERICAN PROFESSIONAL PRODUCTS

The information on this material safety data sheet is provided by NORTH AMERICAN PROFESSIONAL PRODUCTS free of charge. While believed to be reliable, it is intended for use by skilled persons at their own risk. NORTH AMERICAN PROFESSIONAL PRODUCTS assumes no responsibility for events resulting or damages incurred from its use. The information on this material safety data sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.