MATERIAL SAFETY DATA SHEET

Section 1: Product & Company Identification

Product Name:

Battery Terminal Protector

Product Number (s): 05046

Manufactured By:

CRC Industries, Inc.

(215) 674-4300

885 Louis Drive, Warminster, PA 18974

24-Hour Emergency Information: CHEMTREC

(800) 424-9300

Section 2: Composition/Information on Ingredients

| Component | CAS NUMBER | ACGIH TLV | OSHA PEL | OTHER LIMITS | % |
|--|--|---|--|--|--|
| Inhibited Paraffinic Oil Microcrystaline Wax Xylene Petroleum Distillate Isohexanes n-Hexane Heptane Ethylbenzene Hydrocarbon propellant | Mixture 8009-03-8 1330-20-7 8052-41-3 107-83-5 110-54-3 142-82-5 100-41-4 68476-86-8 | 5 mg/m3 NE 100 ppm NE 500 ppm 50 ppm 400 ppm 100 ppm NE | 5 mg/m3 5 mg/m3 100 ppm NE 500 ppm 50 ppm 400 ppm 100 ppm | (mist) NE NE 100 ppm NE NE NE NE NE NE NE NE NE 1000 ppm | 10-20 15-35 < 10 10-20 30-50 < 10 < 10 < 2 25-35 |
| | | | | | |

Section 3: Hazards Identification

Emergency Overview

Appearance & Odor: Red viscous liquid.

Danger: Extremely Flammable. Harmful or Fatal if Swallowed. Contents Under Pressure.

Potential Health Effects:

Inhalation:

Headaches, dizziness, nausea and anesthesia.

Eyes:

Irritation, burning

Skin:

Irritation, drying

Ingestion:

Gastrointestinal discomfort

Carcinogenicity:

OSHA:

IARC:

Yes

NTP:

No

Chronic Overexposure:

No

Dermatitis

Medical Conditions Aggravated by Exposure:

Section 4: First Aid Measures

Inhalation:

Remove to fresh air. Give artificial respiration if necessary.

Eyes:

Flush with large amounts of water for 15 minutes.

Page 1 of 4

Product Name: Battery Terminal Protector

Product Number (s): 05046

Skin:

Remove contaminated clothing and wash area with soap and water.

Ingestion:

Call a physician. Do not induce vomiting.

Section 5: Fire-Fighting Measures

Flashpoint:

<0°F

Method: TCC

LEL: 1.7 UEL: 9.0

Extinguishing Media:

CO₂, dry chemical and foam Thermal – carbon monoxide

Hazardous Combustion Products: Fire-fighting Instructions:

Remove containers from fire area if possible. Use self-contained

breathing apparatus for fire fighting. Aerosol cans may explode if heated

above 120°F.

NFPA:

Health:

Reactivity:

0

PPE: B

HMIS:

Health:

2

Flammability: 4
Flammability: 4

Reactivity:

Section 6: Accidental Release Measures

Spill/Leak Procedures: Usually not a problem with aerosols. Area should be ventilated. Absorbent should be used to pick up excess material. All used and unused product should be disposed of in accordance with federal, state and local regulations.

Section 7: Handling and Storage

Handling Procedures: Store in a cool, dry area. Aerosol cans must be maintained below 120°F to prevent cans from exploding.

Aerosol Level: III

Section 8: Exposure Controls/Personal Protection

Engineering Controls: Provide local ventilation adequate to prevent accumulation of vapors. Use mechanical means if necessary to maintain levels below the exposure limits. If working in a confined space, follow applicable OSHA regulations.

Respiratory: Not necessary for normal conditions of use. Use NIOSH/MSHA compliant respirators or selfcontained breathing apparatus if vapors are above exposure limits. Follow OSHA regulations 29 CFR 1910.134.

Protective Clothing/Equipment: Wear chemically protective gloves and safety glasses. Use a splash apron and boots if splashing occurs.

Section 9: Physical & Chemical Properties

Physical State:

Liquid

Appearance & Odor:

Red viscous liquid

Product Number (s): 05046 **Product Name: Battery Terminal Protector** 138°F - 144 °F approximate **Boiling Point:** 0.745 Specific Gravity: ND Vapor Pressure: Freezing Point: ND Vapor Density (air = 1) > air **Evaporation Rate:** NA Solubility: Negligible in water NA pH: lbs./gal: 4.38 526 Volatile Organic Compounds:%: 78.4 g/L: Section 10: Stability and Reactivity Hazardous Polymerization: No Stable Stability: Chemical Incompatibilities: Strong oxidizers. Temperature extremes Conditions to Avoid: None Hazardous Decomposition Products: Section 11: Toxicological Information Long-term toxicological studies have not been conducted for this product. See Section 3 of this MSDS for acute symptoms of overexposure and carcinogenicity information. Section 12: Ecological Information No data available. Ecotoxicity: Environmental Fate: No data available for biodegradation. Section 13: Disposal Considerations Disposal: This material if discarded may be hazardous waste under U.S. EPA RCRA regulations. All disposal activities must comply with federal, state and local regulations. Contact your local or state environmental agency for specific rules. Do not dump into sewers, on the ground or into any body of water. ______ Section 14: Transportation Information **Consumer Commodity** Shipping Name: NA Packing Group: UN Number: NA Hazard Class: ORM-D Placard: NA NA Label: Special Provisions: NA Section 15: Regulatory Information All components are either listed under TSCA or are exempt. TSCA: Acute, Fire, Pressure Section 311/312: SARA Title III: n-Hexane, Xylene, Ethylbenzene Section 313*: NA CERCLA/Superfund (RQ):

No

Extremely Hazardous Substances:

Product Name: Battery Terminal Protector

Product Number (s): 05046

California Prop 65:

This product contains chemicals known to the State of California to cause cancer, birth defects and other reproductive harm.

* See section 2 for percentage

Section 16: Additional Information

Prepared By:

Michelle Milburn

Date:

April 27, 2005

Technical Information:

(800) 521-3168

CRC #:

00597L

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS:

Chemical Abstract Service

NA:

Not Applicable

ppm:

Parts per Million

ND: NE: Not Determined Not Established

TCC: LEL: Tag Closed Cup Lower Explosive Limit Upper Explosive Limit

Personal Protection Equipment

g/L: lbs./gal:

RQ:

grams per Liter pounds per gallon Reportable Quantity

UEL: PPE: COC:

Cleveland Closed Cup