

**MARTIN
SENOUR
PAINTS**®

Automotive Finishes

MATERIAL SAFETY DATA SHEET

THE MARTIN-SENOUR CO.
101 PROSPECT AVE. N.W.
CLEVELAND, OH 44115

EMERGENCY TELEPHONE NO.
(216) 566-2917
INFORMATION TELEPHONE NO.
(216) 566-2902

DATE OF PREPARATION
5 - FEB - 92

©1992, The Martin-Senour Co.

Body Fillers

FIL/N

— SECTION II —		ACGIH TLV <STEL>	OSHA PEL <STEL>	Units	Vapor Pressure (mm Hg)	6369	6370	6370T 6370TS	6371	6372	6372T 6372TL	(6373)	6374		6378		(6379)
CAS No.	HAZARDOUS INGREDIENT (percent by weight)					FIBRE-HAIR™ Body Filler	MICRO-LITE® Body Filler	MICRO-LITE® Hardener	FIBRE-STRAND™ Body Filler	CUZ* Body Filler	CUZ* Hardener	BLUE MOON™ Body Filler	U-Fix-It Kit™		TEC® Non-Staining	PAY DAY®	
													Part A	Part B	Part A	Part B	
100-42-5	§ Styrene	50 <100>	50 <100>	PPM	4.3	16	18		16	15		20	18		18		15
14807-96-6	Talc	2	2	Mg/M3	as Resp. Dust	>10	>10		>10	>10		50	>10		50		>10
13463-67-7	Titanium Dioxide	10	10[5]	Mg/M3 [Resp. Fraction]			>1			>1		>1			>1		1
94-36-0	§ Dibenzoyl Peroxide	5	5	Mg/M3				50			50			45		50	
85-68-7	§ Butyl Benzyl Phthalate	Not Established						28			28			28		50	
Flash Point (°F)						90	90	>200	90	90	>200	90	90	>200	90	>200	90
VOC - Total Volatile Organic Compounds (lbs./gal.)						2.31	1.80	0.00	2.11	2.04	0.00	2.50	1.80	0.00	1.60	0.00	2.04
VOC - Less Water and exempt Solvents (lbs./gal.)						2.31	1.80	0.00	2.11	2.04	0.00	2.50	1.80	0.00	1.60	0.00	2.04
Photochemically Reactive						No	No	No	No	No	No	No	No	No	No	No	No
HMIS® Ratings (Health - Flammability - Reactivity)						2-3-0	2-3-0	2-1-1	2-3-0	2-3-0	2-1-1	2-3-0	2-3-0	2-1-1	2-3-0	2-1-1	2-3-0
PAINT-SAFE® Personal Protection						J3	J3	J3	J3	J3	J3	J3	J3	J3	J3	J3	J3

§ Ingredient subject to the reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313, 40 CFR 372.65 C

For
Paint

Body Fillers

FIL/N

Section III — PHYSICAL DATA

PRODUCT WEIGHT - See TABLE
SPECIFIC GRAVITY - 1.1-79
BOILING RANGE - 293-294 °F
VOLATILE VOLUME - 0-24 %
EVAPORATION RATE - Slower than Ether
VAPOR DENSITY - Heavier than Air
MELTING POINT - N.A.
SOLUBILITY IN WATER - N.A.

Section IV — FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION FLASH POINT See TABLE LEL 1.1 UEL 6.1
Body Fillers ==> RED LABEL, Flammable Liquid, Flash below 100 °F
Hardeners ==> Not Applicable, Flash above 199 °F
EXTINGUISHING MEDIA
Carbon Dioxide, Dry Chemical, Foam
UNUSUAL FIRE AND EXPLOSION HAZARDS
Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode when exposed to extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent.
SPECIAL FIRE FIGHTING PROCEDURES
Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section V — HEALTH HAZARD DATA

ROUTES OF EXPOSURE
Exposure may be by INHALATION and/or SKIN or EYE contact, depending on conditions of use. To minimize exposure, follow recommendations for proper use, ventilation, and personal protective equipment.
ACUTE Health Hazards
EFFECTS OF OVEREXPOSURE
Irritation of eyes, skin and respiratory system. May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.
SIGNS AND SYMPTOMS OF OVEREXPOSURE
Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.
Redness and itching or burning sensation may indicate eye or excessive skin exposure.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE
None generally recognized.
EMERGENCY AND FIRST AID PROCEDURES
If INHALED: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
If on SKIN: Wash affected area thoroughly with soap and water.
Remove contaminated clothing and laundry before re-use.
If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
If SWALLOWED: Give several glasses of water. Seek medical attention.
CHRONIC Health Hazards
Styrene is listed by IARC as a possible human carcinogen based on "inadequate evidence" in humans, "limited evidence" in animals, and the fact that it is metabolized to styrene oxide, which has been shown to induce cancer in animals. However, studies of humans exposed for long periods of time to styrene have not demonstrated any carcinogenic effect.
Rats exposed to titanium dioxide dust at 250 mg./m3 developed lung cancer, however, such exposure levels are not attainable in the workplace.
Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Section VI — REACTIVITY DATA

STABILITY
Body fillers are stable. Hardeners are unstable and should be stored in cool areas (below 90 °F) away from sources of heat.
INCOMPATIBILITY
Avoid contamination of body fillers with polymerization catalysts such as peroxides and strong acids.
Do not put any mixed material back into the can of unmixed filler.
HAZARDOUS DECOMPOSITION PRODUCTS
By fire: Carbon Dioxide, Carbon Monoxide
HAZARDOUS POLYMERIZATION - Will Not Occur

Section VII — SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED
Remove all sources of ignition. Ventilate and remove with inert absorbent.
WASTE DISPOSAL METHOD
Waste from these products may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Waste must be tested for ignitability to determine the applicable EPA hazardous waste number.
Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

Section VIII — PROTECTION INFORMATION

PRECAUTIONS TO BE TAKEN IN USE
Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using.
This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section II) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section II, the applicable limits for nuisance dusts are ACGIH TLV 10 mg./m3 (total dust), OSHA PEL 15 mg./m3 (total dust), 5 mg./m3 (respirable fraction).
VENTILATION
Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section II is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.
RESPIRATORY PROTECTION
If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section II.
When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product or the abrasive.
PROTECTIVE GLOVES
Wear gloves which are recommended by glove supplier for protection against materials in Section II.
EYE PROTECTION
Wear safety spectacles with unperforated sideshields.

Section IX — PRECAUTIONS

DOL STORAGE CATEGORY ==> Body Fillers 1C
==> Hardeners 3B
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING
Keep away from heat, sparks, and open flame.
Consult NFPA Code. Use approved Bonding and Grounding procedures.
Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.
OTHER PRECAUTIONS
These products must be mixed with other components before use. Before opening the packages, READ AND FOLLOW WARNING LABELS ON ALL COMPONENTS.
Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.