

S.C. Johnson Wax
 Racine, Wisconsin 53403-5011
 Phone: (414) 631-2777
 Emergency Phone: (800) 228-5635
 Extension 092

4=Very High
 3=High
 2=Moderate
 1=Slight
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
1 Health	
4 Flammability	
0 Reactivity	

MATERIAL SAFETY DATA SHEET

SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: BOLT CRACK & CREVICE RESIDUAL			PRODUCT CODE 14810-2-3	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 06/29/90	SUPERSEDES: 06/30/89	MSDS SECTIONS WITH CHANGES:	PREPARED BY: Terry A. Meyers Chemical Info. Adm.

SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Isobutane (CAS# 75-28-5)	15-25	NOT ESTABLISHED
Water	70-90	NA
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Dispenses as a foam	SPECIFIC GRAVITY (H2O=1): 0.9
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): NA
SOLUBILITY IN WATER: Appreciable	VAPOR DENSITY (Air=1): ND
FREEZING POINT (°F): ND	BOILING POINT (°F): ND
pH: NA	EVAPORATION RATE (Butyl Acetate=1): NA
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): under 20 (TCC) (Propellant)
FLAMMABLE LIMITS: ND
EXTINGUISHING MEDIA: Foam. CO2. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Fight fire from maximum distance or protected area. Cool and use caution when approaching or handling fire-exposed containers.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burst in heat of fire.

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact. Inhalation.
SIGNS AND SYMPTOMS: Prolonged or repeated contact of product with skin may cause illness. Product may cause distress and illness if taken internally. Product spray mist, fog or vapor may cause irritation to nose, throat and lungs if adequate ventilation is not employed.

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

BOLT CRACK & CREVICE RESIDUAL
Product Number: 14810
Serial Number: 2-3

SECTION V-HEALTH HAZARD DATA (cont.)

FIRST AID PROCEDURES: If product gets on skin, remove with soap and water. If product is swallowed, seek medical aid at once. If mist, fog or vapors cause discomfort, remove to fresh air and ventilate area. If discomfort persists, seek medical aid.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: Recycle empty aerosol can to nearest steel recycling center.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GLOVES: No special requirements under normal use conditions.

EYE PROTECTION: No special requirements under normal use conditions. Chemical workers splash-proof goggles

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder contaminated clothing/equipment before reuse.

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Keep out of reach of children. Hazards to humans and domestic animals: May be harmful if swallowed or absorbed through the skin. Avoid contact with eyes, skin or clothing. Do not smoke while using. Avoid breathing spray mist or vapors. Keep away from food, feedstuffs and domestic water supplies. Remove pets and cover fish bowls (tanks) before spraying. Do not allow children or pets to contact treated surface until spray has dried. See Section X.

OTHER HANDLING AND STORAGE CONDITIONS: Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur. Wash thoroughly after handling. Keep from freezing. Keep out of reach of children.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax
1525 Howe Street
Racine, Wisconsin 53403

BOLT CRACK & CREVICE RESIDUAL
Product Number: 14810
Serial Number: 2-3

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION: EPA Registration No.: 4822-152. NFPA 30B Level 1 This MSDS also covers product codes: BOLT COMMERCIAL INSECTICIDE CRACK & CREVICE RESIDUAL. Wash thoroughly after handling. Note to Physician: Atropine by injection is antidotal only if symptoms of cholinesterase inhibition are present. Foam can ignite. Keep away from sparks, pilot lights, and other flames, both during and after use.

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Non Regulated.

DOT #: NA

SHIPPING NAME: Insecticides or insect repellents, NOI, other than poison.

DOT NOTES: None

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use. R-106 (Rev 5 - 10/90)