



# Material Safety Data Sheet

## 1.0 Product and Company Identification

**Identification of the preparation:** **C6578 Series – No 78 Color**  
**Use of the preparation:** Inkjet printing  
**Company Identification:** Hewlett-Packard Company  
 1000 NE Circle Boulevard  
 Corvallis, Oregon 97330-4239  
 United States  
**Emergency telephone number** 1-800-457-4209 (USA and Canada)  
**Hewlett-Packard Health Effects Line:** 503-494-7199 (USA direct)  
 Singapore: +001-800-332-13321  
  
**General information telephone number:** 208-323-2551 (USA direct)

### Local Contact Information

**Ireland**  
 Liffey Park Technology Campus  
 Barnhall Road,  
 Leixlip, Co. Kildare  
 Phone: 01 6150000  
  
**United Kingdom**  
 Hewlett-Packard, Ltd.  
 Cain Road, Amen Corner  
 Bracknell, Berkshire, RG12 1HN  
 Phone: 1344 36-0000

Hazard Rating	NFPA/HMIS
Health	1
Flammability	1
Instability/Reactivity	0
Special	none

## 2.0 Composition/Information on Hazardous Ingredients

This ink supply contains an aqueous ink formulation

For cyan (blue) ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkyldiol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentanediol	111-29-5	203-854-4	<10	not classified
Alkyldiol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkyldiol ethoxylate #2	confidential	confidential	<3	Xi; R36/38



# Material Safety Data Sheet

Substituted phthalocyanine salt	confidential	confidential	<4	Xn; N; R22- 48/22-51/53
Water	7732-18-5	231-791-2	>50	not classified

For magenta (red) ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkyldiol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentenediol	111-29-5	203-854-4	<10	not classified
Alkyldiol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkyldiol ethoxylate #2	confidential	confidential	<3	Xi; R36/38
Amino alkyldiol	confidential	confidential	<3	Xi; R36/37/38
Water	7732-18-5	231-791-2	>50	not classified

For yellow ink only:

Component/Substance	CAS Number	EU Number	% by Weight	EU classification
Ethyl alkyldiol	confidential	confidential	<10	not classified
2-Pyrrolidone	616-45-5	210-843-1	<8	Xi; R36/37/38
Ammonium nitrate	6484-52-2	229-347-8	<3	O; Xi; R8-36/37/38
Metal nitrate	confidential	confidential	<8	O; Xi; R8-36/37/38
1,5-Pentenediol	111-29-5	203-854-4	<10	not classified
Alkyldiol ethoxylate #1	confidential	confidential	<3	Xi; R38-41
Alkyldiol ethoxylate #2	confidential	confidential	<3	Xi; R36/38
Water	7732-18-5	231-791-2	>50	not classified

## 3.0 Hazard Identification

The cyan ink is classified for environmental effects according to EU Directive 1999/45/EC with R52-53. The magenta and yellow inks are not classified according to EU Directive 1999/45/EC

**3.1 Routes of Exposure** Potential routes of overexposure to this product are skin and eye contact.

Inhalation of vapor and ingestion are not expected to be significant routes of exposure for this product under normal use conditions.

Complete toxicity data are not available for this specific formulation.

## 3.2 Acute Health Hazards

Any potential hazards are presumed to be due to exposure to the components.

Ethyl alkyldiol: Contact with eyes and skin may cause mild



# Material Safety Data Sheet

irritation.

2-Pyrrolidone: Contact with eyes and skin may result in irritation. Inhalation may result in respiratory irritation. Ingestion may result in nausea, vomiting, and diarrhea.

Ammonium nitrate and metal nitrate: Contact with eyes and skin may cause irritation. Inhalation may cause respiratory irritation.

Note: Nitrates and their derivatives can cause methemoglobinemia and result in respiratory depression. Primary indicators of prolonged exposure include shortness of breath, headaches, dizziness and cyanosis (bluish skin and lips).

1,5-Pentanediol: Contact with eyes and skin may cause irritation.

Alkyldiol ethoxylate #1: Contact with eyes may result in severe irritation and corneal injury. Contact with skin may result in severe irritation. Ingestion may cause irritation of mouth and throat, nausea, vomiting and diarrhea.

Alkyldiol ethoxylate #2: Contact with eyes and skin may result in severe irritation. Ingestion may cause irritation of mouth, throat, nausea, vomiting, and diarrhea.

Cyan Ink Only:

Substituted phthalocyanine salt: Harmful if swallowed.

Magenta Ink Only:

Amino Alkyldiol: Contact with eyes and skin may result in irritation. Inhalation may result in respiratory irritation.

### 3.3 Chronic Health Hazards

### 3.4 Carcinogenicity

Cyan Ink Only:

Substituted phthalocyanine salt: Prolonged ingestion exposure may result in serious damage to health.

None of the components present in this formulation at concentrations equal to or greater than 0.1% are listed by EU, MAK, IARC, NTP or OSHA.

## 4.0 First Aid Measures

**Emergency telephone number**  
**Hewlett-Packard Health Effects Line:**

1-800-457-4209 (USA and Canada)  
503-494-7199 (USA direct)  
Singapore: +001-800-332-13321

**Inhalation:**

Remove to fresh air. If symptoms persist, consult a physician.

**Ingestion:**

If stomach upset persists, consult a physician.

**Skin:**

Wash affected areas thoroughly with soap and water. If irritation persists, consult a physician.



# Material Safety Data Sheet

**Eyes:** Do not rub eyes. Immediately flush with large amounts of clean, lukewarm water (low pressure) for at least 15 minutes or until particles are removed. If irritation persists, consult a physician.

## 5.0 Fire Fighting Measures

**Extinguishing media:** Water, dry chemical, carbon dioxide, foam  
**Unsuitable Extinguishing Media:** None known  
**Special Firefighting Procedures:** None known  
**Unusual fire and explosion hazards:** No special hazards known  
**Auto-ignition temperature:** Not determined  
**Flashpoint (method):** > 200° F, > 93.3° C (US EPA Method 1020)  
**Hazardous Combustion Products** Refer to section 10.

## 6.0 Accidental release measures

**Spill or Leak Procedures:** Standard eye and skin protection is recommended.  
**Environmental precautions:** Do not discharge into drains (See also Section 13, Disposal considerations)

## 7.0 Handling and Storage

**Storage Temperature:** 59° F to 95° F; 15° C to 35° C  
**Handling and Storage precautions:** Keep out of the reach of children  
Keep away from extreme heat or cold.  
**Shelf Life:** 1 year  
**Special Sensitivity:** None

## 8.0 Exposure control/ personal protection

**8.1 Exposure Limit Values** None established.  
**8.2 Exposure Controls** Standard eye and skin protection for laboratory chemical safety is recommended. Use in well ventilated area.



# Material Safety Data Sheet

## 9.0 Physical and chemical properties

<b>pH:</b>	6.6 – 8.5
<b>Boiling point:</b>	Not Determined
<b>Flash point:</b>	> 200° F, > 93.3° C
<b>Flammability:</b>	US NFPA/HMIS Flammability rating = 1
<b>Explosive properties:</b>	Not applicable
<b>Oxidizing properties:</b>	Not applicable
<b>Vapor Pressure:</b>	Not applicable
<b>Relative density:</b>	Specific Gravity 1.0 to 1.2
<b>Solubility:</b>	Soluble in water
<b>Partition coefficient:</b>	Not determined
<b>Viscosity:</b>	Not determined
<b>Vapor density:</b>	>1 (air = 1.0)
<b>Evaporation rate:</b>	Not applicable
<b>Other:</b>	Not applicable

## 10.0 Stability and reactivity

<b>Stability:</b>	Stable under normal storage conditions
<b>Incompatibilities:</b>	Strong oxidizers, strong gases, bleach and other hypo-chlorite containing cleaning agents
<b>Thermal decomposition products:</b>	Oxides of carbon/nitrogen/sulfur; water
<b>Hazardous polymerization:</b>	None

## 11.0 Toxicological information

Refer to Section 3 for potential health effects and Section 4 for first aid measures  
Ink formulations have not been tested.

## 12.0 Ecological information

<b>Cyan, Magenta, Yellow Inks:</b>		
96 Hour LC50	LC50 < 400mg/L	Fathead minnow
96 Hour LC50	Survival (100mg/L) = 100%	Trout
	Survival (10mg/L) = 100%	

## 13.0 Disposal considerations

Dispose in accordance with all applicable US Federal, state, local, and country laws.

## 14.0 Transportation information

Not a regulated article under United States DOT, IATA, ADR, or RID.



# Material Safety Data Sheet

**UN Number:** Not applicable  
**Class:** Not applicable  
**Proper Shipping Name:** Not applicable  
**Packing Group:** Not applicable  
**Marine Pollutant:** Not listed  
**Special Precautions:** None noted

## 15.0 Regulatory information

**US EPA TSCA Inventory:** All ingredients are listed or exempt.  
**US EPA TSCA 12(b):** Does not contain listed chemicals.  
**EU Notification:** All ingredients are listed on EINECS and/or ELINCS or exempt.  
**EU Hazard Label (1999/45/EC):** Product may require a label according to EU Directive 1999/45/EC

## 16.0 Other information

**Date Prepared:** June 29, 2002  
**HP-DMS Document Control Number:** 09000de78022847b-eng  
**Revision Information:** This document replaces all prior versions of the MSDS  
**EU Risk (R) Phrase definitions:**  
R8: Contact with combustible material may cause fire  
R22: Harmful if swallowed  
R38: Irritating to skin  
R41: Possible risks of irreversible effects  
R36/38: Irritating to eyes and skin  
R48/22: Harmful: danger of serious damage to health by prolonged exposure if swallowed  
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment  
R36/37/38: Irritating to eyes, respiratory system and skin.  
**Other Information:** This MSDS was prepared in compliance with EU Directive 91/155/EEC as amended by 2001/58/EC and USA OSHA Hazard Communications regulations (29CFR1910:1200).

**DISCLAIMER:** This Material Safety Data Sheet (MSDS) is provided without charge to customers of Hewlett-Packard. Data is the most current known to Hewlett-Packard at the time of preparation of this MSDS and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application.