.JUN 22 '94 12:55

Removed from Line approx

Revised: 04-15-83R

CITGO Petroleum Corporation P.O. Box 300 Tulsa, Oklahoma 74102

MATERIAL SAFETY DATA SHEET

Trade Name: CITGO Non-

Health

Slightly Toxic

detergent Motor Oil

SAE 20-20W Synonyms: Motor Oil

Fire

Combustible 1

Lubricating Oil

CAS Reg. No.: Mixture

Reactivity

٥ Stable

NPPA*

CITGO Index No.:

*CITGO Assignment based on our evaluation.

TSIS-1062,1803

Technical Contact: (918) 561-5165

I. GENERIC COMPOSITION/INGREDIENTS

Material

Hazard Data

Refined Petroleum Oil(s):

CAS #64742-44-5

0-50

LD50 (oral-rat): >15g/kg

Eye: Practically Non-Irritating

(0.7-1.7/110, Drazie)

Skin: Non-Irritating or Practically Non-Irritating (0-0.6/8, Draîze)

LC50/4H (inhln-rat): >3,540mg/m³

Other Refined Petroleum Oils

50-100

LD50 (oral-rat)

II. PHYSICAL DATA

Boiling Point, 760 mmHg, °C (°F): 371.1 (700)

Melting Point, °C (°F): NA

Vapor Pressure, mmHg (25°C): <3x10⁻⁴

Specific Gravity

(H₂O=1): 0.89/60°F

Solubility in Hoo, % By Wt.: Negligible

Vapor Density (Air=1): >1

Evaporation Rate (Butyl Acetate=1): <1

% Volatiles By Vol.: ND

Appearance and Odor: Amber fluid - mild odor.

(2)

TSIS-1062,1803

III. FIRE AND EXPLOSION DATA

Flash Point, °C (°F): 241 (465) Autoignition Temperature, °C (°F): 188 (380)

Planmable Limits in Air, % by Vol: Lower: NA Upper: NA

Extinguishing Media: CO2, dry chemical, foam or water fog.

Special Fire Fighting Procedure: None

Unusual Fire or Explosion Hazard: Water may cause frothing.

IV. HEALTH HAZARD INFORMATION

Toxicity Summary: Slightly toxic - 1 pt to 1 qt is approximate lethal oral

dose for 150 1b human adult.

Exposure Symptoms

Inhalation: Low risk of inhalation. In enclosed spaces or when hot,

vapors may reach concentrations sufficient to cause drowsiness, dizziness, headache, nausea or lung irritation. Mists (>TLV) may cause chemical

pneumonitis.

Skin Contact: Prolonged and/or frequent contact may cause drying,

cracking (dermatitis) or folliculitis.

Skin Absorption: No probable hazard.

Eye Contact: May be mildly irritating.

Ingestion: Generally low toxicity. Ver

Generally low toxicity. Very large amounts may cause generalized depression, headache, drowsiness, nausea, vomiting or diarrhea. Small doses may produce irritation

and diarrhea.

Special Chronic Effects: Dermatitis or folliculitis possible.

First Aid

Inhalation: Remove to fresh air. Respiratory support if necessary. Seek

medical aid.

Skin: Wash with soap and water. Do not wear heavily contaminated

clothing before laundering. (Subcutaneous injection is a medical emergency . . . Seek medical aid immediately.)

Eyes: Flush with large volumes of water. See physician if any

complications arise.

Ingestion: Do not induce vomiting. Seek medical aid.

Notes to Physician: SUS viscosity at 100°F = 367: For amounts greater than 2 oz . . . careful gastric lavage with tight fitting or cuffed tube is to be preferred over emesis. If viscosity

>100 SUS at 100°F., emesis may be induced for large

quantities.

- Aspiration may cause chemical pneumonitis or lipoid

pneumonia.

ND = No Data

NA = Not Applicable

(3)

TSIS-1062,1803

- Subcutaneous injection requires prompt surgical debridement. If not familiar with technique, seek skilled advice.

V. REACTIVITY DATA

Conditions Contributing to Instability: None

Incompatability: Strong Oxidants

Hazardous Decomposition Products (thermal, unless otherwise specified): CO, CO2, and trace oxides of sulfur, zinc, and phosphorus.

Conditions Contributing to Hazardous Polymerization: None

VI. SPILL OR LEAK PROCEDURES

Follow accepted industry practices and/or local, state and federal regulations. Check before handling.

VII. SPECIAL PROTECTION INFORMATION

Ventilation Requirements: TLV 5 mg/cu m as oil mist. (ACGIH 1979)

Specific Personal Protective Equipment

Respiratory: Normally none required. If high vapor or mist concentrations

expected - organic respirator.

Eyes: Safety goggles if splashing is anticipated.

Gloves: Oil impervious gloves if frequent or prolonged contact is

expected.

Other Clothing or Equipment: Normally, none.

VIII. SPECIAL PRECAUTIONS

Precautionary Statements: None

Storage: Store in steel tank or drum below 120°F. Do not apply high heat or

flame to container. DOT hazard label not required.

The suggestions and data provided herewith are based upon tests and information which we believe to be reliable. However, we make no guarantee with respect thereto and assume no liability resulting from the use thereof. Users should make their own investigations to determine the suitability of the information or products for their particular purpose. Furthermore, nothing contained therein is intended as permission, inducement or recommendation to violate any laws or to practice any invention covered by existing patents.

CITGO Petroleum Corporation



P.O. Box 3758 Tulsa, Oklahoma 74102 (918) 495-4000

June 22, 1994

Account Number:

University of Wisconsin-Whitewater ATTN: Vay Rodman 800 West Main Street Whitewater, WI 53190-1790

Attention: Plant Manager/Hazard Communication Coordinator

Dear Customer:

Enclosed is the Material Safety Data Sheet (MSDS) you requested. In addition to Hazard Communication requirements, the MSDS is intended to provide notification of SARA Section 313 "toxic chemicals" per 40 CFR 372. In order for the MSDS to serve its intended purpose, it should be forwarded to those persons in your organization who have a need for safety and environmental information.

If you are a distributor, OSHA and EPA regulations require that you provide a copy of the MSDS to your customers. You should consult 40 CFR 372.45 for guidance with respect to products containing toxic chemicals referenced in SARA Section 313.

If you have questions regarding CITGO's Hazard Communication Program, please contact me at the above address.

Sincerely,

Yvonne Hale

Yuonne Xale

Literature Distribution Center

Enclosure

Please note that Non-Detergent 20W-20 rus removed from our product line around 1911 or P2.