

SHERWIN-WILLIAMS -- Y38Y107 COLOR ACCENT LATEX PAINT BASE M GOLD - PAINT
MATERIAL SAFETY DATA SHEET

NSN: 801000F037411

Manufacturer's CAGE: 54636

Part No. Indicator: A

Part Number/Trade Name: Y38Y107 COLOR ACCENT LATEX PAINT BASE M GOLD

=====
General Information
=====

Item Name: PAINT
Company's Name: SHERWIN-WILLIAMS CO
Company's Street: 101 PROSPECT AVE N W
Company's City: CLEVELAND
Company's State: OH
Company's Country: US
Company's Zip Code: 44115-1042
Company's Emerg Ph #: 216-566-2917
Company's Info Ph #: 216-566-2902
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 002
Status: SE
Date MSDS Prepared: 01DEC93
Safety Data Review Date: 22NOV94
Preparer's Company: SHERWIN-WILLIAMS CO
Preparer's St Or P. O. Box: 101 PROSPECT AVE N W
Preparer's City: CLEVELAND
Preparer's State: OH
Preparer's Zip Code: 44115-1042
MSDS Serial Number: BWHZK

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: 2-(2-BUTOXYETHOXY)-ETHANOL, DIETHYLENE GLYCOL MONOBUTYL ETHER
(BUTYL CARBITOL)
Ingredient Sequence Number: 01
Percent: 1
NIOSH (RTECS) Number: KJ9100000
CAS Number: 112-34-5

Proprietary: NO
Ingredient: SILICON DIOXIDE, CRYSTALLINE QUARTZ, SAND (ANIMAL SUFFICIENT/
HUMAN LIMITED EVIDENCE BY IARC, NTP). GROUP 2A - *94-3*
Ingredient Sequence Number: 02
Percent: 12
NIOSH (RTECS) Number: VV7330000
CAS Number: 14808-60-7
OSHA PEL: 0.1 MG/CUM RESP DUST
ACGIH TLV: 0.1 MG/CUM RESP DUST
Other Recommended Limit: 0.05 MG/CUM NIOSH

Proprietary: NO
Ingredient: CARBONIC ACID, CALCIUM SALT (1:1), CALCIUM CARBONATE, DURAMITE
Ingredient Sequence Number: 03
Percent: 10
NIOSH (RTECS) Number: FF9335000
CAS Number: 471-34-1
OSHA PEL: 15 MG/M3
ACGIH TLV: 10 MG/M3
Other Recommended Limit: 10 MG/CUM (DUST)

=====
Physical/Chemical Characteristics
=====

Appearance And Odor: GOLD PAINT
Boiling Point: 212-448F

Vapor Density (Air=1): >1
Specific Gravity: 1.24
Evaporation Rate And Ref: SLOWER THAN ETHER
Percent Volatiles By Volume: 64
pH: 9.5

=====
Fire and Explosion Hazard Data
=====

Flash Point: >200F
Flash Point Method: PMCC
Lower Explosive Limit: 0.9
Upper Explosive Limit: 5.9
Extinguishing Media: CO2, DRY CHEMICAL, ALCOHOL FOAM
Special Fire Fighting Proc: FULL PROTECTIVE EQUIPMENT & SCBA SHOULD BE USED. WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS USED, FOG NOZZLES ARE PREFERABLE. (SEE SUPP)
Unusual Fire And Expl Hazrds: CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

=====
Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): EXTREME HEAT, SOURCES OF IGNITION.
Materials To Avoid: IGNITION SOURCES
Hazardous Decomp Products: CO2, CO
Hazardous Poly Occur: NO

=====
Health Hazard Data
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: NO
Health Haz Acute And Chronic: INHALATION: IRRITATION TO UPPER RESPIRATORY SYSTEM. EYES/SKIN: IRRITATION, BURNING SENSATION. INGESTION: LONG TERM EXPOSURE TO HIGH LEVELS OF SILICA DUST MAY CAUSE LUNG DAMAGE & POSSIBLE CANCER.
Carcinogenicity - NTP: YES
Carcinogenicity - IARC: YES
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: SEE INGREDIENTS
Signs/Symptoms Of Overexp: IRRITATION, HEADACHE, NAUSEA, DIZZINESS, REDNESS, ITCHING, BURNING SENSATION.
Emergency/First Aid Proc: INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. KEEP WARM & QUIET. SKIN: WASH AFFECTED AREA THOROUGHLY W/SOAP & WATER. EYES: FLUSH W/LARGE AMOUNTS OF WATER FOR 15 MINS. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: REMOVE ALL SOURCES OF IGNITION. VENTILATE & REMOVE W/INERT ABSORBENT.
Waste Disposal Method: INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINER. DISPOSE OF IAW/FEDERAL, STATE & LOCAL REGULATIONS.
Precautions-Handling/Storing: KEEP CONTAINER CLOSED WHEN NOT IN USE. TRANSFER ONLY TO APPROVED CONTAINERS W/COMPLETE & APPROPRIATE LABELING.
Other Precautions: DON'T TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN. USE ONLY W/ADEQUATE VENTILATION. AVOID BREATHING VAPOR & SPRAY MIST. AVOID CONTACT W/SKIN & EYES.

=====
Control Measures
=====

Respiratory Protection: WEAR A NIOSH/MSHA APPROVED PROPERLY FITTED ORGANIC VAPOR/PARTICULATE RESPIRATOR IF PERSONAL EXPOSURE CAN'T BE CONTROLLED < APPLICABLE LIMITS BY VENTILATION. WEAR A NIOSH/MSHA APPROVED DUST/MIST RESPIRATOR WHEN SANDING/ABRADING DRIED FILM.

Ventilation: LOCAL EXHAUST: PREFERABLE. GENERAL EXHAUST: ACCEPTABLE IF EXPOSURE IS MAINTAINED < APPLICABLE EXPOSURE LIMITS.
Protective Gloves: RECOMMENDED
Eye Protection: SAFETY GLASSES
Other Protective Equipment: UNPERFORATED SIDESHIELDS.
Work Hygienic Practices: REMOVE/LAUNDER CONTAMINATED CLOTHING BEFORE REUSE. WASH HANDS AFTER USING.
Suppl. Safety & Health Data: FIRE FIGHTING PROC CONT'D: WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP & POSSIBLE AUTOIGNITION/EXPLOSION WHEN EXPOSED TO EXTREME HEAT.

=====
Transportation Data
=====

=====
Disposal Data
=====

=====
Label Data
=====

Label Required: YES
Label Status: G
Common Name: Y38Y107 COLOR ACCENT LATEX PAINT BASE M GOLD
Special Hazard Precautions: INHALATION: IRRITATION TO UPPER RESPIRATORY SYSTEM. EYES/SKIN: IRRITATION, BURNING SENSATION. INGESTION: LONG TERM EXPOSURE TO HIGH LEVELS OF SILICA DUST MAY CAUSE LUNG DAMAGE & POSSIBLE CANCER. IRRITATION, HEADACHE, NAUSEA, DIZZINESS, REDNESS, ITCHING, BURNING SENSATION.
Label Name: SHERWIN-WILLIAMS CO
Label Street: 101 PROSPECT AVE N W
Label City: CLEVELAND
Label State: OH
Label Zip Code: 44115-1042
Label Country: US
Label Emergency Number: 216-566-2917