

S.C. Johnson Wax  
 Racine, Wisconsin 53403-5011  
 Phone: (414) 631-2777  
 Emergency Phone: (800) 228-5635  
 Extension 092  
 International Emergency Phone:  
 Extension 092

4=Very High  
 3=High  
 2=Moderate  
 1=Slight  
 0=Insignificant

HAZARD RATING	
HMIS	NFPA
1 Health	1
0 Flammability	0
0 Reactivity	0

## MATERIAL SAFETY DATA SHEET

### SECTION I-PRODUCT IDENTIFICATION

PRODUCT NAME: COMPLETE FOR FLOORS		PRODUCT CODE: 14650-34-35 to 14654-34-35	
CHEMICAL OR COMMON NAME: NA	DATE ISSUED: 01/13/93	SUPERSEDES: 02/20/92	MSDS SECTIONS WITH CHANGES: V
			PREPARED BY: Terry A. Meyers Chemical Info. Adm.

### SECTION II-INGREDIENT INFORMATION

INGREDIENTS	WEIGHT %	EXPOSURE LIMIT
Acrylic Polymers (CAS# N/ACAS)	10-20	NA
[PA,NJ,MA] Ammonium Hydroxide (CAS# 1336-21-6)	1-3	25 PPM ACGIH/OSHA TWA; 35 PPM ACGIH/OSHA STEL
Dipropylene Glycol Methyl Ether (CAS# 34590-94-8CAS)	2-5	100 PPM ACGIH/OSHA TWA, 150 PPM ACGIH/OSHA STEL, (SKIN)
Water (CAS# 7732-18-5)	70-85	NOT ESTABLISHED
Waxes (CAS# N/A)	3-6	NE
See Regulatory Information (Section XII) for explanation of bracketed information.		

### SECTION III-PHYSICAL DATA

APPEARANCE/ODOR: Opaque, tan liquid with mild monomeric odor	SPECIFIC GRAVITY (H2O=1): 1.02
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): ND
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): NA
FREEZING POINT (°F): ND	BOILING POINT (°F): above 200
PH: 9.2-9.5	EVAPORATION RATE (Butyl Acetate=1): ND
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND

### SECTION IV-FIRE AND EXPLOSION INFORMATION

FLASH POINT (°F) (Method Used): NA
FLAMMABLE LIMITS: NA
EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog.
SPECIAL FIREFIGHTING PROCEDURES: Normal fire fighting procedures may be used. Cool and use caution when approaching or handling fire-exposed containers.

**MATERIAL SAFETY DATA SHEET**

Page 2

S. C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

COMPLETE FOR FLOODS  
Product Number: 14650  
Serial Number: 34-35

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Container may burst in heat of fire.

**SECTION V-HEALTH HAZARD DATA**

PRIMARY ROUTE OF ENTRY: Eye contact.

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation.

FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. If product gets on skin, remove with soap and water. If product is swallowed, drink large amounts of water or milk and seek medical aid.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with pre-existing skin disorders may be more susceptible to irritating effects.

**SECTION VI-REACTIVITY DATA**

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID: None known

**SECTION VII-SPILL OR LEAK PROCEDURES**

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Contains ammonia. Do not let

spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dry or similar inert material. Sweep or scrape up and containize. Rinse affected area thoroughly with water.

WASTE DISPOSAL INFORMATION: No special method. Observe all applicable Federal/State regulations and local ordinances regarding disposal of non-hazardous materials. Waste from normal product use may be sewer to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

**SECTION VIII-SPECIAL PROTECTION INFORMATION**

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: General room ventilation adequate.

PROTECTIVE GEAR: If prolonged or repeated contact is possible: Any impervious material.

HYGIENE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices.

**MATERIAL SAFETY DATA SHEET**

Page 3

S. C. Johnson Wax  
1525 Howe Street  
Racine, Wisconsin 53403

COMPLETE FOR FLOODS  
Product Number: 14650  
Serial Number: 34-35

SECTION IX-SPECIAL PRECAUTIONS  
PRECAUTIONARY LABELING: NA

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Keep from freezing.

**SECTION X-ADDITIONAL INFORMATION**

ADDITIONAL INFORMATION: NA

FPA REGISTRATION #: NA

**SECTION XI-TRANSPORTATION INFORMATION**

DOT CLASS: Non Regulated.

DOT #: NA

SHIPPING NAME: Buffing or polishing compounds, NOI.

**SECTION XII-REGULATORY INFORMATION**

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

NA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NU - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

PA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined  
The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.  
R-106 (Rev 5 - 10/90)