S.C. Johnson Wax Racine, Wisconsin 53403-5011 Phone: (414) 631-2777 Emergency Phone: (800) 228-5635 Extension 092 International Emergency Phone:

Extension 092

4=Very High 3=High 2=Moderate 1=Slight 0=Insignificant 0 Reactivity

HAZARD RATING NFPA HMIS 1 Health 1 2 Flammability

## MATERIAL SAFETY DATA SHEET

PRODUCT NAME: CONQ-R-DUST LIQUID	. I PRODUC	T IDENTIFICATION	PRODUCT CODE: 14760-4
CHEMICAL OR COMMON NAME:		MSDS SECTIONS WITH CHANGES: II IX XI	PREPARED BY: Terry A. Meyers Chemical Info. Adm.

SECTION II-INGREDIENT INFORMATION					
INGREDIENTS	WEIGHT %	EXPOSURE LIMIT			
[MA] Light Naphthenic Distillate (CAS# 64741-52-2)	75-90	5mg/m3 (ACGIH TLV-TWA) (OSHA PEL)			
Isoparaffinic Hydrocarbon Solvent (CAS# 64742-48-9)	5-10	300 PPM-EXXON RECOMMENDED			
[PA,NJ,MA] Amyl Acetate (CAS# 628-63-7)	1-2	100 PPM ACGIH/OSHA TWA			
See Regulatory Information (Section XII) for explanation of bracketed information.					

SECTION III	-PHYSICAL DATA		
APPEARANCE/ODOR: Clear slightly yellow with banana odor	SPECIFIC GRAVITY (H20=1): 0.8		
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (%): 100		
SOLUBILITY IN WATER: Negligible	VAPOR DENSITY (Air=1): ND		
FREEZING POINT (°F): ND	BOILING POINT (°F): ND		
pH: NA	EVAPORATION RATE (Butyl Acetate=1): NA		
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (lb/gal): ND		

SECTION IV-FIRE AND EXPLOSION INFORMATION FLASH POINT (°F) (Method Used): 101 (TCC) FLAMMABLE LIMITS: ND Foam. CO2. Dry Chemical. Water Fog. EXTINGUISHING MEDIA: Normal fire fighting procedures may be used. Cool SPECIAL FIREFIGHTING PROCEDURES: and use caution when approaching or handling fire-exposed containers. UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid run-off to sewers may create fire/explosion hazard. Container may explode in heat of fire. Vapors may accumulate in confined spaces (e.g., pits, sumps, sewers) and inadequately ventilated areas.

MATERIAL SAFETY DATA SHEET

S.C. Johnson Wax 1525 Howe Street

Racine, Wisconsin 53403

Product Number: 14760 Serial Number: 4

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.

SIGHS AND SYMPTOMS: Prolonged or repeated contact of product with skin may cause irritation. Product may cause severe distress and serious illness if taken internally. If taken internally, aspiration of liquid product can cause chemical pneumonitis.

If product gets on skin, remove with soap and water. If FIRST AID PROCEDURES: product is swallowed, do not induce vomiting. Seek medical aid at once. MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE: Persons with

pre-existing skin disorders may be more susceptible to irritating effects

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID: None known

INCOMPATIBILITY: None known

HAZARDOUS DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of

combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

MAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID:

None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Eliminate all ignition sources. Do not let spilled or leaking material enter watercourse. Contains Amyl Acetate. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.

waste disposal information: Disposal is regulated under the Resource Conservation and Recovery Act as an ignitable waste (40 CFR 261.21). Disposal of

regulated quantities should be by incineration at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of ignitable wastes.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: NSR

PROTECTIVE GLOVES:

If prolonged or repeated contact is possible: Any impervious

material. EYE PROTECTION: No special requirements under normal use conditions.

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder

contaminated clothing/equipment before reuse

SECTION IX-SPECIAL PRECAUTIONS
DANGER: Harmful or fatal if swallowed. Contains mineral PRECAUTIONARY LABELING: seal oil. If swallowed, do not force to throw up. Go to a doctor or hospital emergency room at once. Keep out of reach of children. Do not use near open fire, flames or heat. FOR INDUSTRIAL USE ONLY. MATERIAL SAFETY DATA SHEET

CONQ-R-DUST LIQUID Product Number: 14760

1525 Howe Street Racine, Wisconsin 53403 Serial Number:

SECTION IX-SPECIAL PRECAUTIONS (cont.)

OTHER HANDLING AND STORAGE CONDITIONS: Store in a cool, dry place with adequate ventilation. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Do not pressurize, cut, heat, weld or expose container to flame; explosion could occur.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION:

EPA REGISTRATION #: NA

S.C. Johnson Wax

SECTION XI-TRANSPORTATION INFORMATION

por class: Combustible liquid (containers over 110 gals.).

Page 2

Cleaning, scouring or washing compounds, NOI, liquid. SHIPPING NAME:

SECTION XII-REGULATORY INFORMATION

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

There are no ingredients subject to the reporting requirements under California's Proposition 65.

- These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

- These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

- These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined

The information herein is given in good faith. No warranty expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use. R-106 (Rev 5 - 10/90)

Page 3