

**SECTION 1 - MANUFACTURER INFORMATION**

Manufacturer/Distr.	DBA Products Co., Inc. 27 Skokie Highway Lake Bluff IL 60044	Information #	1-708-234-8100
		Emergency #	1-800-255-3924 (Chem-Tel) 24 hours
		Emergency Inter1 #	1-813-979-0626 (Chem-Tel) 24 hours/Call Collect

**SECTION 1A - PRODUCT IDENTIFICATION**

Product name	Curethane WB Approach Finish #2500	LEGEND: Severe Hazard = 4 Serious Hazard = 3 Moderate Hazard = 2 Slight Hazard = 1 Minimal Hazard = 0	<b>Hazardous Materials Identification System</b>	
Product Description	Water-born coating		HEALTH	2
Product #	112500		FLAMMABILITY	2
Revision Date	8/18/93		REACTIVITY	0
			PROTECTION	D

**SECTION 2 - HAZARDOUS INGREDIENTS**

CHEMICAL	CAS #	%	Exposure PPM	TLV MG/M3	SARA 313	NTP	IARC	65
Cyclohexanol	108-93-0	N/I	50	206	N/A	N/A	N/A	N/A
2-Butoxyethanol	111-76-2	N/I	25	121	N/A	N/A	N/A	N/A

**SECTION 3 - HEALTH HAZARD DATA**

**HEALTH EFFECTS (Acute & Chronic):** Swallowing: Unknown.  
 Inhalation: May cause irritation of the nose and throat. Temporary headache.  
 Eye: May cause eye irritation.  
 Skin: May cause defatting and irritation of the skin.

**EMERGENCY FIRST AID PROCEDURES:** Swallowing: If swallowed call poison control center immediately, hospital emergency room or physician.  
 Inhalation: Remove to fresh air immediately, if breathing has stopped, give artificial respiration. Keep warm and quiet. Get medical attention immediately.  
 Eye: Flush with large amount of water for at least 15 minutes. If irritation persists, get medical attention.

**PRIMARY ROUTE OF ENTRY:** N/I

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Reports have associated prolonged and repeated occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**SECTION 4 - PHYSICAL, FIRE, EXPLOSION DATA**

Flashpoint (C):	N/I	Evaporation rate:	<1 (ether = 1)	Boiling Point:	100°C (212°F)
Vapor Density:	>1 (air = 1)	UEL:	N/I	Weight per gallon:	N/I
Specific Gravity:	N/I	LEL:	N/I	% volatile by weight:	72

Appearance & odor: Beige liquid with acrylic odor. Solubility in water: Soluble.

**EXTINGUISHING MEDIA:** Use NFPA Class B fire extinguisher (carbon dioxide all purpose dry chemical or alcohol foam) designed to extinguish flammable liquid fires.

**FIRE & EXPLOSION HAZARDS:** Emergency conditions, overexposure to decomposition may cause health hazard. Symptoms not immediately apparent. Obtain medical attention. Keep container tightly closed. Closed containers may explode when exposed to heat. Isolate from heat.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Thermal decomposition may yield carbon monoxide and oxide of nitrogen.

**SPECIAL FIREFIGHTING PROCEDURES:** Firefighters should wear self-contained breathing apparatus. Water may be ineffective, but used to cool exposed containers to prevent pressure build-up and possible explosion when exposed to extreme heat. If water used, fog nozzle.

**SECTION 5 - REACTIVITY DATA**

**IS PRODUCT STABLE:** Stable under normal conditions.

**CONDITIONS TO AVOID FOR STABILITY:** N/I

**INCOMPATIBILITY (Materials to Avoid):** Amine, alkaline and acidic materials strong oxidizers.

**HAZARDOUS POLYMERIZATION:** Will not occur.

**CONDITIONS TO AVOID FOR POLYMERIZATION:** N/I

**SECTION 6 - EXPOSURE CONTROL DATA**

**VENTILATION:** Mechanical is preferred.

**RESPIRATORY PROTECTION:** Use an appropriate NIOSH/MSHA approved respirator to remove organic vapors. Refer to OSHA 29 CFR 1910.134 "Respiratory Protection".

**PROTECTIVE EQUIPMENT:** Impermeable gloves suggested to prevent prolonged or repeated skin contact. Eye protection: Chemical resistant splash goggles or safety glasses. Eyewash facility and safety shower.

**WORK PRACTICES:** Use suggested protective equipment. Keep container tightly closed when not in use.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before each break period and at the end of the shift.

**SECTION 7 - SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Ventilate area as well as possible. Avoid breathing vapors. Dike and contain spill with inert material in covered plastic container for disposal. Prevent contamination of sewers, stream, and groundwater with spilled material or used absorbent.

**WASTE DISPOSAL METHODS:** Dispose in accordance with federal, state and local regulations.

**SECTION 8 - SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:** Do not store above 100°F. Store large quantity in compliance with OSHA 29 CFR 1910.106.

**OTHER PRECAUTIONS:** Do not take internally. Close container after each use. Keep away from children.

The information contained herein is based on the data considered to be accurate. While the information is believed to be reliable, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Since the use of this information and the conditions and use of this product are controlled by the user, it is the user's obligation to determine the conditions of the safe use of the product.