

DAP INC. P.O. BOX 277 DAYTON, OH 45401-0277 MSDS NO: DAP / 30807 INTERNAL ID: 30807 DAP WELDWOOD MULTI-PURPOSE FLOOR ADHESIVE (3055)REVISION: 4 DATE: FEBRUARY 6, 1992

NATIONAL PAINT AND COATINGS ASSOCIATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM

HEALTH HAZARD	1 - SLIGHT
FLAMMABILITY HAZARD	2 - MODERATE
REACTIVITY HAZARD	0 - MINIMAL
PERSONAL PROTECTION	B - GLASSES, GLOVES

SECTION I. MATERIAL IDENTIFICATION

TRADE/MATERIAL NAME: DAP WELDWOOD

MULTI-PURPOSE FLOOR ADHESIVE (3055)

DESCRIPTION: ADHESIVE

CAS: MIXTURE

PREVIOUS REVISION DATE: JANUARY 21, 1991

DOT INFORMATION FOR DOMESTIC GROUND TRANSPORT OF CONTAINER 110 GALLONS OR LESS: SHIPPING NAME (49 CFR 172.101):NOT APPLICABLE D.O.T ID NO. (49 CFR 172.11): NOT APPLICABLE D.O.T. HAZARD CLASS: NOT APPLICABLE D.O.T. LABEL REQUIRED (49 CFR 172.101): NOT APPLICABLE EPA HAZARD CLASS - IF DISCARDED (40 CFR 261): NONE

MANUFACTURER: DAP INC. P.O. BOX 277 DAYTON, OH 45401-0277 PHONE: 1-800-543-3840 IN OHIO 1-513-667-4461

		·	
; S	ECTION II. INGREDIENTS	AND HAZARDS	:
INGREDIENT NAME:	CAS NUMBER:	PERCENT: E	EXPOSURE LIMITS:
MINERAL SPIRITS	64742-88-7	1-5	OSHA PEL:100PPM TWA ACGIH TLV:100PPM TWA
+METHANOL	67-56-1	1-4	OSHA PEL:200PPM TWA ACGIH STEL:250PPM TLV ACGIH TLV:200PPM SKIN
ETHOXYLATED ALKYL PHENOL	9016-45-9	1-5	NE
REMAINING INGREDIENTS ARE	NOT REGULATED BY OSHA	AND ARE COL	NSIDERED TRADE SECRETS.

IF PRESENT, CHEMICALS SUBJECT TO THE REPORTING REQUIREMENTS OF SARA TITLE III SECTION 313 ARE IDENTIFIED BY A (+) PRECEDING THE CHEMICAL NAME ABOVE.

--- PAGE 1



DAP INC. P.O. BOX 277 DAYTON, OH 45401-0277 MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD
MULTI-PURPOSE FLOOR ADHESIVE
(3055)
REVISION: 4
DATE: FEBRUARY 6, 1992

: SECTION III. PHYSICAL DATA	
APPEARANCE & ODOR: OFF WHITE PASTE.	
BOILING POINT: 212F (WATER) VAPOR PRESSURE: 98MMHG @ 68F (METHANOL) WATER SOLUBILITY (%): SOLUBLE VAPOR DENSITY (AIR=1): >1  EVAPORATION RATE: (N-BUTY ACETATE SPECIFIC GRAVITY (H2O=1 % VOLATILE BY VOLUME: 5	L =1):<1 ): 1.2 0-55
VOC LESS WATER LESS EXEMPT SOLVENTS (G/LITER):141 VOC MATERIAL (G/LITER):79	
: SECTION IV. FIRE AND EXPLOSION DATA	:
FLASH POINT (METHOD): 196F (SETA LIMITS: LEL %: NE UEL % C.C.)	
EXTINGUISHING MEDIA: FOAM, CARBON DIOXIDE, DRY CHEMICAL	
UNUSUAL FIRE OR EXPLOSION HAZARDS: CONTAINERS MAY EXPLODE IF EXPOSE HEAT. ELIMINATE SOURCES OF IGNITION: HEAT, ELECTRICAL EQUIPMENT, S FLAMES. DO NOT PUT INTO CONTACT WITH OXIDIZING OR CAUSTIC MATERIAL	PARKS, AND
SPECIAL FIRE-FIGHTING PROCEDURES: FULL PROTECTIVE EQUIPMENT, INCLUD CONTAINED BREATHING APPARATUS IS RECOMMENDED TO PROTECT FROM COMBUS COOL EXPOSED CONTAINERS WITH WATER.	
: SECTION V. REACTIVITY DATA	
MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION WILL NOT	
CHEMICAL INCOMPATIBILITIES: STRONG OXIDIZERS AND CAUSTICS	
CONDITIONS TO AVOID: EXCESSIVE HEAT	
HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL COMBUSTION PRODUCTS, I.E.	COX, NOX
SECTION VI. HEALTH HAZARD INFORMATION	

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY IARC, NTP, OSHA.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: NONE KNOWN

PRIMARY ENTRY ROUTE(S): INHALATION OF VAPORS AND SKIN CONTACT.

ACUTE EFFECTS: MAY IRRITATE EYES, SKIN, NOSE AND RESPIRATORY TRACT. INHALATION OF SOLVENT VAPORS MAY EFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS HEADACHE OR NAUSEA. HARMFUL OR FATAL IF SWALLOWED. INGESTION MAY CAUSE BLINDNESS, NAUSEA, AND OR VOMITING, LEADING TO SEVERE ILLNESS OR POSSIBLE DEATH.

CHRONIC EFFECT(S): REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE.



DAP INC. P.O. BOX 277 DAYTON, OH 45401-0277 MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD
MULTI-PURPOSE FLOOR ADHESIVE
(3055)
REVISION: 4
DATE: FEBRUARY 6, 1992

		:
:	HEALTH HAZARD INFORMATION CONTINUED FROM PAGE 2	<u>-</u>
FIRST AID:		
EYE CON	TACT:FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. CONTACT A PHYSICIAN IMMEDIATELY.	
SKIN CON	TACT: WASH IMMEDIATELY WITH SOAP AND WATER.	
TNHALA	TION:REMOVE TO FRESH AIR. CONTACT PHYSICIAN IMMEDIATELY.	
INGES	TION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN OR REGIONAL POISON CONTROL CENTER IMMEDIATELY.	
	SECTION VII. SPILL, LEAK AND DISPOSAL PROCEDURES	!
	PROCEDURES: USE ABSORBENT MATERIAL OR SCRAPE UP DRIED MATERIAL AND PLACE INTO CONTAINERS.	
WASTE MANAGEM	MENT / DISPOSAL: DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL STANDARDS. DO NOT REUSE EMPTY CONTAINERS.	
	SECTION VIII. SPECIAL PROTECTION INFORMATION	!
PERSONAL PROT	TECTIVE EQUIPMENT:	
GOGGLES:	SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED.	
GLOVES:	RECOMMENDED FOR REPEATED OR PROLONGED CONTACT WITH SKIN.	
RESPIRATOR	:NOT REQUIRED UNDER NORMAL USAGE AND WITH ADEQUATE VENTILATION. SEE VENTILATION SECTION BELOW.	
WORKPLACE COL	NSIDERATIONS:	107)
VENTILATION	PROVIDE SUFFICIENT MECHANICAL VENTILATION (LOCAL OR GENERAL EXHAL TO MAINTAIN EXPOSURE BELOW PEL AND TLV. VAPORS ARE HEAVIER THAN AND WILL COLLECT IN LOW AREAS. CHECK LOW AREAS (BASEMENTS, SUMFETC.) BEFORE ENTERING.	A AIR

WASH CONTAMINATED CLOTHING BEFORE REUSE.

SAFETY STATIONS: NOT REQUIRED.

CONTAMINATED EQUIPMENT:





DAP INC. P.O. BOX 277 DAYTON, OH 45401-0277 MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD
MULTI-PURPOSE FLOOR ADHESIVE
(3055)
REVISION: 4
DATE: FEBRUARY 6, 1992

SECTION IX. SPECIAL PRECAUTIONS

STORAGE SEGREGATION: STORE AWAY FROM CAUSTICS AND OXIDIZERS.

SPECIAL HANDLING / STORAGE: KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS FROM EXCESSIVE HEAT AND FREEZING.

OTHER PRECAUTIONS: INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING VAPORS MAY BE HARMFUL OR FATAL.

DOT CLASS: SEE SECTION I

UN REGISTER: SEE SECTION I

THIS DATA IS OFFERED IN GOOD FAITH AS TYPICAL VALUES AND NOT AS A PRODUCT SPECIFICATION. NO WARRANTY, EITHER EXPRESSED OR IMPLIED, IS HEREBY MADE. THE RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THESE RECOMMENDATIONS IN THE SPECIFC CONTEXT OF THE INTENDED USE AND DETERMINE IF THEY ARE APPROPRIATE.