

	SECTION IA-PHOOL	JUI IDENTIFICATION		
Product name	DBA Lane Cleaner #7583-C	LEGEND:	Hazardous Materials iden	tification System
		Severe Hazard = 4		
Product Description	Cleaner	Serious Hazard = 3	HEALTH	2
•		Moderate Hazard = 2	FLAMMABILITY	2
Product #	137583-C	Slight Hazard = 1	REACTIVITY	0
Revision Date	10/6/95	Minimal Hazard = 0	PROTECTION	В

SECTION 2 - HAZARDOUS INGREDIENTS

				Exposure	TLV	SARA			
-	CHEMICAL	CAS#	%	PPM	MG/M3	313	NTP	IARC	65
	Proprietary blend cleaning solution	N/I	N/I	N/I	N/I	N/I	N/I	N/I	N/I

TRADE SECRET: The identity of the specific ingredients contained in this product are classified a trade secret covered by OSHA Standard 29 CFR 1910.12 Section (g) (i), specific chemical identity can be available under OSHA Standard 29 CFR 1910.12 section (g) (2).

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute & Chronic): Ingestion: Can cause gastrointestinal irritation, nausea, and vomiting.

Inhalation: May cause nose and throat irritation, high concentrations may cause acute nervous depression characterized by headache, dizziness, nausea and confusion. Aspiration of material into the lung may cause pulmonary pneumonitis, which can be fatal.

Eve: May cause transient comeal damage.

Manufacturer/Distr.

Dermal; Liquid material may be absorbed through the skin in harmful amount. May cause defatting and irritation of the skin.

REPEATED OVEREXPOSURE: Reports have been associated with prolonged and repeated occupational overexposure to solvents with permanent brain and nervous system darnage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

EMERGENCY FIRST AID PROCEDURES: Ingestion: DO NOT induce vomiting. Call hospital emergency room or physician immediately.

Inhalation: Remove to fresh air immediately.

Eye: Flush with large amount of water, occasionally raising upper and lower eye lids. Continue for at least 15 minutes. Get medical attention.

Dermal: Remove contaminated clothing. Wash affected area thoroughly with soap and water.

PRIMARY ROUTE OF ENTRY: Skin contact or inhalation.

TEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: N/I

SECTION 4 - PHYSICAL, FIRE, EXPLOSION DATA					
Flashpoint (C):	38°C (101°F TCC)	Evaporation rate:	<1 (ether = 1)	Boiling Point:	77°C (170°F)
Vapor Density:		UEL:	N/I	Weight per gallon:	7,2 lbs.
Specific Gravity:	0.868	LEL:	N/I	% volatile by weight:	99.9

Appearance & odor: Red low viscosity liquid with alcohol odor.

| Solubility in water: Soluble.

EXTINGUISHING MEDIA: Use NFPA class B fire extinguisher (carbon dioxide, all purpose dry chemical or alcohol foam) designed to extinguish flammable liquid fires.

FIRE & EXPLOSION HAZARDS:During emergency conditions, overexposure to decomposition product may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention immediately.

HAZARDOUS DECOMPOSITION PRODUCTS: Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide.

SPECIAL FIREFIGHTING PROCEDURES: Firefighter should wear self-contained breathing apparatus. Water maybe ineffective, but may be used to cool exposed containers to prevent pressure build-up or explosion. Fog nozzle preferred for dispensing water.

SECTION 5 - REACTIVITY DATA

IS PRODUCT STABLE: Stable under normal conditions.

CONDITIONS TO AVOID FOR STABILITY: Keep away from all sources of ignition, open flame, sparks, excessive heat.

INCOMPATIBILITY (Materials to Avoid): Strong acids, alkaline materials, or oxidizing agents.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID FOR POLYMERIZATION: None Known.

SECTION 6 - EXPOSURE CONTROL DATA

VENTILATION: Local exhaust should be adequate.

RESPIRATORY PROTECTION: In areas with restricted ventilation use approved chemical-mechanical filter respirator designed to remove a combination of vapors and particulate.

PROTECTIVE EQUIPMENT: Use solvent impermeable gloves, if needed, to prevent repeated or prolonged skin contact. Wear chemical splash goggles or full face shield to prevent eye contact.

DRK PRACTICES: Use suggested protective equipment and adequate ventilation.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before each break period, and at the end of the shift.

MATERIAL SAFETY DATA SHEET • DBA PRODUCTS CO., INC. • PRODUCT #7583-C • PAGE 2 OF 2

SECTION 7 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Ventilate spill area, wear eye protection, and appropriate protective clothing and respiratory protection for the size of the spill. Soak up liquid with an inert absorbent (sand, vermiculite), using non-sparking tools. Place used absorbent into appropriate waste containers. Cover and remove from working area. Wash down spill area with water. Prevent material from entering sewers.

WASTE DISPOSAL METHODS: Dispose of only in accordance with federal, state and local regulations.

SECTION 8 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use. Do not store near heat. Adequate ventilation is required do not store in areas where temperature will exceed 120°F.

OTHER PRECAUTIONS: Minimize inhalation of vapors. Do not take internally. Close container after each use. Launder any contaminated clothing before reuse

SECTION 9 - SHIPPING INFORMATION					
SHIPPING INFORMATION	U.S. D.O.T. INFORMATION	INTERNATIONAL INFORMATION			
SHIPPING NAME	Combustible Liquid	Flammable Liquid NOS (contains Isopropyt Alcohol)			
HAZARD CLASS	N/A	Class #3			
U.N. NUMBER	N/A	UN 1993			
PACKAGING GROUP	N/A	iii			
LABELS	N/A	Flammable Liquid			

The information contained herein is based on the data considered to be accurate. While the information is believed to be reliable, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereor. Since the use of this information and the conditions and use of this product are controlled by the user, it is the user's obligation to determine the conditions of the safe use of the product.