

11/09/05



5332 Dansher Road
 Countryside, Illinois 60525

MATERIAL SAFETY DATA SHEET

MSDS No. N640

Revision Date: 9/19/2001

Emergency Phones: 708-579-8100 (NYCO)

PLEASE NOTE: This MSDS is being provided to your company for the purpose of providing current health and safety information to your management and for your employees who work with this material. Please read the information on these sheets, and then provide this information to those people at your company whose responsibility it is to comply with FEDERAL and STATE RIGHT-TO-KNOW regulations. Also make this information available to any employee who requests it. It is your obligation to comply with these regulations.

SECTION I - PRODUCT IDENTITY

PRODUCT NAME: Defoam

Formula: Mixture silicone emulsion and additives in water

HMIS RATINGS

| | |
|--------------------------|-----------------------------------|
| Health = 1 (Slight) | Flammability = 1 (Minimal) |
| Reactivity = 0 (Minimal) | Protection = B (Goggles & Gloves) |

SECTION II - HAZARDOUS INGREDIENTS

| | PERCENT | TLV | CARCINOGEN (OSHA, TP, IARC) |
|---|---------|---------|--------------------------------|
| Dipropylene glycol methyl ether CAS No. 34590-94-8 | <3% | 100 ppm | No |

SECTION III - CHEMICAL AND PHYSICAL

| | |
|--|--|
| Appearance: White emulsion Odor: Pleasant pH: 6.0-8.0 Water Solubility: Dispersible | Boiling Point: est.: 212° F Melting Point: N/A Spec. Gravity (H ₂ O = 1): 1.00 Vapor Pressure (mm Hg): N/A VOC Content: 2.0% (N.A.) |
|--|--|

SECTION IV - FIRE AND EXPLOSION HAZARDS

| | |
|---------------------------------------|--|
| Flash Point (Method): >200° F. Cl.Cp. | Explosion Limits: Upper: N/A Lower: N/A |
|---------------------------------------|--|

Extinguishing Media: Water, carbon dioxide, dry chemical.
 Special Firefighting Procedures and Hazards: Minimize prolonged skin and eye contact. Wear eye protection if exposure is likely.

SECTION V - REACTIVITY INFORMATION

Stable:

Unstable:

Precautions:

Incompatibility: Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition or burning may produce carbon monoxide/dioxide and/or silicone oxides and hydrocarbon.

Hazardous Polymerization: Occurs:

Does Not Occur:

SECTION VI - HEALTH HAZARDS - PROTECTIVE MEASURES - FIRST AID

Inhalation: Breathing of mists may cause irritation. Remove to fresh air. Give artificial respiration or oxygen if needed.

Skin: Extended contact may cause irritation. Prolonged contact with 2-butoxyethanol may result in the absorption of potentially harmful amounts leading to possible liver and kidney damage. Wear protective gloves if necessary. Flush skin with water for 15 minutes. Get medical attention for any irritation.

Eyes: Can cause irritation. Wear goggles as needed. Flush immediately with water for 15 minutes. Get prompt medical attention if needed.

Ingestion: May cause a mild gastric disturbance. Drink lots of water. Do not induce vomiting. Get medical attention if effects persist.

Most likely routes of entry: Skin, Eyes.

Other Important Medical or Precautionary Information: None

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Spills and Leaks: This material is very slippery when wet. Use good housekeeping. Maintain ventilation. Avoid contact with strong oxidizing agents.

Storage and Handling: Check daily for any leaks from containers, vessels, pumps, and piping.

Waste Disposal: Product may be disposable in sewers if local regulations permit. Otherwise send to a licensed treatment facility.

Empty Containers: Rinse well before handling and disposal. Observe label precautions.

Other Precautions: None

SECTION VIII - REGULATORY INFORMATION

Reportable for SARA Title III, S.313 (Form R): None

The information herein has been compiled from sources believed to be reliable and is accurate to the best of our knowledge. However, NYCO Products Company cannot give any guarantees regarding information from other sources, and expressly does not make any warranties, nor assumes any liability, for its use.