



# MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P.O. BOX 399 • HUDSON, OHIO 44236 • 1-800-321-3444 • FAX (216) 650-1453

## EASY SURFACE PREP

### SECTION I - PRODUCT IDENTIFICATION

NAME.....The Flood Company  
 ADDRESS.....1212 Barlow Road  
                   P. O. Box 399  
                   Hudson, OH 44236  
 EMERGENCY TELEPHONE NO.....800-321-3444 or your local poison  
   control center  
 PRODUCT NAME.....EASY SURFACE PREP  
 PRODUCT CLASS.....Clear solvent cleaner  
 HMIS RATINGS.....HEALTH  2  
   FLAMMABILITY  2  
   REACTIVITY  0  
   PERSONAL PROTECTIVE EQUIPMENT                          G

### SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	PERCENT BY WT.	OCCUPATIONAL EXPOSURE LIMIT		VAPOR PRESSURE
		TLV	PEL	
PETROLEUM DISTILLATES	90			<7mm Hg @ 100 F.
Mixture of CAS #64742-88-7	70-90 %	100	100	
64742-95-6	2-5 %	100	100	
25551-13-7	1-5 %	25	25	

### SECTION III - PHYSICAL DATA

BOILING RANGE..... 325-395 DEGREES F.  
 VAPOR DENSITY..... HEAVIER THAN AIR  
 EVAPORATION RATE..... SLOWER THAN ETHER  
 VOLATILE VOLUME..... 92%  
 WEIGHT/GALLON..... 6.59 LBS/GAL

MATERIAL SAFETY DATA SHEET

EASY SURFACE PREP

---

---

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

---

---

FLAMMABILITY CLASSIFICATION: OSHA - COMBUSTIBLE LIQUID; CLASS II  
DOT - FLAMMABLE LIQUID, UN 1263  
FLASH POINT: 112|F. T.C.C. LEL: NOT ESTABLISHED

EXTINGUISHING MEDIA: (X) FOAM ( ) ALCOHOL FOAM (X) CO2 (X) DRY CHEMICAL  
(X) WATER FOG ( ) OTHER

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible. Exposure of closed containers to heat can cause disruptive pressure. Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, and ignition sources at locations distant from material handling point. Do not flush into public sewer system.

SPECIAL FIREFIGHTING PROCEDURES: Water may be ineffective as extinguishing medium but may be used to cool closed containers exposed to heat. Respiratory protection should be self-contained, breathing apparatus type with a full face piece operated in a pressure demand or other positive pressure mode.

---

---

SECTION V - HEALTH HAZARD DATA

---

---

EFFECTS OF OVEREXPOSURE: Vapors may cause narcosis and irritation of respiratory system. Liquid is irritating to eyes and liquid material may be harmful or fatal if swallowed. Excessive, prolonged, or repeated exposure may dry skin or cause irritation.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: EYES - Can cause irritation, redness, tearing, and blurred vision.

SKIN - Prolonged or repeated contact can cause moderate irritation, defatting, and dermatitis.

INHALATION - Prolonged or repeated contact can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation.

SWALLOWING - Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

PRIMARY ROUTE(S) OF ENTRY: ( ) DERMAL (X) INHALATION ( ) INGESTION



# MATERIAL SAFETY DATA SHEET

THE FLOOD COMPANY P.O. BOX 399 • HUDSON, OHIO 44236 • 1-800-321-3444 • FAX (216) 650-1453

## EASY SURFACE PREP

EMERGENCY AND FIRST AID PROCEDURES: SKIN - Thoroughly wash exposed area with soap and water. Remove contaminated clothing and launder before reuse. Discard oil-soaked leather goods.  
EYES - Flush with large amounts of water for 15 minutes holding eyelids apart and away from eyeball. Get medical attention.  
SWALLOWING - DO NOT INDUCE VOMITING DUE TO DANGER OF ASPIRATING OIL INTO LUNGS. After spontaneous vomiting, monitor for breathing difficulty. This effect may be delayed. IF SYMPTOMS APPEAR, PERSIST, OR IF EXPOSURE IS SEVERE, SEEK PROMPT MEDICAL HELP. Remove to fresh air.  
Note to physician: Aspiration of liquid petroleum products into lungs may cause severe pneumonitis (oil pneumonia). Vomiting should not be induced and gastric lavage should be undertaken with consideration of endotracheal intubation, especially with an unconscious patient.

## SECTION VI - REACTIVITY DATA

STABILITY: ( ) UNSTABLE (X) STABLE

HAZARDOUS POLYMERIZATION: ( ) MAY OCCUR (X) WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion may produce carbon monoxide, carbon dioxide and various hydrocarbons.

CONDITIONS TO AVOID: Contact with heat, flames or strong oxidizing agents.

## SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of vapor ignitions, ventilate area and stop spill at source.  
SMALL SPILL - Remove liquid by oil-absorbing materials. LARGE SPILL - Exclude persons not wearing protective equipment, dike area of spill and pump liquid into salvage tank.

WASTE DISPOSAL METHOD: Dispose in accordance with applicable pollution control regulations. If this product becomes a waste material, it would be considered a hazardous waste (ignitable). Waste code D001.

MATERIAL SAFETY DATA SHEET

EASY SURFACE PREP

---

---

SECTION VIII - SAFE HANDLING AND USE INFORMATION

---

---

**RESPIRATORY PROTECTION:** If TLV of the product or any component is exceeded, a NIOSH/OSHA jointly approved, air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/OSHA respirators under specified conditions (see your safety equipment supplier). Engineering or administrative controls should be implemented to reduce exposure.

**VENTILATION:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

**PROTECTIVE GLOVES:** Oil resistant if prolonged liquid contact is likely.

**EYE PROTECTION:** Goggles with side shields when spraying or where splashing is likely.

**OTHER PROTECTIVE EQUIPMENT:** Oil repellent, protective clothing if prolonged liquid contact is likely.

**HYGIENIC PRACTICES:** Wash hands with soap and water before eating, drinking, smoking, or using toilet facilities. Launder contaminated clothing before reuse.

---

---

SECTION IX - SPECIAL PRECAUTIONS

---

---

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: COMBUSTIBLE.** Prevent contact with flames or hot surfaces. Do not store near heat. Keep containers closed when not in use. Avoid prolonged contact with skin. Avoid breathing concentrated vapors.

**OTHER PRECAUTIONS:** Store only in well-ventilated areas. Store out of sun and away from heat.

---

---

This information is furnished without warranty, except it is accurate to the best of The Flood Company's knowledge or obtained from sources believed to be accurate. This information is not to be construed as representation for which The Flood Company assumes legal responsibility expressed or implied.