

BORDEN -- ELMERS RUBBER CEMENT
MATERIAL SAFETY DATA SHEET
NSN: 804000N071775
Manufacturer's CAGE: 86142
Part No. Indicator: B
Part Number/Trade Name: ELMERS RUBBER CEMENT

=====
General Information
=====

Company's Name: BORDEN INC
Company's Street: 180 EAST BROAD ST
Company's City: COLUMBUS
Company's State: OH
Company's Country: US
Company's Zip Code: 43215
Company's Emerg Ph #: 614-431-6600
Company's Info Ph #: 800-848-9400; 614-431-6680
Record No. For Safety Entry: 002
Tot Safety Entries This Stk#: 002
Status: SMJ
Date MSDS Prepared: 20FEB92
Safety Data Review Date: 29APR97
MSDS Serial Number: CDPRD

=====
Ingredients/Identity Information
=====

Proprietary: NO
Ingredient: ISOPROPYL ALCOHOL; (ISOPROPANOL) (SARA 313)
Ingredient Sequence Number: 01
Percent: 1-5
NIOSH (RTECS) Number: NT8050000
CAS Number: 67-63-0
OSHA PEL: 400 PPM
ACGIH TLV: 400 PPM;500 STEL

Proprietary: NO
Ingredient: HEPTANE
Ingredient Sequence Number: 02
Percent: >70
NIOSH (RTECS) Number: MI7700000
CAS Number: 142-82-5
OSHA PEL: 500 PPM
ACGIH TLV: 400 PPM;500 STEL

Proprietary: NO
Ingredient: SUPP DATA:VAPS. DO NOT CUT, PUNCTURE/WELD ON/NEARBY. HANDLE I/
A/W GOOD INDUSTRIAL SFTY PRACTICES. THESE PRACTICES(ING 4)
Ingredient Sequence Number: 03
NIOSH (RTECS) Number: 9999999ZZ
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE

Proprietary: NO
Ingredient: ING 3:INCLUDE AVOIDING UNNECESSARY EXPOSURE & REMOVAL OF
MATERIAL FROM EYES, SKIN & CLOTHING.
Ingredient Sequence Number: 04
NIOSH (RTECS) Number: 9999999ZZ
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE

Proprietary: NO
Ingredient: VENT:BE PROVIDED TO KEEP AIR CONTAMINANT CONCENTRATION LEVELS
BELOW ACCEPTABLE CRITERIA.

Ingredient Sequence Number: 05
NIOSH (RTECS) Number: 9999999ZZ
OSHA PEL: NOT APPLICABLE
ACGIH TLV: NOT APPLICABLE

=====

Physical/Chemical Characteristics

=====

Appearance And Odor: OPAQUE LIQUID; MILD SOLVENT ODOR.
Boiling Point: 194F,90C
Vapor Density (Air=1): >1
Specific Gravity: 0.71
Evaporation Rate And Ref: <1 (ETHER=1)
Solubility In Water: NEGLIGIBLE
Percent Volatiles By Volume: 90

=====

Fire and Explosion Hazard Data

=====

Flash Point: 14F,-10C
Flash Point Method: TCC
Extinguishing Media: IN CASE OF FIRE, USE WATER SPRAY, DRY CHEMICAL, FOAM OR CO*2.
Special Fire Fighting Proc: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N). USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.
Unusual Fire And Expl Hazrds: EXTREMELY FLAMM LIQ & VAP. KEEP LIQ & VAP AWAY FROM HEAT, SPKS, FLAME & OTHER IGNIT SOURCES INCL, BUT NOT LTD TO, PILOT LIGHTS, HEATERS, CIGARETTES, (SUPP DATA)

=====

Reactivity Data

=====

Stability: YES
Cond To Avoid (Stability): NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: ACIDS, BASES, AMINES.
Hazardous Decomp Products: CO, CO*2.
Hazardous Poly Occur: NO
Conditions To Avoid (Poly): NOT RELEVANT

=====

Health Hazard Data

=====

LD50-LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
Route Of Entry - Inhalation: YES
Route Of Entry - Skin: YES
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: RISK OF DMG & EFTS DEPENDS UPON DURATION & LEVEL OF EXPOS. NOT TOX DERMALLY, ORALLY/BY INHAL. INHAL:NOT EXPECTED TO BE HARMFUL UNDER NORMAL CNDTNS OF USE. HOWEVER, OVEREXP MAY CAUSE CNS DEPRESS. ALSO, IF ALLOWED TO BECOME AIRBORNE, MAY CAUSE IRRIT OF NOSE, THROAT & LUNGS. SKIN:MAY CAUSE IRRIT ON PRLNG/(EFTS OF OVEREXP)
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NOT RELEVANT
MAY CAUSE IRRIT ON PRLNG/RPTD CONT. SLIGHTLY IRRIT. ING 1:SUSPECT REPRO HAZ. MAY CAUSE REPRO DISORDERS BASED ON ANIMAL DATA. MAY CAUSE LIVER/KIDNEY DMG BASED ON ANIMAL DATA. CAN CAUSE CNS DEPRESS. SIGNS & SYMPS MAY INCL HDCH, DIZZ, NAUS, VOMIT, UNCON & EVEN ASPHY. (SUPP DATA)
Med Cond Aggravated By Exp: NONE SPECIFIED BY MANUFACTURER.
Emergency/First Aid Proc: INGEST:DILUTE BY DRINKING LARGE QUANTITIES OF WATER. IMMEDIATELY CONTACT POISON CONTROL CENTER OR HOSPITAL EMERGENCY ROOM FOR ANY OTHER ADDITIONAL TREATMENT DIRECTIONS. INHAL:REMOVE TO FRESH AIR. SKIN:FLUSH W/WATER. EYES:IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES. CALL MD IF IRRITATION PERSISTS.

=====

Precautions for Safe Handling and Use

Steps If Matl Released/Spill: ELIMINATE ALL IGNITION SOURCES. SOAK UP W/ ABSORBENT MATERIAL & REMOVE TO CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Method: RECOVER FREE LIQUID. ABSORB RESIDUE & DISPOSE OF ACCORDING TO LOCAL, STATE/PROVINCIAL & FEDERAL REQUIREMENTS.

Precautions-Handling/Storing: STORE IN A COOL, DRY PLACE. KEEP CONTAINERS TIGHTLY CLOSED. KEEP AWAY FROM HEAT, SPARKS, FLAME & OTHER IGNITION SOURCES. USE W/ADEQUATE VENTILATION.

Other Precautions: AVOID PRLNG/RPTD BRTHG OF VAP. PERS W/SENSITIVE SKIN SHOULD AVOID PRLNG, CONTINUOUS CONT W/SKIN. IF IRRIT DEVELS, DISCONTINUE USE. AVOID PRLNG/RPTD CONT W/EYES. INSTRUCT YOUR WORKERS TO HANDLE THIS PROD PROPERLY. BEFORE USING/HNDLG, (SUPDAT)

Control Measures

Respiratory Protection: WHERE AIR CONTAMINANTS CAN EXCEED ACCEPT CRITERIA, USE NIOSH APPROVED RESPIRATORY PROT EQUIP. NIOSH APPROVED RESPS SHOULD BE SELECTED BASED ON FORM & CONC OF CONTAMS IN AIR I/A/W OSHA 29 CFR 1910.134/ OTHER APPLIC STANDARDS OR GUIDELINES.

Ventilation: IF AIRBORNE CONTAMS ARE GENERATED WHEN MATL IS HEATED/HNDLD, SUFFICIENT VENT IN VOL & AIR FLOW PATTERNS SHOULD (ING 5)

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: EYE WASH FOUNTAIN & DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA (FP N).

Work Hygienic Practices: HANDLE I/A/W GOOD INDUSTRIAL HYGIENE PRACTICES. WASH THOROUGHLY AFTER HANDLING.

Suppl. Safety & Health Data: EXPLO HAZ:ELEC MOTORS & STATIC DISCHARGE. VAP IS HVR/AIR & MAY SETTLE IN LOW PLACES/TRAVEL OUTWARD TO SOURCE OF IGNIT & FLASHBACK. EFTS OF OVEREXP:ING 2:CAN CAUSE CNS DEPRESS. SIGNS & SYMPS MAY INCL HDCH, DIZZ, NAUS, VOMIT, UNCON & EVEN ASPHY. OTHER PREC:READ & UNDERSTAND MSDS. EMPTY CNTNR:MAY CONTAIN EXPLO (ING 3)

Transportation Data

Disposal Data

Label Data

Label Required: YES

Technical Review Date: 29APR97

Label Date: 11APR97

Label Status: G

Common Name: ELMERS RUBBER CEMENT

Chronic Hazard: NO

Signal Word: DANGER!

Acute Health Hazard-Moderate: X

Contact Hazard-Slight: X

Fire Hazard-Severe: X

Reactivity Hazard-None: X

OVEREXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM DEPRESSION. ALSO, IF ALLOWED MAY CAUSE IRRITATION ON PROLONGED OR REPEATED CONTACT. EYES:IRRITATION.

CHRONIC:NONE LISTED BY MANUFACTURER.

Protect Eye: Y

Protect Skin: Y

Protect Respiratory: Y

Label Name: BORDEN INC

Label Street: 180 EAST BROAD ST

Label City: COLUMBUS

Label State: OH
Label Zip Code: 43215
Label Country: US
Label Emergency Number: 614-431-6600

=====
URL for this msds <http://siri.org>. If you wish to change, add to, or delete information in this archive please sent updates to dan@siri.org.