**** MATERIAL SAFETY DATA SHEET ****

Ethylene Glycol 09400

**** SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION ****

MSDS Name: Ethylene Glycol

Catalog Numbers:

AC410010040, AC410010200, S79007, S80005, S80005-1, S80005-2, S800051, BP230-1, BP230-4, E177-20, E177-4, E178-1, E178-200, E178-4, E178-500, E178J4, S800052, ZZE1785C15

Synonyms:

1,2-Dihydroxyethane; 1,2-Ethanediol; Ethylene alcohol; Ethylene dihydrate.

Company Identification: Fisher Scientific 1 Reagent Lane Fairlawn, NJ

For information, call: 201-796-7100 Emergency Number: 201-796-7100

Emergency Number: 201-796-7100 For CHEMTREC assistance, call: 800-424-9300

For International CHEMTREC assistance, call: 703-527-3887

**** SECTION 2 - COMPOSITION, INFORMATION ON INGREDIENTS ****

ł	+				۴.
ŀ	CAS#	Chemical Name	%	EINECS#	1
ł					1
١	107-21-1	Ethylene glycol	99.0	203-473-3	3

Hazard Symbols: XN Risk Phrases: 22

**** SECTION 3 - HAZARDS IDENTIFICATION ****

EMERGENCY OVERVIEW

Appearance: clear, colorless liquid. Warning! May cause respiratory tract irritation. Hygroscopic. This substance has caused adverse reproductive and fetal effects in animals. May cause kidney damage. May cause central nervous system effects. May cause eye and skin irritation. May cause cardiac disturbances. Harmful or fatal if swallowed. Target Organs: Kidneys, heart, central nervous system

Potential Health Effects

Eye:

May cause moderate eye irritation.

Skin:

May cause skin irritation. Low hazard for usual industrial handling. Ingestion:

May cause nausea and vomiting. Toxicity follows 3-stage progression. (1) involves central nervous system effects including paralysis of eye muscles, convulsions, and coma. Metabolic acidosis and cerebral swelling may also occur. (2) involves cardiopulmonary system with symptoms of hypertension, rapid heart beat, and possible cardiac failure. (3) involves severe kiqney abnormalities including possible renal

Inhalation:

May cause respiratory tract irritation. Heated or misted substance may cause headache, irregular eye movements, and possible coma. Chronic:

May cause kidney injury.

**** SECTION 4 - FIRST AID MEASURES ****

Eves:

Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid immediately. Do NOT allow victim to rub or keep eyes closed.

Flush skin with plenty of soap and water for at least 15 minutes while removing contaminated clothing and shoes. Get medical aid if irritation develops or persists. Wash clothing before reuse.

Ingestion:

If victim is conscious and alert, give 2-4 cupfuls of milk or water. Never give anything by mouth to an unconscious person. Get medical aid immediately.

Inhalation:

Remove from exposure to fresh air immediately. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid if cough or other symptoms appear.

Notes to Physician: Ethanol may inhibit methanol metabolism.

**** SECTION 5 - FIRE FIGHTING MEASURES ****

General Information:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full

6,852

PACIE: 7 DATE: 07/17/03 ACCT: 888235001 INDEX: H31963909 CAT NO: E17720 PO NBR: VS 7-15-03

protective gear. Vapors may be heavier than air. They can spread along the ground and collect in low or confined areas.

Extinguishing Media: In case of fire, use water, dry chemical, chemical foam, or alcohol-resistant foam. Water or foam may cause frothing. Use agent most appropriate to extinguish fire.

Autoignition Temperature:410 deg C (770.00 deg F) Flash Point: 111 deg C (231.80 deg F) Explosion Limits, lower:3.20 vol %

Explosion Limits, upper:15.30 vol % NFPA Rating: (estimated) Health: 1; Flammability: 1; Instability: 0

**** SECTION 6 - ACCIDENTAL RELEASE MEASURES ****

General Information: Use proper personal protective equipment as indicated in Section 8. Spills/Leaks:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Remove all sources of ignition. Provide ventilation.

**** SECTION 7 - HANDLING and STORAGE ****

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Use with adequate ventilation. Ground and bond containers when transferring material. Avoid contact with eyes, skin, and clothing. Avoid ingestion and inhalation.

Keep away from sources of ignition. Store in a cool, dry, well-ventilated area away from incompatible substances.

**** SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION ****

Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

- 1	+				4
١	Chemical Name	ACGIH	NIOSH	OSHA - Final PELs	ĺ
	Ethylene glycol	100 mg/m3 Ceiling (aerosol only)	none listed	none listed	
П	1				!

OSHA Vacated PELs:

Ethylene glycol:

No OSHA Vacated PELs are listed for this chemical.

Personal Protective Equipment

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Skin:

Wear appropriate protective gloves to prevent skin

Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Respirators:

Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Always use a NIOSH or European Standard EN 149 approved respirator when necessary.

**** SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES ****

Physical State: Color: clear, colorless Odor: odorless Not available. : Ho Vapor Pressure: Vapor Density: 2.1 (air=1) Evaporation Rate: Not available. 21cP @ 20 deg Viscosity: Boiling Point: 195 deg C @ 760.00mm Hg -13 deg C Freezing/Melting Point: Decomposition Temperature: soluble in water

Solubility in water: Specific Gravity/Density: Molecular Formula: Molecular Weight:

1.1200g/cm3 C2H6O2

62.06

**** SECTION 10 - STABILITY AND REACTIVITY ****

6,853

PAGE: 3 07/17/03 DATE ACCT: 888235001 INDEX: H31963909 CAT NO: E17720 PO NBR: VS 7-15-03 Chemical Stability: Stable at room temperature in closed containers under normal storage and handling conditions. Conditions to Avoid: Incompatible materials, ignition sources, moisture, excess heat. Incompatibilities with Other Materials:
Chlorosulfonic acid, dimethyl terephthalate, oleum, phosphorus pentasulfide, silvered-copper wire, sodium hydroxide, sulfuric acid, titanium butoxide. Causes ignition at room temperature with chromium trioxide, potassium permanganate, and sodium peroxide. Causes ignition at 100C with ammonium dichromate, silver chlorate, sodium chloride, and uranyl nitrate.
Hazardous Decomposition Froducts: Carbon monoxide, irritating and toxic fumes and gases, carbon dioxide. Hazardous Polymerization: Has not been reported. **** SECTION 11 - TOXICOLOGICAL INFORMATION **** RTECS#: CAS# 107-21-1: KW2975000 LD50/LC50: /LC50: CAS# 107-21-1: Draize test, rabbit, eye: 500 mg/24H Mild; Draize test, rabbit, eye: 100 mg/1H Mild; Draize test, rabbit, eye: 1440 mg/6H Moderate; Oral, mouse: LD50 = 5500 mg/kg; Oral, rat: LD50 = 4700 mg/kg; Skin, rabbit: LD50 = 9530 uL/kg. Carcinogenicity: Ethylene glycol -ACGIH: A4 - Not Classifiable as a Human Carcinogen (aerosol) Epidemiology:
No data available. Teratogenicity:
No data available.
Reproductive Effects: No data available. Neurotoxicity: No data available. Mutagenicity: No data available. Other Studies: Please refer to RTECS KW2975000 for additional information. **** SECTION 12 - ECOLOGICAL INFORMATION **** Ecotoxicity: Fish: Rainbow trout: LC50 = 41000 mg/L; 96 Hr.; UnspecifiedFish: Bluegill/Sunfish: LC50 = 27500-41000 mg/L; 96 Hr.; UnspecifiedFish: Goldfish: LC50 = 27500-41000 mg/L; 96 Hr.; UnspecifiedWater flea LC50 = 46300 mg/L; 48 Hr.; UnspecifiedBacteria: Phytobacterium phosphoreum: EC50 =620 mg/L; 30 minutes; Microtox testGoldfish LD50= >5000mg/L/24Hr Guppies LC50= 493,000ppm/7D Shrimp (salt water) LC50= 100ppm/48Hr **** SECTION 13 - DISPOSAL CONSIDERATIONS **** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste.

US EPA guidelines for the classification determination are listed in
40 CFR Parts 261.3. Additionally, waste generators must consult state
and local hazardous waste regulations to ensure complete and accurate classification. RCRA P-Series: None listed. RCRA U-Series: None listed. **** SECTION 14 - TRANSPORT INFORMATION **** IIS DOT No information available Canadian TDG No information available. **** SECTION 15 - REGULATORY INFORMATION **** US FEDERAL CAS# 107-21-1 is listed on the TSCA inventory. Health & Safety Reporting List None of the chemicals are on the Health & Safety Reporting List. Chemical Test Rules None of the chemicals in this product are under a Chemical Test Rule. Section 12b None of the chemicals are listed under TSCA Section 12b. TSCA Significant New Use Rule
None of the chemicals in this material have a SNUR under TSCA. CERCLA Hazardous Substances and corresponding RQs CAS# 107-21-1: 5000 lb final RQ: 2270 kg final RQ SARA Section 302 Extremely Hazardous Substances None of the chemicals in this product have a TPQ.

6,854

PAGE: 4 DATE: 07/17/03 ACCT: 888235001 INDEX: H31963909 CAT NO: E17720 PO NBR: VS 7-15-03 SARA Codes CAS # 107-21-1: acute, chronic. Section 313 This material contains Ethylene glycol (CAS# 107-21-1, 99 0%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 372. Clean Air Act: CAS# 107-21-1 is listed as a hazardous air pollutant (HAP). This material does not contain any Class 1 Ozone depletors. This material does not contain any Class 2 Ozone depletors. Clean Water Act: None of the chemicals in this product are listed as Hazardous Substances under the CWA. None of the chemicals in this product are listed as Priority Pollutants under the CWA. None of the chemicals in this product are listed as Toxic Pollutants under the CWA. None of the chemicals in this product are considered highly hazardous by OSHA. STATE Ethylene glycol can be found on the following state right to know lists: California, New Jersey, Florida, Pennsylvania, Minnesota, Massachusetts. California No Significant Risk Level: None of the chemicals in this product are listed. European/International Regulations European Labeling in Accordance with EC Directives Hazard Symbols: XN Risk Phrases:
R 22 Harmful if swallowed. Safety Phrases: WGK (Water Danger/Protection) CAS# 107-21-1: 0 United Kingdom Occupational Exposure Limits
CAS# 107-21-1: OES-United Kingdom, TWA 10 mg/m3 TWA (particulate); 52 mg/m3 TWA (vapour) CAS# 107-21-1: OES-United Kingdom, STEL 104 mg/m3 STEL (vapour) United Kingdom Maximum Exposure Limits Canada CAS# 107-21-1 is listed on Canada's DSL List. This product has a WHMIS classification of D2A. CAS# 107-21-1 is listed on Canada's Ingredient Disclosure List. Exposure Limits
CAS# 107-21-1: OEL-AUSTRALIA:TWA 60 mg/m3;STEL 120 mg/m3 OEL-BELGIUM:STEL 50 ppm (127 mg/m3)
OEL-DENMARK:STEL 50 ppm (130 mg/m3)
OEL-DENMARK:TWA 10 mg/m3 OEL-DENMARK:TWA 10 mg/m3
OEL-FINLAND:TWA 10 mg/m3;STEL 20 mg/m3
OEL-FINLAND:TWA 50 ppm (125 mg/m3);STEL 75 ppm (190 mg/m3)
OEL-FRANCE:STEL 50 ppm (125 mg/m3)
OEL-HUNGARY:STEL 50 mg/m3;Skin
OEL-THE NETHERLANDS:TWA 10 mg/m3
OEL-THE NETHERLANDS:TWA 50 ppm (125 mg/m3)
OEL-RUSSIA:STEL 5 mg/m3 OEL-SWEDEN:TWA 50 ppm (130 mg/m3); STEL 75 ppm (19 mg/m3) OEL-SWITZERLAND:TWA 1 mg/m3
OEL-SWITZERLAND:TWA 50 ppm (125 mg/m3)
OEL-UNITED KINGDOM:TWA 10 mg/m3
OEL-UNITED KINGDOM:TWA 60 mg/m3;STEL 125 mg/m3
OEL IN BULGARIA, COLOMBIA, JORDAN, KOREA check ACGIH TLV OEL IN NEW ZEALAND, SINGAPORE, VIETNAM check ACGI TLV **** SECTION 16 - ADDITIONAL INFORMATION **** MSDS Creation Date: 5/12/1999 Revision #2 Date: 8/02/2000

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no way shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howscever arising, even if the company has been advised of the possibility of such damages.