

# Material Safety Data Sheet

MSDS#: 142-18

Page 1 of 2

Sanford Corporation  
2711 Washington Boulevard  
Bellwood, IL 60104

Telephone Number: 1-800-323-0749  
Initiated By: Susan Nyborg  
Date of Last Revision: June 1, 2001  
Medical Emergency No: 1-800-228-5635

## Section One: Product Identification

Product Name: Expo<sub>8</sub> Cleaner for Dry Erase Surfaces

Colors: Clear

Sanford Corporation is a member of The Art and Creative Materials Institute, Inc. This product is certified by the Institute to be labeled in accordance with the voluntary chronic hazard labeling standard ASTM D4236 and is labeled with the CL Cautionary Label Seal. Products bearing the CL Seal are certified to be properly labeled in a program of toxicological evaluation by a medical expert for any known health risks and with information on the safe and proper use of these materials. Conforms to ASTM D4236. This MSDS is applicable for the consumer use of the following product numbers: 81801, 81803

## Section Two: Composition

Water, isopropyl alcohol (67-63-0), ethylene glycol monobutyl ether (111-76-2)

## Section Three: Physical and Chemical Characteristics

**For isopropanol:**  
Boiling Point: 180°F at 760 mm Hg  
Vapor Pressure (mm Hg): 33 mm Hg at 68°F  
Specific Gravity: 0.78 at 77°F  
Solubility in Water: Not available  
Appearance and Odor: Clear liquid; characteristic alcohol odor  
Evaporation Rate: 7.7 (ethyl ether = 1)

## Section Four: Fire and Explosion Hazard Data

Flash Point (Method Used): 105°F (TCC) for mixture  
Flammability Limits (% by volume): Lower: 2.5% for isopropanol Upper: Not available  
Extinguishing Medium: N/A  
Special Fire Fighting Procedures: N/A  
Unusual Fire and Explosion Hazards: N/A

**Section Five: Reactivity Data**

Stability:	Stable
Conditions to Avoid:	Avoid extreme heat and flame.
Chemical Incompatibility:	None known
Hazardous Decomposition:	None known
Hazardous Polymerization:	Will not occur.

**Section Six: Health Hazard Data**

Chemicals Listed as Carcinogens or Potential Carcinogen:

IARC Monographs:	No
National Toxicology Program:	No
OSHA Regulated:	No

WARNING: FLAMMABLE. MAY BE HARMFUL BY INGESTION OR BY SKIN CONTACT. MAY BE HARMFUL IF SWALLOWED. EYE IRRITANT. CONTAINS: 2-BUTOXY ETHANOL/ACETATE, ISOPROPYL ALCOHOL.  
 PRECAUTIONS: Avoid ingestion. Keep away from eyes. Do not store or use near heat or flame. KEEP OUT OF REACH OF CHILDREN. FIRST AID: If eye contact occurs, rinse with tap water for 5-10 minutes. If irritation persists, seek medical care. If skin contact occurs, wash with soap and water for 5 minutes. If swallowed, get prompt medical attention. For further health information, contact a poison control center or call 1-800-228-5635.

**Section Seven: Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material Is Released or Spill:	Wipe up with absorbent material.
Waste Disposal Method:	Dispose in accordance with Federal, State, and Local Regulations.
Precautions to Be Taken in Handling and Storage:	Use in a well-ventilated area.
Other Precautions:	Aim nozzle away from eyes.

**Section Eight: Personal Protection and Exposure Control Measures**

Eye Protection:	None under normal use conditions. Avoid eye contact.
Skin Protection:	None under normal use conditions. Avoid prolonged skin contact.
Respiratory Protection:	None under normal use conditions.
Ventilation:	Use in a well-ventilated area.
Protective Clothing:	None under normal use conditions.

HMIS Code	
Health	2
Flammability	2
Reactivity	0
Personal Protection	N/A

Sanford Corporation has been advised by council that the OSHA Hazard Communication Standard does not apply to the Sanford product described in this MSDS. The reason for the exemption is contained in 29 CFR 1910.1200 (b)(6)(ix), as amended July 1, 1994, per the Code of Federal Regulations. The information contained in this MSDS is forwarded to you for your information, but is not meant to imply that the product is covered by the Hazard Communication Standard, nor is the MSDS meant to comply with all the requirements of the Hazard Communication Standard.

0 = Minimal / 4 = Severe Hazard