



Innovative Signs & Safety Solutions

Home | Order Status | Register | View

Search Item Number

GO

1-800-4

Regulation Resource Site

On-Line Catalog | Site Home | MSDS | CFR | Safety Resources

MSDS Database

Search Resource Site All

GO

Most Po
in Hazard M

Material Safety Data Sheet

Name F/S SOFT PAINT BASIC 16 POT, MS-20932

MSDS bwqjk

Company PLAID ENTERPRISES

FSC 8010

- ▶ Software - Ma
- ▶ RTK Label Blar
- ▶ Diamond Pane
- ▶ Do-It-Yourself
- ▶ Panel Characte

MSDS Safety Information

FSC: 8010
 MSDS Date: 05/25/1993
 MSDS Num: BWQJK
 LIIN: 00N057111
 Product ID: F/S SOFT PAINT BASIC 16 POT, MS-20932
 MFN: 01
 Responsible Party
 Cage: 0ACX4
 Name: PLAID ENTERPRISES
 Address: 1649 INTERNATIONAL BLVD
 City: NORCROSS GA 30091
 Info Phone Number: 404-923-8200
 Emergency Phone Number: 404-923-8200
 Preparer's Name: J. STANLEY
 Published: Y

Fast F

- ▶ Confined Spac
- ▶ Lockout Chec
- ▶ CFR - 1910 L
Fire Protector
- ▶ Asbestos Fact
- ▶ Traffic Signs
- ▶ Parking Signs
- ▶ Industrial Sign
- ▶ Tags

Contractor Summary

Cage: 0ACX4
 Name: PLAID ENTERPRISES
 Address: 1649 INTERNATIONAL BLVD
 City: NORCROSS GA 30091
 Phone: 404-923-8200

Ingredients

Name: NON-HAZARDOUS INGREDIENTS
 OSHA PEL: N/K (FP N)
 ACGIH TLV: N/K (FP N)

RTECS #: 9999999VO
 Name: VOLATILE ORGANIC COMPOUNDS: COATING - 0.25 LB/GAL (30 G/L); MATERIAL -
 0.02 LB/GAL (3 G/L).

Health Hazards Data

LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER.
 Route Of Entry Inds - Inhalation: NO
 Skin: YES
 Ingestion: NO
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO
 Effects of Exposure: SKIN CONTACT:PROLONGED OR REPEATED CONTACT MAY CAUSE LOCAL
 IRRITATION. EYE CONTACT:DIRECT CONTACT W/PRODUCT MAY CAUSE IRRITATION.
 INHAL/INGEST/SKIN ABSORPTION:NOT APPLICABLE.
 Explanation Of Carcinogenicity: NOT RELEVANT
 Signs And Symptions Of Overexposure: SEE HEALTH HAZARDS.
 First Aid: INGEST:CALL MD IMMEDIATELY (FP N). INHAL:REMOVE TO FRESH AIR.
 SUPPORT BREATHING (GIVE O*2/ARTF RESP) (FP N). SKIN:WASH THOROUGHLY W/SOAP



ANDamp; WATER. EYE: PROMPTLY ANDamp; THOROUGHLY FLUSH W/WATER FOR AT LEAST 15 MINUTES. CONSULT MD IF IRRITATION PERSISTS.

Handling and Disposal

Spill Release Procedures: KEEP UNNECESSARY PERSONNEL AWAY, DIKE ANDamp; CONTAIN SPILL W/INERT MATERIAL SUCH AS SAND OR EARTH. TRANSFER MATERIAL INTO A CONTAINER FOR PROPER DISPOSAL. KEEP SPILL OUT OF SEWERS ANDamp; OPEN BODIES OF WATER. F LOORS MAY BECOME SLIPPERY.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSE OF I/A/W ALL LOCAL, STATE ANDamp; FEDERAL WASTE DISPOSAL REGULATIONS.

Handling And Storage Precautions: DO NOT FREEZE. DO NOT STORE AT TEMPERATURES ANDgt;130F.

Fire and Explosion Hazard Information

Extinguishing Media: MEDIA SUITABLE FOR SURROUNDING FIRE (FP N).

Fire Fighting Procedures: USE NIOSH/MSHA APPROVED SCBA ANDamp; FULL PROTECTIVE EQUIPMENT (FP N). USE WATER SPRAY TO COOL CONTAINERS NOT ACTIVELY INVOLVED IN FIRE.

Unusual Fire/Explosion Hazard: PRODUCT IN LIQUID STATE WILL NOT BURN, BUT MAY SPLATTER IF TEMPERATURE EXCEEDS BOILING POINT.

Control Measures

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN (FP N). NOT APPLICABLE.

Protective Gloves: IMPERVIOUS GLOVES (FP N).

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: EYE WASH FOUNTAIN AND DELUGE SHOWER WHICH MEET ANSI DESIGN CRITERIA (FP N).

Work Hygienic Practices: AFTER USING PRODUCT, WASH HANDS BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health: NONE SPECIFIED BY MANUFACTURER.

Physical/Chemical Properties

B.P. Text: 212F, 100C

Spec Gravity: 1.1 (H*20=1)

Evaporation Rate ANDamp; Reference: SLOWER THAN ETHER

Solubility in Water: 100% SOL/DISPERSABLE

Appearance and Odor: VISCOUS LIQUID W/SLIGHT ODOR OF AMMONIA.

Reactivity Data

Stability Indicator: YES

Stability Condition To Avoid: DO NOT FREEZE.

Hazardous Decomposition Products: HAZARDOUS DECOMPOSITION WILL NOT OCCUR.

Hazardous Polymerization Indicator: NO

Conditions To Avoid Polymerization: NOT RELEVANT

Toxicological Information

Ecological Information

MSDS Transport Information

Regulatory Information

Other Information

HAZCOM Label

Product ID: F/S SOFT PAINT BASIC 16 POT, MS-20932
Cage: OACK4
Company Name: PLAID ENTERPRISES
Street: 1649 INTERNATIONAL BLVD
City: NORCROSS GA
Zipcode: 30091
Health Emergency Phone: 404-923-8200
Label Required IND: Y
Date Of Label Review: 02/06/1995
Status Code: C
Label Date: 02/06/1995
Origination Code: G
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: WARNING
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Moderate
Fire Hazard: None
Reactivity Hazard: None
Hazard And Precautions: ACUTE:SKIN CONTACT:PROLONGED OR REPEATED CONTACT MAY
CAUSE LOCAL IRRITATION. EYE CONTACT:DIRECT CONTACT W/PRODUCT MAY CAUSE
IRRITATION. CHRONIC:NONE LISTED BY MANUFACTURER.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

[About](#) | [Contact emedco](#) | [Catalog Request](#)
[Jobs](#) | [Links](#) | [Privacy Statement](#)

©Copyri
800-442-36
FAX 800-344-25
/