

\* \* \* \* \*  
 \* M S D S \*  
 \* \* \* \* \*  
 \* Canadian Centre for Occupational Health and Safety \*  
 \* \* \* \* \* (February, 2002) \*

\*\*\* IDENTIFICATION \*\*\*

MSDS RECORD NUMBER : 2109377  
 PRODUCT NAME(S) : FAST DRY ALKYD ENAMEL  
 PRODUCT IDENTIFICATION : Manufacturer's Code: 36399  
 DATE OF MSDS : 1996-12-17  
 CURRENCY NOTE : This MSDS was provided to CCOHS in electronic form on  
 1999-08-30

\*\*\* MANUFACTURER INFORMATION \*\*\*

MANUFACTURER : International Paint Inc  
 International  
 ADDRESS : 6001 Antoine Drive  
 Houston Texas  
 U.S.A. 77091  
 Telephone: 713-684-1244 (International Info 8AM-5PM CST)  
 MANUFACTURER : International Paint Inc  
 Interlux  
 ADDRESS : 2270 Morris Avenue  
 Union New Jersey  
 U.S.A. 07083-0386  
 Telephone: 908-964-2206 (Interlux Info 8AM-5PM EST)  
 EMERGENCY TELEPHONE NO. : 800-854-6813  
 800-424-9300 (CHEMTREC)

\*\*\* MATERIAL SAFETY DATA \*\*\*

MATERIAL SAFETY DATA SHEET

Product Description: FAST DRY ALKYD ENAMEL  
 Manufacturer's Code: 36399

Revision Date 12/17/96  
 Initial Issue Date 10/01/98

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Description FAST DRY ALKYD ENAMEL  
 Product Description Continued  
 LIGHT BASE  
 Manufacturer's Code: 36399

Manufacturer:  
 International Paint Inc. International Paint Inc.  
 International Interlux  
 6001 Antoine Drive 2270 Morris Avenue  
 Houston, TX 77091 Union, NJ 07083-0386

WHMIS Classification: Class B, Division 2

International Info 8AM-5PM CST: 713-684-1244  
 Interlux Info 8AM-5PM EST: 908-964-2206  
 Emergency Telephone Number: 800-854-6813  
 CHEMTREC #: 800-424-9300

2. OSHA REPORTABLE HAZARDOUS COMPONENTS (20 CFR1910.1200)

Component	Wt %	CAS Registry #
Aliphatic Hydrocarbon SBP3	25-50	064742-89-8
Titanium Dioxide	10-25	013463-67-7
Nonylphenol Ethoxylate	01-10	127087-87-0
Amorphous Silica	01-10	007631-86-9
Aluminum Hydroxide	01-10	021645-51-2
Vinyl Toluene Monomer	01-10	025013-15-4

EXPOSURE LIMITS (ppm)

Page Number

1

Continued

MATERIAL SAFETY DATA SHEET

Product Description: FAST DRY ALKYD ENAMEL  
 Manufacturer's Code: 36399

Component	ACGIH TLVs		OSHA PELs	
	TWA	STEL	TWA	STEL
Aliphatic Hydrocarbon SBP3	300			
Titanium Dioxide	10mg/m3	N/E	15mg/m3 S	N/E
Nonylphenol Ethoxylate	N/E	N/E	N/E	N/E
Amorphous Silica	10mg/m3	N/E	6mg/m3 S	N/E
Aluminum Hydroxide	N/E	N/E	N/E	N/E
Vinyl Toluene Monomer	N/E	N/E	N/E	N/E

- (M) Maximum Exposure Limit
- (S) Occupational Exposure Standard
- (R) Supplier's Recommended Limit
- (+) There is a risk of absorption through unbroken skin.

3. HAZARDS IDENTIFICATION

INHALATION:

Harmful if inhaled. May affect the brain or nervous system causing dizziness, headache or nausea.  
 Causes nose and throat irritation.

EYE CONTACT:

Causes eye burns.

SKIN CONTACT:

Causes skin irritation.  
 May be harmful if absorbed through skin.

INGESTION:

Harmful if swallowed.

Contains an ingredient listed as known or suspected carcinogen?

NTP: No      OSHA: No      IARC: No

Page Number

2

Continued

## MATERIAL SAFETY DATA SHEET

Product Description: FAST DRY ALKYD ENAMEL  
Manufacturer's Code: 36399

## 4. FIRST AID MEASURES

## GENERAL:

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

## INHALATION:

Remove to fresh air. If discomfort is present or breathing is absent get medical attention immediately.

## EYE CONTACT:

Flush immediately with plenty of water for 15 minutes until irritation subsides. If irritation persists, get medical attention.

## SKIN CONTACT:

Flush with large amounts of water. Use soap if available. Remove severely contaminated clothing (including shoes) and wash before reuse. If irritation persists, get medical attention.

## INGESTION:

If swallowed, DO NOT induce vomiting. Keep at rest. Get prompt medical attention.

-----  
5. FIRE AND EXPLOSION DATA

Flashpoint: 59 F 14.9985 C  
OSHA Classification: Flammable Liquid - Class IB  
LEL: .9

## FIRE AND EXPLOSION HAZARDS:

Isolate from heat, sparks, electrical equipment and open flame. Closed containers may explode when exposed to extreme heat. In the absence of electricity, a water spray (a fog nozzle is preferred) may be used to cool containers. Decomposition and combustion products may be toxic.

## EXTINGUISHING MEDIA:

Foam, Carbon Dioxide, Dry Chemical

Page Number

3

Continued

## MATERIAL SAFETY DATA SHEET

Product Description: FAST DRY ALKYD ENAMEL  
Manufacturer's Code: 36399

-----  
6. ACCIDENTAL RELEASE MEASURES

## STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Contain spilled liquid with sand or earth. DO NOT use combustible

materials such as sawdust. Absorb spill with an inert material (e.g., dry sand or earth), then place in a chemical waste container.

---

## 7. HANDLING AND STORAGE

### GENERAL:

Keep container closed. Loosen closure cautiously before opening. Store in a cool, well ventilated place away from incompatible materials. (See Stability and Reactivity Section 10.) Keep away from heat, sparks and flames. Protect material from direct sunlight. Ground and bond containers when transferring materials. Empty containers may retain hazardous properties. Follow all MSDS/label warnings, even after the container is emptied.

---

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### ENGINEERING CONTROLS:

- Provide sufficient ventilation, in volume and pattern, to:
- keep the TLV of the hazardous ingredients below the limits specified in Section Two.
  - remove volatiles produced during cure and decomposition products produced during welding or cutting on surfaces coated with this product.

### PERSONAL PROTECTION:

#### RESPIRATOR:

Do not breathe vapors or spray mist. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacture's directions for respirator use.

Page Number

4

Continued

## MATERIAL SAFETY DATA SHEET

Product Description:  
 Manufacturer's Code:

FAST DRY ALKYD ENAMEL  
 36399

### PROTECTIVE EQUIPMENT:

CLOTHING: As needed, use body protection to avoid contact with product.

EYE: Safety glasses, chemical goggles and/or a face shield should be worn to prevent eye contact.

GLOVES: Wear chemical resistant gloves.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Specific Gravity:	1.034
Boiling Point:	235 F 112.7665 C
Physical State:	liquid
Evaporation Rate:	Slower/ether
Vapour Density:	Heavier than air

-----  
10. STABILITY AND REACTIVITY

## GENERAL:

This product is stable and hazardous polymerization will not occur.

## INCOMPATIBLE MATERIALS AND CONDITIONS TO AVOID:

Strong oxidizing agents.

## HAZARDOUS DECOMPOSITION:

May produce hazardous fumes when heated to decomposition as in welding. Fumes may produce Carbon Dioxide and Carbon Monoxide.

  
-----

Page Number

5

Continued

## MATERIAL SAFETY DATA SHEET

Product Description:

FAST DRY ALKYD ENAMEL

Manufacturer's Code:

36399

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the product itself.

  
-----

## 12. ECOLOGICAL INFORMATION

There is no data available on the product itself.

  
-----

## 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state and federal regulations.  
Do not incinerate unopened containers.

  
-----

## 14. TRANSPORT INFORMATION

DOT (Department of Transportation):  
Proper Shipping Name: Paint  
Hazard Class: Flammable Liquid, 3  
UN Number: UN1263  
Packing Group: Packing Group II

  
-----

## 15. REGULATORY INFORMATION

TSCA (Toxic Substance Control Act):  
Components of this product are listed on the TSCA Inventory.

CERCLA (Comprehensive Response Compensation, and Liability Act):  
We recommend you contact local authorities to determine if there may be other local reporting requirements.

SARA TITLE III (Superfund Amendments and Reauthorization Act):

Page Number

6

Continued

## MATERIAL SAFETY DATA SHEET

Product Description: FAST DRY ALKYD ENAMEL  
Manufacturer's Code: 36399

None known unless chemicals are specified below.

Section 302 Reportable Ingredients

313 Reportable Ingredients  
127087-87-0 Nonylphenol Ethoxylate

CALIFORNIA PROPOSITION 65:  
None known unless specified below

Warning: This product contains a chemical known to the State of California to cause cancer.

---

16. OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, express or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

End of Document

Page Number

7

---

©2001 Canadian Centre for Occupational Health & Safety