

# MATERIAL SAFETY DATA SHEET

## FAST DRY RUST CURB GLOSS WHITE



1. Product And Company Identification			
<b>Supplier</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com		<b>Manufacturer</b> Chase Products Co. 19th and Gardner Road Broadview, IL 60155 USA  Company Contact: Aludia B. Hernandez Telephone Number: 708-865-1000 FAX Number: 708-865-0923 E-Mail: sales@chaseproducts.com Web Site: www.chaseproducts.com	
<b>Supplier Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924		<b>Manufacturer Emergency Contacts &amp; Phone Number</b> Chem-Tel: 1-800-255-3924	
Issue Date: 01/06/2004  Product Name: FAST DRY RUST CURB GLOSS WHITE Chemical Name: 6-5832-2 CAS Number: Not Established MSDS Number: 2281 Product Code: 419-4301-4 Product/Material Uses - Spray Paint			
2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
ACETONE	67-64-1		
BUTANE	106-97-8		
PROPANE	74-98-6		
TOLUENE	108-88-3		15 - 20
V.M. & P. NAPHTHA	64742-89-8		
Hazardous components, according to OSHA, are listed when present at 1.0% or greater. Carcinoges are listed when present at 0.1% or greater.			
3. Hazards Identification			
<b>Primary Routes(s) Of Entry</b> - Ingestion (possible, but considered unlikely), eye contact, skin contact, inhalation. <b>Eye Hazards</b> - Causes eye irritation. <b>Skin Hazards</b> - Causes skin irritation. <b>Ingestion Hazards</b> - This is an aerosol product, ingestion is unlikely to occur. <b>Inhalation Hazards</b> - Deliberate inhalation of concentrate vapor or mist may cause headache, dizziness and nausea.. <b>Chronic/Carcinogenicity Effects</b> - Toluene and xylene have been associated with kidney and liver disorders. Contains less than 1% xylene. Contains less than 0.1% ethylbenzene; IARC has evaluated and classified ethylbenzene as a possible human carcinogen (group 2B) based on sufficient evidence of carcinogenicity in animals, but inadequate evidence for cancer in exposed humans. This product contains less than 0.1% naphthalene. California's Proposition 65: "Warning: This product contains a chemical known to the State of California to cause cancer" <b>Epidemiology</b> - None known <b>Teratogenicity (Birth Defects)</b> - California's Proposition 65: "Warning: this product contains toluene, a chemical known			

# MATERIAL SAFETY DATA SHEET

## FAST DRY RUST CURB GLOSS WHITE

### 3. Hazards Identification - Continued

to the State of California to cause birth defects or other reproductive harm".

**Reproductive Effects** - Suspect reproductive hazard. Contains material which may cause birth defects, based on animal data. This product contains toluene.

**Neurotoxicity** - None known


**Mutagenicity (Genetic Effect)** - None known

**Signs And Symptoms** - Acute: Prolonged inhalation of vapor or mist may cause headache, dizziness and nausea. Prolonged contact with the skin causes irritation. Irritant to eyes.

**Conditions Aggravated By Exposure** - Pre-existing skin, respiratory, liver and kidney disorders.

**Conditions Aggravated By Overexposure** - Pre-existing skin, respiratory, liver and kidney disorders.

### First Aid (Pictograms)



### 4. First Aid Measures

**Eye** - Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.

**Skin** - Wash skin with soap and water. If irritation develops, consult a physician.

**Ingestion** - Ingestion from an aerosol product is unlikely to occur. Contains petroleum distillates. Harmful if swallowed. If accidentally swallowed, do not induce vomiting, call physician immediately.

**Inhalation** - If overcome by vapor move victim to fresh air. If person is not breathing, call 911 or an ambulance, then provide artificial respiration, preferably mouth-to-mouth, if possible. Call a poison control center or doctor for further treatment advise.

### 5. Fire Fighting Measures

**Flash Point:** Not available °F Not available °C

**Flash Point Method:** Not available

**Lower Explosive Limit:** Not available

**Upper Explosive Limit:** Not available

**Fire And Explosion Hazards** - This product is an aerosol product for which **Flame Projection is 18 in, with flashback.** Temperatures above 120 F may cause cans to burst.

**Extinguishing Media** - Use CO2 (Carbon Dioxide), dry chemical, or water fog.

**Fire Fighting Instructions** - Water spray may be used to cool cans in the vicinity of fire or excessive heat.

### 6. Accidental Release Measures

Provide adequate ventilation to area being treated. Soak up spills with chemically inert, absorbent material.

### Handling & Storage (Pictograms)



### 7. Handling And Storage

**Handling And Storage Precautions** - Handle as an extremely flammable material. Store in a cool, dry place away from heat and open flame.

**Handling Precautions** - Avoid getting spray into eyes. Keep out of reach of children

**Storage Precautions** - Keep away from heat, sparks, flame, and other sources of ignition (i.e., pilot lights, electric

# MATERIAL SAFETY DATA SHEET

## FAST DRY RUST CURB GLOSS WHITE

### 7. Handling And Storage - Continued

motors and static electricity).

**AEROSOL STORAGE LEVEL III (NFPA-30B)**

**Work/Hygienic Practices** - Wash hands thoroughly after using this product.

### Protective Clothing (Pictograms)



### 8. Exposure Controls/Personal Protection

**Engineering Controls** - Use with adequate general and local exhaust ventilation.

**Eye/Face Protection** - Conventional eyeglasses to guard against splashing.

**Skin Protection** - Rubber, vinyl or household type gloves.

**Respiratory Protection** - Use in well-ventilated area ONLY. NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. To avoid breathing vapor or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air or use an appropriate, properly fitted respirator (NIOSH approved), or leave the area. NOTE: Follow respirator manufacturer's instructions carefully.

#### **Ingredient(s) - Exposure Limits**

ACETONE

ACGIH TLV-STEL 750 ppm ; ACGIH TLV-TWA 500 ppm ; OSHA PEL-TWA 1,000 ppm

BUTANE

ACGIH TLV-TWA 800 ppm

PROPANE

ACGIH TLV-TWA 2500 ppm ; OSHA PEL-TWA 1,000 ppm

TOLUENE

ACGIH TLV-TWA 50 ppm (Skin) ; OSHA PEL-CEILING 300 ppm ; OSHA PEL-PEAK 500 ppm

OSHA PEL-TWA 200 ppm

V.M. & P. NAPHTHA

ACGIH TLV-TWA 300 ppm

### 9. Physical And Chemical Properties

**Appearance** - Appearance of paint.

**Odor** - Paint odor.

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** Not applicable °F Not applicable °C

**Boiling Point:** Acetone 133 °F Acetone 56 °C

**Specific Gravity:** 0.886

**Percent VOCs:** 60.30

**Solubility:** Insoluble

**Evaporation Rate:** Faster than butyl acetate

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

# MATERIAL SAFETY DATA SHEET

## FAST DRY RUST CURB GLOSS WHITE

### 10. Stability And Reactivity - Continued

**Conditions To Avoid (Stability)** - Temperatures above 120 F

**Incompatible Materials** - Avoid heat, open flame and contact with strong oxidizers.

**Hazardous Decomposition Products** - Thermal decomposition may yield gases like carbon monoxide and carbon dioxide.

**Conditions To Avoid (Polymerization)** - Temperatures above 120 F

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Do not puncture or incinerate container. **If empty:** Place in trash or offer for recycling if available. **If partly filled:** Call your local solid waste agency for disposal instructions.

### 14. Transport Information

**Proper Shipping Name** - ORM-D Consumer Commodity

**Hazard Class**

2.1

**DOT Identification Number**

UN1950

**DOT Shipping Label**

Aerosol Consumer Commodity

### 15. Regulatory Information

**U.S. Regulatory Information** - All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**SARA Hazard Classes**

Acute Health Hazard; Chronic Health Hazard; Fire Hazard

**SARA Section 313 Notification** - This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372. This information must be included in all MSDSs that are copied and distributed for this material: Toluene. See section 2 for % amount in the product.

**Ingredient(s) - U.S. Regulatory Information**

TOLUENE

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical; SARA - Acute Health Hazard; SARA - Chronic Health Hazard; SARA - Fire Hazard

**Ingredient(s) - State Regulations**

ACETONE

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

BUTANE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania -

# MATERIAL SAFETY DATA SHEET

## FAST DRY RUST CURB GLOSS WHITE

### 15. Regulatory Information - Continued

#### Ingredient(s) - State Regulations - Continued

Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### PROPANE


New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### TOLUENE

New Jersey - Workplace Hazard; New Jersey - Environmental Hazard; New Jersey - Special Hazard; Pennsylvania - Workplace Hazard; Pennsylvania - Environmental Hazard; California - Proposition 65; Massachusetts - Hazardous Substance; New York City - Hazardous Substance

#### V.M. & P. NAPHTHA

New Jersey - Workplace Hazard; Pennsylvania - Workplace Hazard; New York City - Hazardous Substance

<p><b>NFPA</b></p> 	<p><b>HMIS</b></p> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">HEALTH</td> <td style="text-align: center; padding: 2px;">*2</td> </tr> <tr> <td style="padding: 2px;">FLAMMABILITY</td> <td style="text-align: center; padding: 2px;">4</td> </tr> <tr> <td style="padding: 2px;">REACTIVITY</td> <td style="text-align: center; padding: 2px;">1</td> </tr> <tr> <td style="padding: 2px;">PERSONAL PROTECTION</td> <td style="text-align: center; padding: 2px;">B</td> </tr> </table>	HEALTH	*2	FLAMMABILITY	4	REACTIVITY	1	PERSONAL PROTECTION	B
HEALTH	*2								
FLAMMABILITY	4								
REACTIVITY	1								
PERSONAL PROTECTION	B								

### 16. Other Information

#### Revision/Preparer Information

MSDS Preparer: Laura E. Radevski

MSDS Preparer Phone Number: 708-865-1000

This MSDS Supersedes A Previous MSDS Dated: 06/27/2001

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

Chase Products Co.

Printed Using MSDS Generator™ 2000