

MINWAX -- M060092 FAST DRYING POLYURETHANE CLEAR GLOSS - PAINT
MATERIAL SAFETY DATA SHEET
NSN: 801000F051615
Manufacturer's CAGE: 0K1A4
Part No. Indicator: A
Part Number/Trade Name: M060092 FAST DRYING POLYURETHANE CLEAR GLOSS

General Information

Item Name: PAINT
Company's Name: MINWAX CO
Company's Street: 15 MERCEDES DRIVE
Company's P. O. Box: 438
Company's City: MONTVALE
Company's State: NJ
Company's Country: US
Company's Zip Code: 07645-5000
Company's Emerg Ph #: 201-391-0253/201-573-5700
Company's Info Ph #: 201-573-5700/201-391-0253
Record No. For Safety Entry: 001
Tot Safety Entries This Stk#: 001
Status: SE
Date MSDS Prepared: 05JAN95
Safety Data Review Date: 23OCT96
Preparer's Company: MINWAX CO
Preparer's St Or P. O. Box: 15 MERCEDES DRIVE
Preparer's City: MONTVALE
Preparer's State: NJ
Preparer's Zip Code: 07645-5000
MSDS Serial Number: CCFKQ

Ingredients/Identity Information

Proprietary: NO
Ingredient: MEDIUM ALIPHATIC NAPHTHA (AROMATIC 100), PARAFFIN-NAPTHANES
MINERAL SPIRITS * 96-3 *
Ingredient Sequence Number: 01
Percent: 20-26
NIOSH (RTECS) Number: 1003692SN
CAS Number: 64742-88-7
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 100 PPM

Proprietary: NO
Ingredient: STODDARD SOLVENT (PETROLEUM DISTILLATE), MINERAL SPIRITS *
96-3 *
Ingredient Sequence Number: 02
Percent: 29-40
NIOSH (RTECS) Number: WJ8925000
CAS Number: 8052-41-3
OSHA PEL: 500 PPM
ACGIH TLV: 100 PPM
Other Recommended Limit: 525 MG/CUM

Proprietary: NO
Ingredient: VOLATILE ORGANIC CONTENT: 485 GM/L
Ingredient Sequence Number: 03
NIOSH (RTECS) Number: 9999999VO

Physical/Chemical Characteristics

Appearance And Odor: CLEAR AMBER LIQUID W/HYDROCARBON ODOR
Specific Gravity: 0.872
Solubility In Water: INSOLUBLE

=====
Fire and Explosion Hazard Data
=====

Flash Point: >101F
Flash Point Method: SCC
Extinguishing Media: WATER SPRAY, FOAM, DRY CHEMICAL/CO2
Special Fire Fighting Proc: WEAR SELF CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING. USE WATER SPRAY TO COOL FIRE-EXPOSED CONTAINERS. DON'T USE DIRECT STREAM OF WATER.
Unusual Fire And Expl Hazrds: PRODUCT MAY FLOAT & CAN BE REIGNITED ON SURFACE OF WATER. CONTAINERS EXPOSED TO INTENSE HEAT FROM FIRE MAY CAUSE VAPOR PRESSURE BUILDUP & RUPTURE CONTAINERS.

=====
Reactivity Data
=====

Stability: YES
Cond To Avoid (Stability): INTENSE HEAT, SPARKS, FIRE/FLAME & OTHER IGNITION SOURCES
Materials To Avoid: STRONG OXIDIZING AGENTS
Hazardous Decomp Products: HYDROCARBON FUMES, SMOKE, CO.
Hazardous Poly Occur: NO

=====
Health Hazard Data
=====

Route Of Entry - Inhalation: YES
Route Of Entry - Skin: NO
Route Of Entry - Ingestion: YES
Health Haz Acute And Chronic: SKIN: IRRITATION. INGESTION: HARMFUL/FATAL.
Carcinogenicity - NTP: NO
Carcinogenicity - IARC: NO
Carcinogenicity - OSHA: NO
Explanation Carcinogenicity: NONE
Signs/Symptoms Of Overexp: IRRITATION
Med Cond Aggravated By Exp: PRE-EXISTING LUNG DISORDERS.
DON'T INDUCE VOMITING. OBTAIN MEDICAL ATTENTION IN ALL CASES.

=====
Precautions for Safe Handling and Use
=====

Steps If Matl Released/Spill: SMALL: ABSORB W/SAND/OTHER SUITABLE ABSORBENT MATERIAL & PLACE IN A CONTAINER FOR DISPOSAL. LARGE: AREA MAY BE SLIPPERY, DIKE W/ABSORBENT MATERIAL. TRANSFER LIQUIDS & CONTAMINATED DIKING MATERIAL TO SEPARATE, SUITABLE CONTAINERS FOR RECOVERY/DISPOSAL
Waste Disposal Method: DISPOSE OF IN ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.
Precautions-Handling/Storing: DON'T USE/STORE NEAR HEAT, SPARKS, FLAME/ OTHER SOURCES OF IGNITION. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.
Other Precautions: AVOID CONTACT W/SKIN/EYES. AVOID INHALATION & USE ONLY W/ADEQUATE VENTILATION. DON'T TAKE INTERNALLY.

=====
Control Measures
=====

Respiratory Protection: IF ADEQUATE VENTILATION CAN'T BE MAINTAINED, WEAR RESPIRATORY PROTECTION (NIOSH/MSHA TC23C)/LEAVE THE AREA.
Ventilation: ADEQUATE VENTILATION
Protective Gloves: RUBBER
Eye Protection: SAFETY GLASSES

=====
Transportation Data
==========
Disposal Data
==========
Label Data
=====