MATERIAL SAFETY DATA SHEET

ohnson wax PROFESSIONAL

FASTRIP Floor Stripper

HMIS NFPA		NFPA	Personal protective equipment		
Health		3	3		
Fire Hazard		0	0		
Reactivity		0	0		
Version Numbe	er: 4			Preparation date: 2007-06-22	

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

FASTRIP Floor Stripper

MSDS #:

MS0200002

Product Code:

4122398, 4122401, 4362447

Recommended use:

Industrial/Institutional. Floor stripper. This product is intended to be diluted prior to use.

Manufacturer, importer, supplier:

US Headquarters JohnsonDiversey, Inc. Canadian Headquarters JohnsonDiversey - Canada, Inc. 2401 Bristol Circle

8310 16th St. Sturtevant, Wisconsin 53177-0902

Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131

Phone: 1-888-352-2249

MSDS Internet Address: www.johnsondiversey.com

Emergency telephone number:

1-800-851-7145 (Prosar); 1-651-917-6133 (Int'l Prosar); 01-800-710-3400 (México)

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER, CORROSIVE. CAUSES SKIN AND EYE BURNS. HARMFUL OR FATAL IF SWALLOWED.

Principle routes of exposure:

Eve contact. Skin contact. Inhalation.

Eye contact:

Corrosive. Causes permanent eye damage, including blindness.

Skin contact: Inhalation:

Corrosive. Causes permanent damage.

Ingestion:

May cause irritation and corrosive effects to nose, throat and respiratory tract.

Corrosive. Causes burns to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS COMPONENTS

Ingredient(s)	CAS#	Weight %	LD50 Oral - Rat	LD50 Dermal - Rabbit	LC50 Inhalation - Rat
Potassium hydroxide	1310-58-3	5 - 10%	=214 mg/kg	Not available	Not available
Monoethanolamine	141-43-5	10 - 20%	=1720 mg/kg	=1 mL/kg	Not available
Benzyl alcohol	100-51-6	20 - 30%	=1230 mg/kg	=2000 mg/kg	=8.8 mg/L (4 h)

4. FIRST AID MEASURES

Eye contact:

Immediately flush eyes with running water for at least 15-20 minutes, keeping eyelids open. Get medical

attention immediately.

Skin contact:

Flush immediately with plenty of water for at least 15-20 minutes. Get medical attention immediately.

If breathing is affected, remove to fresh air. Get medical attention immediately.

Inhalation: Ingestion:

If swallowed, give a cupful of water or milk. THEN IMMEDIATELY CONTACT A PHYSICIAN OR POISON

CENTER. DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by

mouth to an unconscious person.

Aggravated Medical Conditions:

Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be

more susceptible to irritating effects.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media:

The product is not flammable. Extinguish fire using agent suitable for surrounding fire.

Specific hazards:

Unusual hazards:

Corrosive material (See sections 8 and 10).

Specific methods:

No special methods required

5. FIRE-FIGHTING MEASURES

Special protective equipment for firefighters: As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Extinguishing media which must not be used for safety reasons: None.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: **Environmental precautions** and clean-up methods:

Put on appropriate personal protective equipment (see Section 8.).

Use appropriate containment to avoid environmental contamination. Soak up with inert absorbent material.

Shovel into suitable container for disposal.

7. HANDLING AND STORAGE

Handling:

Avoid contact with skin, eyes and clothing. Do not taste or swallow. Avoid breathing vapors or mists. Use only with adequate ventilation. Remove and wash contaminated clothing and footwear before re-use. Wash thoroughly after handling. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.

Protect from freezing, Keep tightly closed in a dry, cool and well-ventilated place. KEEP OUT OF REACH OF CHILDREN.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures to reduce exposure:

Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.

Personal Protective Equipment

Eye protection:

Chemical-splash goggles.

Hand protection:

Chemical-resistant gloves

Skin and body protection:

Protective footwear. If major exposure is possible, wear suitable protective clothing and footwear.

Respiratory protection:

In case of insufficient ventilation wear suitable respiratory equipment. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace

conditions warrant a respirator's use.

Hygiene measures:

Keep away from food, drink and animal feeding stuffs. Handle in accordance with good industrial hygiene

and safety practice.

Ingredient(s)	CAS#	ACGIH	OSHA	Mexico
Potassium hydroxide	1310-58-3	2 mg/m³ (Ceiling)		
Monoethanolamine	141-43-5	6 ppm (STEL) 3 ppm (TWA)	3 ppm (TWA) 6 mg/m³ (TWA)	6 ppm (STEL) 15 mg/m³ (STEL) 3 ppm (TWA) 8 mg/m³ (TWA)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:

Liquid

14 nΗ:

Appearance:

Aqueous solution

Color:

Yellow Slight Solvent

Odor: Specific gravity:

1.080

Density:

9.01 lbs/gal

VOC:

17.45% *

Flash point:

>200°F >99.3°C

Solubility:

Soluble

Viscosity:

No information available

Bulk density:

Dilution pH:

Vapor density:

Evaporation Rate

Boiling point/range:

Melting point/range:

Decomposition temperature:

Autoignition temperature:

Solubility in other solvents:

No information available Partition coefficient (n-octanol/water): No information available No information available

No information available

No information available

No information available

No information available

Not determined

Not determined

Not determined

Elemental Phosphorus:

0 %P

* - Title 17, California Code of Regulations, Division 3, Chapter 1, Subchapter 8.5, Article 2, Consumer Products, Sections 94508

10. STABILITY AND REACTIVIT

Stability:

The product is stable

Polymerization: Hazardous decomposition products: Hazardous polymerization does not occur

Materials to avoid:

None reasonably foreseeable.

Strong oxidising agents. Strong exothermic reaction with acids .

11. TOXICOLOGICAL INFORMATION

Acute toxicity:

Corrosive. Oral LD50 estimated to be >1000 and <5000 mg/kg. Dermal LD50 estimated to be > 2000 mg/kg

11. TOXICOLOGICAL INFORMATION

Component Information:

See Section 3

Chronic toxicity:

None known

Specific effects

Carcinogenic effects: Mutagenic effects:

None known None known

Reproductive toxicity: Target organ effects:

None known None known

12. ECOLOGICAL INFORMATION

Environmental Information:

When used for its intended purpose this product should not cause adverse effects in the environment .

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products:

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local applicable regulations.

14. TRANSPORT INFORMATION

DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information

15. REGULATORY INFORMATION

International Inventories

All components of this product are listed on the following inventories: U.S.A. (TSCA), Canada (DSL/NDSL).

U.S. Regulations

California Proposition 65: This product is not subject to the reporting requirements under California's Proposition 65

STATE RIGHT TO KNOW

Ingredient(s)	CAS#	MARTK:	NJRTK:	PARTK:	RIRTK:
Potassium hydroxide	1310-58-3	X	Х	X	X
Monoethanolamine	141-43-5	X	X	X	Χ -
Water	7732-18-5	-	-	-	-
Benzyl alcohol	100-51-6	X	-	X	-
Hexyloxyethanol	112-25-4	-	-	X	-
Potassium tallate	61790-44-1	-	-	-	-

CERCLA/ SARA

Ingredient(s)	CAS#	Weight %	CERCLA/SARA RQ (lbs)	Section 302 TPQ (lbs)	Section 313
Potassium hydroxide	1310-58-3	5 - 10%	1000		
Hexyloxyethanol	112-25-4	10 - 20%			X

Ingredient(s)	CAA HAP	CAA ODS	CWA Priority Pollutants
Hexyloxyethanol	X		

SARA 311/312 Hazard Categories

Immediate:

Delayed:

Ν

Fire:

Ν

Reactivity: Sudden Release of Pressure: Ν Ν

WHMIS hazard class: E Corrosive material .



Ingredient(s)	CAS#	NPRI
Monoethanolamine	141-43-5	X
Benzyl alcohol	100-51-6	X

16. OTHER INFORMATION

Reason for revision: Prepared by: Additional advice: Not applicable NAPRAC None

Notice to Reader: This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.