

BASE PAINT FOR BASES

MAR 30 2010

MATERIAL SAFETY DATA SHEET

FLEXIBOND COATING-WHITE

Page: 1

PRODUCT NAME: FLEXIBOND COATING-WHITE
PRODUCT CODE: 88-1578-I-01

HMS CODES: H F R P
2 0 1 X

=====
SECTION I - MANUFACTURER IDENTIFICATION
=====

MANUFACTURER'S NAME: CONTINENTAL PRODUCTS COMPANY
ADDRESS : 1150 East 222 Street
Euclid, OH 44117

EMERGENCY PHONE : (800)255-3924 DATE PRINTED : 03/15/01
INFORMATION PHONE : (216)531-0710 NAME OF PREPARER : John Stevens

=====
SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION
=====

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
Water (nonhazardous) ACGIH TLV: Not Established OSHA PEL: Not Established	7732-18-5		42
+ TITANIUM DIOXIDE ACGIH TLV: 10 mg/M3 (TWA) OSHA PEL: 10 mg/M3 (Total Dust)	13463-67-7		16
+ SILICA ACGIH TLV: 0.1 mg/M3 (Respirable) (TWA) OSHA PEL: 0.1 mg/M3 (Respirable)	14808-60-7		3.21037
+ N-METHYL-2-PYRROLIDONE ACGIH TLV: Not Established OSHA PEL: Not Established	872-50-4		3.0
+ ALUMINA ACGIH TLV: 10 mg/M3 (TWA) OSHA PEL: 15 mg/M3 (Total Dust); 5 mg/M3 (Respirable Fraction)	1344-28-1		1.5
+ 2-PROPANOL ACGIH TLV: 400 ppm; 983 mg/M3 (TWA); 500 ppm; 1230 mg/M3 (STEL) OSHA PEL: 400 ppm; 980 mg/M3	67-63-0		1.3
2,2,4-TRIMETHYL-1,3-PENTANEDIOL MONOISOBUTYR ACGIH TLV: Not Established OSHA PEL: Not Established	25265-77-4		1
Oxyalkylated amino alcohol - ZENECA proprietary ingredient ACGIH TLV: Not Established OSHA PEL: Not Established	Solsperse200		1
+ FORMALDEHYDE ACGIH TLV: 0.3 ppm (Ceiling) OSHA PEL: .75ppm TWA; 0.5ppm Action Level; STEL 2 ppm see 29 CFR 1910.1048 RQ 100 lbs	50-00-0		0.02205

Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

Indicates toxic chemical(s) subject to the reporting requirements of section 311 and 312 of Title III and of 40 CFR 372.

Indicates a Chronic hazard. See warning (if applicable) in Section IX.

THIS MATERIAL CONTAINS INGREDIENTS COVERED BY THE CALIFORNIA "SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986" (proposition 5). SEE SECTION IX.

=====
SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS
=====

BOILING RANGE: 180 F - 482 F
VAPOR DENSITY: HEAVIER THAN AIR

SPECIFIC GRAVITY (H2O=1): 1.22
EVAPORATION RATE: SLOWER THAN ETHER

M A T E R I A L S A F E T Y D A T A S H E E T

FLEXIBOND COATING-WHITE

Page: 2

V.O.C. (less water): 1.31 lb/gl
SOLUBILITY IN WATER: READILY SOLUBLE
APPEARANCE : WHITE LIQUID

MATERIAL V.O.C. : 0.63 lb/gl
ODOR: CHARACTERISTIC PAINT ODOR

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASHPOINT : ABOVE 200F SETAFLASH METHOD USED: SETAFLASH
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 7.0 UPPER: 73.0

EXTINGUISHING MEDIA: Carbon Dioxide, dry chemical or foam. If water, fog nozzles preferred.

SPECIAL FIREFIGHTING PROCEDURES

Water may be used to cool closed containers to prevent pressure build-up when exposed to extreme heat. Firefighting personnel should wear self-contained breathing apparatus.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Isolate from heat, electrical equipment, sparks, and open flame. Closed containers may explode (due to the build-up of steam pressure) when exposed to extreme heat.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable
CONDITIONS TO AVOID

Heat, sparks, open flame and fire. Material is subject to freezing. Do not store above 120 Degrees Fahrenheit.

INCOMPATIBILITY (MATERIALS TO AVOID)
Strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

BY FIRE: Normal products of incomplete combustion. May produce fumes when heated to decomposition, as in welding. Fumes may contain carbon monoxide/dioxide or oxides of nitrogen.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

THRESHOLD LIMIT VALUE: SEE SECTION II

PRIMARY ROUTE(S) OF ENTRY:
Inhalation and skin contact.

EFFECTS OF OVEREXPOSURE:
May cause headache, nausea, eye or skin irritation. (Material is slightly alkaline.)

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: No

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Repeated exposure to emitted vapors may cause irritation to the upper respiratory tract. Preexisting skin sensitization may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. Administer artificial respiration or oxygen if breathing is difficult. Call for prompt medical attention. EYES: Flush immediately with large amounts of water for at least 15 minutes. Get medical attention. SKIN: Wash affected area with soap and water. Remove and launder contaminated clothing. Consult a physician if irritation persists. INGESTION: Do not induce vomiting. Keep at rest. Call a physician immediately.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Dike spill area. Ventilate area if necessary. Recover free liquid by addition of inert absorbent to spill area. Sweep up and place material in a suitable disposal container. Wash down spill area with copious quantities of water.

WASTE DISPOSAL METHOD

Disposal must be made in accordance with Local, State, and Federal regulations. Incineration or landfilling must be in an approved facility. Do not incinerate closed containers.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store out of the sun and away from heat, sparks, and open flame. Keep containers closed and upright to prevent leakage. Do not store below 40 Degrees Fahrenheit or above 120 Degrees Fahrenheit for extended periods. Do not reuse product container for any purpose.

OTHER PRECAUTIONS

Do not get in eyes. Avoid skin contact. Do not take internally. Prevent prolonged or repeated breathing of vapor or spray mist. Keep out of reach of children.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Observe the OSHA Respiratory Protection Standard (29 CFR 1910.134) for respirator selection and use. Selection of the most appropriate respirator will depend on the specific work environment and should be made only by a person familiar with the working conditions and with the benefits and limitations of respiratory protection products.

VENTILATION

Ventilation should dilute to below LEL and TLV to be considered adequate. All applications areas should be ventilated in accordance with the applicable regulations found in 29 CFR, Part 1910.

Respiratory protection should be provided in accordance with 29 CFR, Part 1910.134.

PROTECTIVE GLOVES

Recommended if skin contact is likely.

EYE PROTECTION

Chemical goggles or safety eyewear with splash shields is recommended.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Suitable barrier cremes, impermeous clothing and boots are recommended to reduce repeated contact with material and limit contamination.

WORK/HYGIENIC PRACTICES

Wash hands with soap and water before eating or using the washroom. Smoke in smoking areas only. Remove and wash contaminated clothing before reuse.

===== SECTION IX - REGULATORY INFORMATION =====

Silica (Crystalline) - The IARC has concluded that there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica in the form of quartz or cristobalite from occupational sources. Crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1). (IARC Monographs VOL 68(1997) SILICA)
IUPAC lists crystalline silica as reasonably anticipated to be a human carcinogen.

THIS PRODUCT CONTAINS FORMALDEHYDE, WHICH IS A POTENTIAL CANCER HAZARD TO HUMANS. FORMALDEHYDE IS KNOWN TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

FORMALDEHYDE MAY CAUSE IRRITATION AND SENSITIZATION OF THE SKIN AND RESPIRATORY SYSTEM, MAY CAUSE EYE AND THROAT IRRITATION, AND IS ACUTELY TOXIC. FORMALDEHYDE IS LISTED IN IARC GROUP 2A AS PROBABLY CARCINOGENIC TO HUMANS.

M A T E R I A L S A F E T Y D A T A S H E E T
FLEXIBOND COATING-WHITE

Page: 4

NTP LISTS FORMALDEHYDE AS REASONABLY ANTICIPATED TO BE A HUMAN CARCINOGEN.

Risk of cancer depends on duration and level of exposure. See OSHA Standard 1910.1048

All components of this product are listed in the TSCA inventory.

THE INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER NO GUARANTY OR WARRENTY OF ANY KIND, EXPRESSED OR IMPLIED, IS MADE WITH RESPECT TO THE INFORMATION ABOVE.