S.C. Johnson Wax Racine, Wisconsin 53403-5011 Phone: (414) 631-2777 Emergency Phone: (800) 228-5635

4=Very High 3=Hiqh 2=Moderate 1=Slight 0=Insignificant 0 Reactivity

HMIS NFPA 2 Health 0 Flammability

HAZARD RATING

MATERIAL SAFETY DATA SHEET

| SECTION 1-1 RODUCT IDENTIFICATION | | | | | |
|-----------------------------------|--------------|-------------|--------------|------------|--|
| PRODUCT NAME: | | | PRO | DUCT CODE | |
| FORWARD DC | | | | 14540-26 | |
| CHEMICAL OR COMMON NAME | DATE ISSUED: | SUPERSEDES: | PREPARED BY: | | |
| NA | 04/10/91 | 05/01/90 | Terry A. | Meyers | |
| | | | Chemical | Info. Adm. | |

SECTION II-INGREDIENT INFORMATION INGREDIENTS WEIGHT % EXPOSURE LIMIT N-Alkyl Dimethyl Benzyl Ammonium 1.6 NOT ESTABLISHED Chloride (CAS $\frac{1}{4}$ 68391 $\frac{1}{-}$ 01-5) Sodium Metasilicate (CAS# 6834-92-0) |2-5|NOT ESTABLISHED Sodium Tripolyphosphate (CAS# 2 - 4NOT ESTABLISHED 7758-29-4) Nonylphenol Polyethylene Glycol Ether 3-6 NOT ESTABLISHED (CAS# 26027-38-3) Water (CAS# 7732-18-5) 80-90 NA See Regulatory Information (Section XII) for explanation of bracketed information.

SECTION III-PHYSICAL DATA APPEARANCE/ODOR: Greenish liquid with SPECIFIC GRAVITY (H20=1): mild odor VAPOR PRESSURE (mm Hg): NA PERCENT VOLATILE BY VOLUME (%): NA SOLUBILITY IN WATER: Complete VAPOR DENSITY (AIR=1): NA FREEZING POINT (°F): ND BOILING POINT (°F): 200 12.5 - 13.5nH: EVAPORATION RATE (BUTYL ACETATE=1): NA

SECTION IV-FIRE AND EXPLOSION INFORMATION FLASH POINT (°F) (METHOD USED): FLAMMABLE LIMITS: ÑĀ EXTINGUISHING MEDIA: Foam. CO2. Dry Chemical. Water Fog. SPECIAL FIREFIGHTING PROCEDURES: Cool and use caution when approaching or handling fire-exposed containers. UNUSUAL FIRE AND EXPLOSION HAZARDS: Corrosive Material (See Sections VI, VIII). Container may burst in heat of fire.

MATERIAL SAFETY DATA SHEET

Page 2

S.C. Johnson Wax 1525 Howe Street Racine,Wisconsin

FORWARD DC

Product Number: 14540

Serial Number: 2

SECTION V-HEALTH HAZARD DATA

PRIMARY ROUTE OF ENTRY: Skin contact.

53403

SIGNS AND SYMPTOMS: Direct contact of product with eyes can cause irritation. Prolonged or repeated contact of undiluted product with skin may cause irritation. If taken internally, product may cause corrosive damage to mouth, throat or stomach.

FIRST AID PROCEDURES: Flush eyes with water for 15 minutes. If irritation persists, seek medical aid. Wash skin with plenty of water. If irritation persists, seek medical aid. If product is swallowed, drink large amounts of water or milk and seek medical aid.

MEDICAL CONDITIONS GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE:

SECTION VI-REACTIVITY DATA

STABILITY: Stable

STABILITY-CONDITIONS TO AVOID:

None known

INCOMPATIBILITY:

Strong acids (e.g., muriatic acid).

HAZARDOUS DECOMPOSITION PRODUCTS:

HAZARDOUS POLYMERIZATION-CONDITIONS TO AVOID:

When exposed to fire, produces normal products

of combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

None known

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water. Wear/use appropriate protective equipment.

WASTE DISPOSAL INFORMATION: For undiluted product: Disposal is regulated under the Resource Conservation and Recovery Act as a corrosive waste (40 CFR 261.22). Disposal of regulated quantities should be by neutralization at a permitted facility in accordance with all Federal/State regulations and local ordinances regarding disposal of corrosive wastes. Waste from normal product use may be sewered to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: No special requirements under normal use conditions.

VENTILATION: NSR

PROTECTIVE GLOVES: For undiluted product: Any impervious material.

EYE PROTECTION: For undiluted product: Chemical workers splash-proof goggles

OTHER PROTECTIVE MEASURES: Use good personal hygiene practices. Launder contaminated clothing/equipment before reuse.

MATERIAL SAFETY DATA SHEET

Page 3

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin FORWARD DC

Product Number: 14540

Serial Number: 2

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONARY LABELING: CAUTION: Avoid contact of undiluted product with skin or eyes. In case of contact immediately flush eye or skin with plenty of water. Get medical attention if irritation persists.

OTHER HANDLING AND STORAGE CONDITIONS: Keep out of reach of children. Store in a cool, dry place with adequate ventilation. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. Keep from freezing. Wash thoroughly after handling.

SECTION X-ADDITIONAL INFORMATION

ADDITIONAL INFORMATION:

EPA REG. 4822-21

53403

SECTION XI-TRANSPORTATION INFORMATION

DOT CLASS: Non-Hazardous

DOT #: NA

SHIPPING NAME:

Cleaning, scouring or washing compounds. NOI Liquid.

DOT NOTES: NA

NA-Not Applicable, NE-Not Established, NSR-No Special Requirement, ND-Not Determined for this product The information herein is given in good faith. No warranty, expressed or implied is made. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and local laws and regulations. The information contained in this form is confidential and is submitted solely for your organization's internal use.