

## Office Equipment Division

9-1. Hiraide Kogyo Danchi, Utsunomiya City, Tochigi Pref., 321-JAPAN  
 Phone No. Japan 0286-63-3221. Fax. No. Japan 0286-62-8393

FP-1530/1510/1307/1540

Material Safety Data Sheet

(This Form is Similar to U.S. Labor Dept. Form Approved OMB No. 1218-0072)

## SECTION I

Product Name EQ EQ-H500	Date : May 30, 1991	Chemical Name & Synonyms Aluminum (Al), Selenium (Se) Tellurium (Te)
Product Class Photoconductive Drum	Emergency Phone No.	

## SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components		( L : listed, NL : not listed, )					
INGREDIENTS (CHEMICAL NAME)	CAS #	wt%	OSHA	LISTED AS A HAZARDOUS OSHA PEL	ACGIH	ACGIH TLV	
Aluminum (Al)	7429-90-5	92.5	NL		L	10mg/m <sup>3</sup>	
Se:Te Alloy	7782-49-2	6.75	L	0.2mg./M <sup>3</sup>	L	0.2mg/m <sup>3</sup>	
Selenium (Se)	13494-80-9	0.75	L	0.1mg./M <sup>3</sup>	L	0.1mg/m <sup>3</sup>	
Tellurium (Te)							

Se:Te alloy is hard vitreous substance. When coated it strongly adheres to an aluminum substrate, so there is no hazard as long as the drum is used as intended.

Section 313 Supplier Notification : This product contains the following toxic chemicals subject to the reporting requirement of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

Photoconductor is an "article" as defined in §372.3. So, notification is not required.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point	1148~1328 (°F)	Specific Gravity (H <sub>2</sub> O = 1)	4.3~6.3
Vapor Pressure (mm Hg.)	N. A.	Melting Point	419~473 (°F)
Vapor Density (AIR = 1)	N. A.	Evaporation Rate (Butyl Acetate = 1)	N. A.
Solubility in Water	negligible		
Appearance and Odor	brown, no odor		

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	N. A.	Flammable Limits	N. A.	LEL	UEL
Extinguishing Media	CO <sub>2</sub> , Dry chemicals				
Special Fire Fighting Procedures	Self contained breathing apparatus and full protection against dust and fumes. (In case that a large quantity of drums produces fumes or vapors at a high temperature)				
Unusual Fire and Explosion Hazards	Nothing				

SECTION V - REACTIVITY DATA

Stability	Unstable		Condition to Avoid	N. A.
	Stable	X		
Incompatibility (Materials to Avoid)		Oxidizing agents, reductive acids		
Hazardous Decomposition or Byproducts		SeO <sub>2</sub> , H <sub>2</sub> Se		
Hazardous Polymerization	May occur		Condition to Avoid	N. A.
	Will not occur	X		

SECTION VI - HEALTH HAZARD DATA

Route (s) of Entry:	Inhalation?	No	Skin?	No	Ingestion?	No
Health Hazard (Acute and Chronic)		Health hazard of Se:Te alloy is unknown.				
Carcinogenicity:	NTP?		IARC Monographs?		OSHA Regulated?	
	Selenium	No	Tellurium	No		No
Signs and Symptoms of Exposure		No effects are known.				
Medical Conditions Generally Aggravated by Exposure		Unknown				
Emergency and First Aid Procedures		N. A.				

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled	Usual cleaning methods
Waste Disposal Method	Return used drums to manufacturer or arrange for long term storage.
Precautions to Be Taken in Handling and Storing	N. A.
Other Precautions	N. A.

SECTION VIII - CONTROL MEASURES

Respiratory Protection (Specify Type)		N. A.	
Ventilation	Local Exhaust	N. A.	Special
	Mechanical (General)	N. A.	Other
Protective Gloves	N. A.	Eye Protection	N. A.
Other Protective Equipment		N. A.	
Work/Hygienic Practices		N. A.	