

MATERIAL SAFETY DATA SHEET

Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

Date of Prep: 3/18/94

SECTION 1

SUNNYSIDE CORPORATION
225 CARPENTER AVENUE
WHEELING, ILLINOIS 60090
EMERGENCY TELEPHONE

(708) 541-5700
(800) 424-9300

SUNNYSIDE CORPORATION
CHEM TREC

FOR INFORMATION: (708) 541-5700

Product Class: Mixed Solvents
Trade Name: **GLOSS REMOVER & PRE-PAINT CLEANER**

Manufacturer's Code:
NPCA HMIS:

722
Health: 1
Flammability: 2
Reactivity: 0

Product Appearance and Odor: Clear, colorless liquid; mild mixed-solvent odor.

SECTION 2 -- HAZARDOUS INGREDIENTS

OCCUPATIONAL EXPOSURE LIMITS

INGREDIENT	CAS #	PERCENT	ACGIH TLV (TWA)	ACGIH TLV (STEL)	OSHA PEL (TWA)	OSHA PEL (STEL)	VAPOR PRESSURE
Hydro-Treated Heavy Naphtha Petroleum	64742-48-9		Not Est.	Not Est.	Not Est.	Not Est.	Approx. 1mm Hg @ 25°C.
Dipropylene Glycol Methyl Ether	34590-94-8		100 PPM	150 PPM	100 PPM	150 PPM	0.4mm Hg @ 77° F.
N-Methyl-2-Pyrrolidone	872-50-4		Not Est.	Not Est.	Not Est.	Not Est.	0.3 mm Hg @ 68° F.

SECTION 3 -- EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention immediately.

EYE CONTACT: Immediately flush with clean water for 20-30 minutes. Get medical attention.

SKIN CONTACT: Remove contaminated clothing and shoes. Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes. Seek medical attention if irritation or ill effects develop.

INGESTION: Do not induce vomiting. Contact physician or emergency medical facility immediately.

SECTION 4 -- PHYSICAL DATA

The following data represent approximate or typical values. They do not constitute product specifications.

Boiling Range:	354° (F) - I.B.P.	Vapor Density:	Heavier than air
Evaporation Rate:	Slower than ether	% Volatile By Volume:	100%
Weight Per Gallon:	6.40 lbs.		
Solubility in Water:	Approx. 6% (By Weight)		

SECTION 5 -- FIRE AND EXPLOSION DATA

Flammability Classification: Combustible Liquid - Class II.

Flash Point: 120° F. (Tag. Closed Cup) - Minimum

Lower Explosive Limit: Not established for mixture

Extinguishing Media: Water fog, dry chemical, foam, carbon dioxide. Do not use direct water stream. It will spread fire.

Unusual Fire and Explosion Hazards: Do not store or mix with strong oxidants.

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Use water spray to keep fire - exposed containers cool.

SECTION 6 -- HEALTH HAZARD DATA**THRESHOLD LIMIT VALUE:
EFFECTS OF OVEREXPOSURE**
Acute:

Not established for mixture - see Section 2.

Eye Contact: May cause irritation, discomfort, redness and swelling of the eye.

Skin Contact: Liquid is slightly irritating to the skin. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis.

Inhalation: Vapors may cause irritation to nose, throat and respiratory tract. High vapor concentrations may result in central nervous system depression.

Ingestion: Ingestion may result in vomiting. Aspiration (breathing) of vomitus into the lungs must be avoided, as even small quantities may result in aspiration pneumonia.

Chronic:

Repeated skin contact may aggravate an existing dermatitis (skin condition).

Carcinogenicity:

The components of this product are not listed as carcinogens by NTP, IARC or OSHA.

SECTION 7 -- REACTIVITY DATA

Stability: Stable under normal conditions.

Conditions to Avoid: Sparks and open flame.

Incompatibility (Materials to Avoid): Strong oxidizing agents like liquid chlorine or concentrated oxygen.

Hazardous Decomposition Products: Thermal decomposition may yield carbon monoxide.

Hazardous Polymerization: Will not occur.

SECTION 8 -- SPILL OR LEAK PROCEDURES

Steps to be taken in case material is spilled or released: Remove ignition sources, evacuate area, avoid breathing vapor or contact with liquid. Recover free liquid or stop leak if possible. Dike large spills and use absorbent material for small spills. Keep spilled material out of sewers, ditches and bodies of water. Avoid contaminating ground and surface waters.

Waste disposal method: Send to a licensed reclaimer or incinerator. Dispose of in accordance with local, state and federal regulations.

SECTION 9 -- SAFE HANDLING AND USE INFORMATION

Respiratory Protection: Not required under normal use. Use a NIOSH/MSHA approved respirator where mist, spray or vapor is generated and exceeds TLV. See Section 2.

Ventilation: Do not use in closed or confined space. Open doors and/or windows. Use ventilation to maintain exposure levels below occupational exposure limits (see section 2).

Protective Gloves: Wear solvent-resistant gloves such as neoprene or rubber.

Eye Protection: Chemical goggles and/or face shield should be worn where splashing is possible. Contact lenses should not be worn.

Other Protective Equipment: Impervious clothing or boots, if needed. Wash contaminated clothing before reuse.

SECTION 10 -- SPECIAL PRECAUTIONSDept. of Labor Storage Category:
Hygienic Practices:Combustible Liquid Class II
Avoid contact with skin and avoid breathing vapors. Do not eat, drink or smoke in work areas. Wash hands prior to eating, drinking or using rest room.

Additional Precautions:

Ground containers when transferring liquid to prevent static accumulation and discharge.

Empty Container Warning:

"Empty" containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks or other sources of ignition. They may explode and cause injury or death. Do not attempt to clean since residue is difficult to remove. "Empty" drums should be completely drained, properly bunged and promptly returned to supplier or disposed of in an environmentally safe manner and in accordance with governmental regulations.

SECTION 11 -- ADDITIONAL INFORMATION

This product contains the following toxic chemical(s) which are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>TOXIC CHEMICAL</u>	<u>CAS #</u>	<u>APPROXIMATE % BY WEIGHT</u>
-----------------------	--------------	------------------------------------

NONE

SARA Title III Hazard Categories: Immediate (Acute) Health, Delayed (Chronic) Health.

TRANSPORTATION

U.S. D.O.T. Proper Shipping Name:	Paint Related Material
U.S. D.O.T. Hazard Class & Packing Group:	Combustible Liquid, III
U.S. D.O.T. Identification Number:	UN 1263

Refer to 49 CFR for possible exceptions and exemptions.