

Company Address:
8125 Cobb Center Drive
Kennesaw, GA 30144

Product Information: 800-TECH-401
Customer Service: 800-645-5244

Emergency: (Chemtec) 800-424-9300
Revision Date: July 14, 1994
Prepared by: Michael S. Watkins

Product Identification

GOLD GUARD™ 2000

Product Code: ES601

Product Ingredient Information	CAS#	Wt. % Range
n-Propyl alcohol	71-23-8	75.0-80.0
Propane	74-98-6	3.0-8.0
Isobutane	74-28-5	15.0-20.0
Polyphenyl ether	proprietary	0.1-1.0

Hazard Identification

Emergency Overview: Clear, colorless liquid with strong alcohol odor. Liquid will irritate eyes and skin under repeated or prolonged exposure. This product is extremely flammable. Breathing high concentrations of product may produce drowsiness and a headache.

Potential Health Effects:

- Eyes:** Liquid, aerosols and vapors of this product are irritating and can cause pain, tearing, reddening and swelling accompanied by a stinging sensation.
- Skin:** Contact causes skin irritation.
- Ingestion:** Harmful if swallowed. Irritating to mouth, throat and stomach. May cause vomiting.
- Inhalation:** Harmful if inhaled. High concentrations in immediate area can displace oxygen and can cause dizziness, unconsciousness, and even death with longer exposure. Keep people away from such vapors without self-contained breathing apparatus.
- Pre-Existing Medical Conditions Aggravated by Exposure:** Heart, lung, skin, eye.

First Aid

- Eyes:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Have eyes examined and tested by medical personnel if irritation develops persists.
- Skin:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash clothing separately before reuse.
- Ingestion:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get immediate medical attention.
- Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Fire and Explosion Information

- Flash Point:** -156 F (propellant) / 73 F (liquid) LEL/UEL: 1.8/9.5 (% by volume in air propellant)
- Extinguishing Media:** Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
- Fire Fighting Instructions:** As in any fire, wear self-contained breathing apparatus (pressure-demand, MSHA/NIOSH approved or equivalent) and full protective gear.

Accidental Release Measures

- Large Spills:** Shut off leak if possible and safe to do so. Wear a self-contained breathing apparatus and appropriate personal protective equipment. Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal. Do not flush to sewer. Avoid runoff into storm sewers and ditches which lead to waterways.
- Small Spills:** Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container for proper disposal.

Handling and Storage Information

Avoid prolonged or repeated contact with eyes, skin, and clothing. Wash hands before eating. Use with adequate ventilation. Avoid breathing product vapor or mist. Do not reuse this container. Store in a cool dry place away from heat, sparks and flame. Keep container closed when not in use. Do not store in direct sunlight. **KEEP OUT OF REACH OF CHILDREN.**

Exposure Information/Personnel Protection

Exposure Guidelines:

CHEMICAL NAME	ACGIH TWA	OSHA PEL	ACGIH STEL
n-Propyl alcohol	200 ppm	200 ppm	250 ppm
Propane	NA	1000 ppm	NA
Isobutane	NA	NA	NA
Polyphenyl ether	NA	NA	NA

(All values listed are from the ACGIH Guide to Occupational Exposure Values - 1991).

Work/Hygienic Practices: Good general ventilation should be sufficient to control airborne levels. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product. This material does not have established exposure limits. Wear a positive pressure air-supplied respirator in situations where there may be potential for airborne exposure. Wear safety glasses with side shields (or goggles) and a full face shield. Wear rubber or other chemically resistant gloves when handling this material.

NFPA and HMIS Codes:

	NFPA	HMIS
Health	2	2
Flammability	4	4
Reactivity	1	1
Personal Protection	-	B

Toxicological Information (All values listed are from the NIOSH RTECS 1985-1986)

- Inhalation:** n-Propyl alcohol Rat LCLo 4000 ppm/4 hr **Ingestion:** n-Propyl alcohol Rat LD50 1870 mg/kg
- (No toxic effects noted) (No toxic effects noted)
- Skin:** n-Propyl alcohol Rabbit 500 mg open; MILD **Eye:** Rabbit 4 mg open; SEVERE

Physical and Chemical Properties

Physical State: Clear, colorless liquid
Odor: Mild alcohol
pH: NA
Vapor Pressure: 15 mm Hg @ 77°F(liquid only)
Vapor Density: 2.1 @ 77°F (liquid only)
 (Air=1)
Percent Volatile: 99.5%
Boiling Point: 207°F(liquid only)
 -43.7F(propellant only)

Solubility in Water: substantially
Specific Gravity: (Water =1) 0.80 (liquid only)
Evaporation Rate: 1
 (Butyl acetate=1)
Viscosity: 1 (Approximately)
 (Water =1)
Melting Point: NA
Can Pressure at 77F: 46 psig

Stability and Chemical Properties

Stability: This product is stable. Conditions to Avoid: Do not spray near open flames, red hot surfaces or other sources of ignition.
Incompatibility: Do not mix with powdered alkali and alkaline earth metals or strong oxidizing agents.
Products of Decomposition: Thermal decomposition may release carbon monoxide, carbon dioxide and incompletely burned hydrocarbons.
Hazardous Polymerization: Will not occur.

Disposal Considerations

Dispose of in accordance with all federal, state and local regulations. Water runoff can cause environmental damage.

Transportation Information

Proper Shipping Name	UN Number	Hazard Class	Sub. Risk	Pkg. Group	Hazard Label	Pkg. Instr.	Max. Quantity
<u>Air:</u> Aerosols, flammable n.o.s.	UN 1950	2.1	NA	NA	Flammable Gas	203	75:150 kg
<u>Ground:</u> Consumer Commodity	ORM-D	NA	NA	NA	ORM-D	Pkg. Auth.	173.306

Regulatory Information

SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372).

Chemical Name	CAS#	Wt. % Range
CONTAINS NO CHEMICALS LISTED UNDER SARA TITLE III		

This information should be included on all MSDSs copied and distributed for this material.

TOXIC SUBSTANCES CONTROL ACT (TSCA)

All ingredients of this product are listed on the TSCA Inventory.

Other Information

Product is a Level 2 aerosol. Do not puncture or incinerate containers. Normal ventilation for standard manufacturing practices is usually adequate. Local exhaust should be used when large amounts are released.

Cancer Information: No ingredients listed as human carcinogens by NTP or IARC

Environmental Impact Information

Avoid runoff into storm sewers and ditches which lead to waterways. Water runoff can cause environmental damage.

Environmental Impact Data
(percent by weight)

CFC	0.0%	VOC	99.5%
HCFC	0.0%	HFC	0.0%
Cl. Solv.	0.0%	ODP	0.0

REPORTING

US regulations require reporting spills of this material that could reach any surface waters. The toll-free number for the US Coast Guard National Response Center is:
 1-800-424-8802

For more information call:
 Michael S. Watkins
 1-800-645-5244

To the best of our knowledge, the information contained herein is accurate. However, all materials may present unknown hazards and should be used with caution. In particular, improper use of our products and their inappropriate combination with other products and substances may produce harmful results which cannot be anticipated. Final determination of the suitability of any material is the sole responsibility of the user. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that may exist.