

Material Safety Data Sheet

Complies with OSHA's Hazard Communication
Standard 29 CFR 1910.1200

JUL 25 1994

NFPA
FIRE 4
HEALTH 2
REACTIVITY 1

SECTION I - IDENTITY AND MANUFACTURER'S INFORMATION

Manufacturer's Name & Address	The Fuller Brush Company PO Box 729 Great Bend, Kansas 67530	Product Name	Graffiti Cleaner
Chemical Family	Pressurized water soluble, chlorinated solvent based	Product Number	9179
E.P.A. Reg. No.	N/A	Package Size	17 oz.
Emergency Telephone No.	1-316-792-1711		
Preparer	Bill Dayton	Date	2/13/91
		Signature	<i>Bill Dayton</i>

SECTION II - HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Hazardous Components	CAS#	OSHA TWA	ACGIH TWA	Percent
Propylene Glycol Methyl Ether	107-98-2	NE	100 ppm	36.0
Dipropylene Glycol Methyl Ether	34590-94-8	100 ppm	100 ppm	27.0
1,1,1-Trichloroethane	71-55-6	350 ppm	350 ppm	26.0
Propane	74-98-6	1000 ppm	1000 ppm	10.0

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

No Physical Hazards	Flammable Aerosol	Unstable - Reactive
Combustible Liquid	Explosive	Water Reactive
Compressed Gas	Flammable Liquid/Solid	Oxidizer
Flammable Gas	Pyrophoric	Organic Peroxide

Boiling Point °F	Compressed Gas	Specific Gravity (water = 1)	1.016
Vapor Pressure (mm Hg)	54psig @ 70F	%Volatiles by Weight	100
Vapor Density (air = 1)	Unknown	Evaporation Rate (water = 1)	Unknown
Solubility in Water	Dispersible	pH	N/A
Appearance and Odor	Wet spray with cherry, solvent odor.		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used)	Conc. 124F (TOC)	Flammable Limits	LEL unknown UEL unknown
---------------------------	------------------	------------------	-------------------------

Extinguishing Media

Special Fire Fighting Procedures
Keep aerosols cooled with water to preventing bursting.

Unusual Fire and Explosion Hazards
FLAMMABLE AEROSOLS: Temperatures in excess of 120F may cause bursting. Contents of ruptured cans contribute combustible materials in the event of fire.

SECTION V - REACTIVITY DATA

Stability: Unstable Conditions to Avoid N/A
Stable

Incompatibility Do not mix with any other materials
(Materials to Avoid)

Hazardous Decomposition Products or By Products
With extreme heat or fire, releases typical hydrocarbon decomposition by-products.

Hazardous Polymerization Conditions to Avoid
May Occur Will Not Occur

SECTION VI - HEALTH HAZARD DATARoute (s) of Entry Inhalation x Skin x Eye x Ingestion x

No Health Hazard	<u> </u>	Reproductive Toxin	<u> </u>	Sensitizer	<u> </u>
Toxic	<u> </u>	Irritant	<u> </u>	Carcinogen	<u> </u>
Highly Toxic	<u> </u>	Corrosive	<u> </u>	See Target Organs	<u> X </u>

TARGET ORGANS

Lungs	<u> X </u>	Prostrate	<u> </u>	Central Nervous System	<u> X </u>
Heart	<u> </u>	Blood	<u> </u>	Cardiovascular System	<u> </u>
Kidney	<u> </u>	Liver	<u> X </u>	Mucous Membranes	<u> X </u>
Eyes	<u> X </u>	Mutagen	<u> </u>	Autonomic Nervous System	<u> </u>
Skin	<u> X </u>	Teratogen	<u> </u>	Respiratory System	<u> </u>

Carcinogenicity: None Known x NTP IARC Monographs OSHA Regulated Medical Conditions Generally Aggravated by Exposure:
Impaired Liver Function**Signs and Symptoms of Exposure:**Eye, skin & mucous membrane irritation. Dizziness, nausea, anesthetic effects.
Possible Chemical pneumonia from aspiration.**Emergency and First Aid Procedures:**

Eye and skin: Flush with copious amounts of water. Contact a physician if irritation persists. Inhalation: Remove to fresh air. Ingestion: Do Not Induce Vomiting. Contact a physician or Poison Control Center immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE**Steps to be taken in case Material is released or Spilled:**Eliminate all ignition sources. Small spills: Mop up, rinse with detergent & water.
Large Spills: Absorb with an inert, dike or turn container over as applicable.**Waste Disposal Method:**

Do Not Puncture or Incinerate. Single Unit: Wrap in newspaper and dispose in trash receptacle. Large Amounts: Dispose in accordance with Local, State and Federal Regulations.

Potential EPA Hazardous Waste Code(s): D001

Precautions to be taken in Handling and Storage:

NFPA "LEVEL 3 AEROSOLS" Store at 40-90F. Temperatures in excess of 120F may cause bursting. Follow label directions. KEEP OUT OF REACH OF CHILDREN.

SECTION VII - CONTROL MEASURES**Respiratory Protection (Specify Type)**

None required with general ventilation

Ventilation:	Local Exhaust	<u> Required </u>	Special	<u> </u>
	Mechanical	<u> </u>	Other	<u> </u>

Protective Gloves: None required Eye Protection: Recommended by manufacture

Other Protective Clothing and Equipment:
None required**SECTION IX - SHIPPING INFORMATION****DOT Proper Shipping Name and Number:**

Consumer Commodity, ORM-D

NE = Not Established

N/A = Not Applicable