Page 1 of 2 Issue Date: 9-30-92

MATERIAL SAFETY DATA SHEET

Reckitt & Colman Inc. P. O. Box 943 Wayne, NJ 07474-0943

800-338-6167 for medical emergency 800-424-9300 for transportation emergency 201-633-6700 for technical information during business hours NFPA Hazard Rating:
Health 1
Flammability 2
Reactivity 0

SECTION 1 MATERIAL IDENTIFICATION

Name: Gulf Lite Charcoal Starter

SECTION 2 INGREDIENT INFORMATION

		% by	Exposure Limits	
Chemical/Common Name	CAS No.	Weight	OSHA TWA	ACGIH TWA
Aliphatic hydrocarbon mixture	64742-48-9 64742-47-8	100	Not established	Not established

SECTION 3 HAZARDS IDENTIFICATION

Signs and Symptoms of Overexposure: Harmful or fatal if swallowed.

Potential Health Effects

Eye Contact: Not an eye irritant

Skin Contact: Not a primary skin irritant

Ingestion: Not orally toxic. However, may be aspirated into lungs if swallowed resulting in

pulmonary edema and chemical pneumonitis.

Inhalation: Inhalation toxicity not determined. May cause headache, dizziness, nausea,

unconsciousness.

Chronic Effects: The product has not been tested as a whole for chronic effects. No ingredient is a listed carcinogen (NTP, IARC, OSHA).

Medical Conditions Recognized as Being Aggravated by Exposure to the Product: None known

SECTION 4 FIRST AID MEASURES

Eye Contact: Flush immediately with water. Remove contact lenses. Continue flushing for 15 minutes.

Skin Contact: Wash with soap and water.

Ingestion: DO NOT induce vomiting. Call physician immediately.

Inhalation: Remove to fresh air.

Name: Gulf Lite Charcoal Starter

Page 2 of 2 Issue Date: 9-30-92

SECTION 5 FIRE FIGHTING MEASURES

Flammability Properties

Flash Point: 140 °F TCC Flame Extension: Not applicable

Extinguishing Media: CO₂, dry chemical, foam

Fire Fighting Instructions: Water fog or spray may be used to cool exposed containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

In Case of Leakage or Spillage: Soak up with absorbent material. Contain large spills.

SECTION 7 HANDLING AND STORAGE

Store away from heat or flame. Do not use on burning or glowing coals. Use outdoors only. Keep out of reach or children.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation Requirements: Use only in well-ventilated area.

Personal Protective Equipment: None required. Avoid frequent or prolonged contact with skin. Avoid

prolonged or repeated breathing of vapor.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Colorless mobile liquid

Odor: Slight petroleum

Boiling Range: Approx. 350-510 ° F

Freezing Point: Less than 32°F

Solubility in Water: Insoluble

Volatiles: 100 %

Vapor Density (Air = 1): >5

pH: Not applicable

Melting Point: Not applicable

Specific Gravity: 0.78 @ 60/60°F

Vapor Pressure: 1 mm Hg @ 77°F

Pressure in Can: Not applicable

SECTION 10 STABILITY AND REACTIVITY

Storage Stability: X Stable Unstable Conditions to Avoid: None known Hazardous Polymerization: May occur X Will not occur Conditions to Avoid: None known Incompatibility (Materials to avoid): None known Hazardous Decomposition Products: CO_x, smoke

SECTION 11 DISPOSAL

Proper Disposal Method: Transport to secure landfill, approved incinerator, or other facility in accord with federal, state, and local law.

SECTION 12 ADDITIONAL COMMENTS

CERCLA ("Superfund") Reportable Quantity: Not applicable

SARA Section 313 Chemicals: None

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof.