MATERIAL SAFETY DATA SHEET

State Chemical Division - State Industrial Products

3100 Hamilton Avenue, Cleveland, OH 44114 (216) 861-7114

State Chemical Ltd.

1745 Meyerside Dr., Unit #1, Mississauga, Ontario L5T 1C6 (905) 670-4669

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name Product Description: **IN-SIGHT**

24 Hour Emergency CHEMTREC Number:

800-424-9300

MSDS Number:

700142

2. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS Number	Weight	ACGIH	OSHA
Propane	74-98-6	< 5.0%	2500 ppm	1000 ppn
Butane	106-97-8	< 5.0%	800 ppm	800 ppm
2-Butoxyethanol	111-76-2	< 5.0%	25 ppm	25 ppm

Foaming aerosol glass cleaner.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Extremely flammable. Contents under pressure. Do not puncture, incinerate or expose to temperature above 120°F(49°C). Eye, skin and respiratory irritant. Vapor harmful.

Routes of Exposure:

Exposure may be by inhalation and/or skin or eye contact, depending on conditions of use. To minimize exposure, follow recommendations for proper

use, ventilation and personal protective equipment.

Eye Contact:

Skin Contact:

May cause eye irritation. Redness and itching or burning sensation may indicate excessive exposure.

May cause skin irritation. Avoid prolonged skin contact. Contains 2-Butoxyethanol which may be absorbed through skin. Redness and itching or burning

sensation may indicate excessive exposure.

Ingestion:

May be harmful if swallowed. Vomiting is a sign of overexposure.

Inhalation: General:

May irritate respiratory tract. Difficulty breathing is a sign of overexposure.

May cause dizziness or narcosis at high vapor concentrations. May cause nervous system depression. Extreme overexposure may result in

unconsciousness and possibly death. Headache, dizziness, nausea and loss of coordination are indications of excessive exposure to vapors or spray mists.

Prolonged exposure to solvent ingredients may cause adverse effects to the liver, urinary, blood forming and reproductive systems. Reports have

associated repeated or prolonged exposure to solvents with permanent brain and nervous system damage.

4. FIRST AID MEASURES

Eye Contact:

Promptly flush with a large amount of water for at least 15 minutes. Seek medical attention.

Skin Contact:

Promptly wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before reuse. If irritation persists, seek

medical attention.

Inhalation: Ingestion:

Remove to fresh air. Restore breathing if necessary. Keep warm and quiet. If irritation persists, consult a physician

Give several glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. Seek medical attention.

5. FIRE FIGHTING MEASURES

Flashpoint:

Propellant < 0°F

Lower Explosive Limit(LEL): Fire and Explosion Hazards:

Upper Explosive Limit(UEL):

10.6 Autoignition Temperature: NA

Heated cans may burst. Isolate from heat, electrical equipment, sparks and open flame. Closed containers may explode when exposed to

extreme heat. Application to hot surfaces requires special precautions. During emergency conditions overexposure to decomposition

products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

Extinguishing Media:

Fire Fighting Instructions:

Carbon Dioxide, dry chemical, foam, Full protective equipment including self-contained breathing apparatus should be used. Water spray maybe ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion

when exposed to extreme heat.

6. ACCIDENTAL RELEASE MEASURES

Remove all sources of ignition. Ventilate area and remove with inert absorbent. Dispose of in accordance with all Federal, State and Local Regulations regarding waste disposal. Product as supplied is a DOO1 unspecified ignitable waste.

7. HANDLING AND STORAGE

Keep away from heat, flames, sparks or other sources of ignition. Vapors will accumulate readily and may ignite explosively. Do not smoke. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances. Consult NFPA Code. Use approved Bonding and Grounding procedures. Contents under pressure. Do not puncture, incinerate or expose to temperature above 120°F(49°C). Heat from sunlight, radiators, stoves, hot water and other heat sources could cause container to burst. Do not take internally. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. Keep out of reach of children. Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes. Wash hands after using. When spraying more than one half can continuously or more than one can consecutively, use NIOSH-approved respirator.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls: Local exhaust preferable. General exhaust acceptable if the exposure to materials is maintained below applicable exposure limits.

Personal Protective Equipment: Respiratory:

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted NIOSH-approved organic vapor/particulate respirator.

Wear approved safety glasses with unperforated sideshields. Eve:

None required for normal application of aerosol products where minimal skin contact is expected. For long or repeated contact, wear chemically resistant gloves. Skin-

An emergency eyewash station or source of clean potable water should be available in case of accidental eye contact. Other:

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

White foaming aerosol.

Odor: Product Weight:

Physical State: pH:

Aerosol.

7.0

< 0 to -343° F; <-18 - 172° C

Vapor Density:

7.94 lb./gal.; 951 g/L

Boiling Point: Evaporation Rate:

Faster than Ether.

Melting Point:

Heavier than air.

VOC Content:

< 12%

Specific Gravity: Solubility in Water:

NA 0.96 NA

10. STABILITY AND REACTIVITY

Hazardous Polymerization:

Will not occur.

Conditions to Avoid:

Heat, sparks, flames or other sources of ignition.

Incompatibility:

None expected.

Hazardous Decomposition Products: By Fire: Carbon Dioxide, Carbon Monoxide.

11. TOXICOLOGICAL INFORMATION

IARC / NTP / OSHA: This product contains no ingredients at 0.1% or greater that is listed as a human carcinogen.

Hazardous Ingredients Propane

CAS Number

LD50

Butane

106-97-8

NE 1480 mg/kg (oral rat)

658 mg/l/4 hr (rat) 700 ppm/7 hr (mouse)

2-Butoxyethanol 111-76-2

ECOLOGICAL INFORMATION

12. NA

13. DISPOSAL CONSIDERATIONS

Do not incinerate. Depressurize container. Dispose of in accordance with all Federal, State and Local Regulations regarding pollution and waste disposal. Product as supplied is a DOO1 unspecified ignitable waste.

14. TRANSPORT INFORMATION

DOT Shipping Data:

Consumer Commodity, ORM-D

Canadian TDG:

Shipped in accordance with 49 CFR as part of a transborder shipment authorized under Section 5.2 (1) of the Canadian Transportation of

Dangerous Goods.

For International and Air Shipments: Aerosols, Flammable, 2.1, UN1950.

15. REGULATORY INFORMATION

All ingredients in this product are listed or exempt from listing on the TSCA Chemical Inventory.

CEPA: Proposition 65: All ingredients in this product are listed or exempt from listing on the Canadian DSL/NDSL. This product may contain trace amounts of the following chemicals that are known to the state of California to cause cancer, birth defects or other

reproductive harm:

1.4 Dioxane

123-91-1 < 0.01% 75-21-8 < 0.01%

VOC: SARA 313:

Ethylene Oxide This product as regulated by California and other states, is classified as a "glass cleaner, aerosol" with a maximum VOC content of 12%. This product contains that following toxic chemicals that are subject to the reporting requirements of Section 313 of the Emergency Planning

and Community Right-To-Know Act of 1986 (40 CFR 372.65C):

Glycol Ethers

HMIS Classification:

Health = 2

Flammability = 4

Reactivity = 0

Personal Protection = A

WHMIS Classification: Class A; Class B, Division 5; Class D, Division 2B

16. OTHER INFORMATION

NA = Not Available or Not Applicable

NE = Not Established

Read and follow all label directions and precautions before using the product. These products are intended for industrial and institutional use only. NOT FOR HOUSEHOLD USE OR RESALE KEEP OUT OF THE REACH OF CHILDREN. While we believe that the data contained herein is factual and the opinions expressed are those of qualified experts, the data are not to be taken as a warranty or representation for which the company assumes legal responsibility. They are offered solely for your consideration, investigation, and verification. Any use of these data and information must be determined by the user to be in accordance with applicable Federal, State, and Local Laws and regulations.

HEALTH AND SAFETY INFORMATION:

(216) 861-7114

Completed On: January 2005

Replaces: July 2000

Completed By: Regulatory Affairs Specialist,