

DATE: 05/22/06 ACCT: 888235001 PAGE: 1
INDEX: D61395037 CAT NO: AC327270010 PO NBR: CROSSGROVE-FACDEV-52113

Material Safety Data Sheet

Isopropanol
MSDS# 95533

Section 1 - Chemical Product and Company Identification

MSDS Name: Isopropanol
95533
Catalog Numbers: 55020
Synonyms: Isopropanol; Dimethylcarbinol; sec-Propyl alcohol; Rubbing alcohol; Petrohol; 1-Methylethanol; 1-Methylethyl alcohol; 2-Hydroxypropane; 2-Propyl alcohol; Isopropyl alcohol; Propan-2-ol; IPA; 2-Propanol.
Company Identification: Fisher Diagnostics

8365 Valley Pike
Middletown, VA 22645-0307

For information in the US, call:
800-528-0494
Emergency Number US:800-524-0294
CHEMTREC Phone Number, US:
800-424-9300

Section 2 - Composition, Information on Ingredients

CAS#: 67-63-0
Chemical Name: 2-Propanol
%: >= 99.5
EINECS#: 200-661-7

Hazard Symbols:

XI F
Risk Phrases:
11 36 67

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Warning! Flammable liquid and vapor. Causes respiratory tract irritation. Prolonged or repeated contact causes defatting of the skin with irritation, dryness, and cracking. Causes eye irritation. Hygroscopic (absorbs moisture from the air). May cause central nervous system depression. Aspiration hazard if swallowed. Can enter lungs and cause damage. May form explosive peroxides. This material has been reported to be susceptible to autoxidation and therefore should be classified as peroxidizable. Breathing vapors may cause drowsiness and dizziness.

Target Organs: Central nervous system, respiratory system, eyes, skin.

Potential Health Effects

Eye: Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury.

Skin: May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported. May be absorbed through intact skin.

Ingestion: Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

Chronic: Prolonged or repeated skin contact may cause defatting and dermatitis.

Section 4 - First Aid Measures

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical aid.

Skin: In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

Ingestion: Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

4,156

DATE: 05/22/06 ACCT: 888235001 PAGE: 2
INDEX: D61395037 CAT NO: AC327270010 PO NBR: CROSSGROVE-FACDEV-52113

Notes to Physician:

Urine acetone test may be helpful in diagnosis. Hemodialysis should be considered in severe intoxication. Treat symptomatically and supportively.

General Information:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. May form explosive peroxides. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Extinguishing Media:

Water may be ineffective. Do NOT use straight streams of water. For large fires, use dry chemical, carbon dioxide, alcohol-resistant foam, or water spray. For small fires, use carbon dioxide, dry chemical, dry sand, or alcohol-resistant foam. Cool containers with flooding quantities of water until well after fire is out.

Autoignition Temperature:399 deg C (750.20 deg F)

Flash Point:12 deg C (53.60 deg F)

Explosion Limits: Lower: 0 vol %

Explosion Limits: Upper:12.7 @ 93&C

NFPA Rating:

health: 1; flammability: 3; instability: 0;

Section 6 - Accidental Release Measures

General Information:

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Use water spray to dilute spill to a non-flammable mixture. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Keep container tightly closed. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor or mist. Do not allow to evaporate to near dryness.

Storage:

Keep away from heat, sparks, and flame. Do not store in direct sunlight. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances. Flammables-area. After opening, purge container with nitrogen before reclosing. Periodically test for peroxide formation on long-term storage. Addition of water or appropriate reducing materials will lessen peroxide formation. Store protected from moisture. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. All peroxidizable substances should be stored away from heat and light and be protected from ignition sources.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:

Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

| Chemical Name | ACGIH | NIOSH | OSHA - Final PELs |
|---------------|-----------------------|--|--|
| 2-Propanol | 200 ppm; 400 ppm STEL | 400 ppm TWA; 980 mg/m ³ TWA 2000 ppm IDLH | 400 ppm TWA; 980 mg/m ³ TWA |

OSHA Vacated PELs:

2-Propanol:
400 ppm TWA; 980 mg/m³ TWA
Personal Protective Equipment

Eyes:

Wear chemical splash goggles.

Skin:

Wear appropriate gloves to prevent skin exposure.

Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Respirators:

4,157

DATE: 05/22/06 ACCT: 888235001 PAGE: 3
INDEX: D61395037 CAT NO: AC327270010 PO NBR: CROSSGROVE-FACDEV-52113

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: Liquid
Color: colorless
Odor: alcohol-like
pH: Not available
Vapor Pressure: 33 mm Hg @ 20 deg C
Vapor Density: 2.1 (Air=1)
Evaporation Rate: 1.7 (n-butyl acetate=1)
Viscosity: 2.27 mPas @ 20C
Boiling Point: 82 deg C @ 760 mmHg (179.60&F)
Freezing/Melting Point: -88 deg C (-126.40&F)
Decomposition Temperature: Not available
Solubility in water: Miscible
Specific Gravity/Density: 0.7850 (water=1)
Molecular Formula: C3H8O
Molecular Weight: 60.09

Section 10 - Stability and Reactivity

Chemical Stability:
Under normal storage conditions, peroxidizable compounds can form and accumulate peroxides which may explode when subjected to heat or shock. This material is most hazardous when peroxide levels are concentrated by distillation or evaporation. Isopropanol is susceptible to autoxidation and therefore should be classified as peroxidizable.

Conditions to Avoid:

Light, ignition sources, excess heat, exposure to moist air or water.

Incompatibilities with Other Materials

Strong oxidizing agents, strong acids, strong bases, amines, ammonia, ethylene oxide, isocyanates, acetaldehyde, chlorine, phosgene, Attacks some forms of plastics, rubbers, and coatings., aluminum at high temperatures.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

RTECS#:

CAS# 67-63-0: NT8050000

LD50/LC50:

RTECS: CAS# 67-63-0: Draize test, rabbit, eye: 100 mg
Severe; Draize test, rabbit, eye: 10 mg Moderate; Draize test, rabbit, eye: 100 mg/24H Moderate; Draize test, rabbit, skin: 500 mg Mild; Inhalation, mouse: LC50 = 53000 mg/m3; Inhalation, rat: LC50 = 16000 ppm/8H; Inhalation, rat: LC50 = 72600 mg/m3; Oral, mouse: LD50 = 3600 mg/kg; Oral, mouse: LD50 = 3600 mg/kg; Oral, rabbit: LD50 = 6410 mg/kg; Oral, rat: LD50 = 5045 mg/kg; Oral, rat: LD50 = 5000 mg/kg; Skin, rabbit: LD50 = 12800 mg/kg;.

Carcinogenicity:

2-Propanol -

IARC: Group 3 (not classifiable)

Epidemiology:

No information found

Teratogenicity:

A rat & rabbit developmental toxicity study showed no teratogenic effects at doses that were clearly maternally toxic. In a separate rat study, no evidence of developmental neurotoxicity was associated with gestational exposures to IPA up to 1200 mg/kg/d

Reproductive:

See actual entry in RTECS for complete information.

Neurotoxicity:

In rats exposed to isopropanol by inhalation, acute neurotoxicity was noted at 1 and 6 hours at 5000 ppm, but only minimal effects were seen at 1500 ppm and the animals recovered within 5 hours. No toxicity was noted at 500 ppm.

Mutagenicity:

See actual entry in RTECS for complete information.

Other:

See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Ecotoxicity:

Fish: Fathead Minnow: >1000 ppm; 96h; LC50Daphnia: >1000 ppm; 96h; LC50Fish: Gold orfe: 8970-9280 ppm; 48h; LC50

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste.

US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series: None listed.

Section 14 - Transport Information

US DOT

Shipping Name: ISOPROPANOL

4,158

DATE: 05/22/06 ACCT: 888235001 PAGE: 4
INDEX: D61395037 CAT NO: AC327270010 PO NBR: CROSSGROVE-FACDEV-52113

Hazard Class: 3
UN Number: UN1219
Packing Group: II
Canada TDC
Shipping Name: ISOPROPANOL
Hazard Class: 3
UN Number: UN1219
Packing Group: II

Section 15 - Regulatory Information

US Federal

TSCA

CAS# 67-63-0 is listed on the TSCA Inventory.

Health & Safety Reporting List

CAS# 67-63-0: Effective 12/15/86, Sunset 12/15/96
Chemical Test Rules

CAS# 67-63-0: 40 CFR 799.2325

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQs

None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPQ.

SARA Codes

CAS # 67-63-0: acute, chronic, flammable.

Section 313

This material contains 2-Propanol (CAS# 67-63-0, 99.5%), which is subject to the reporting requirements of Section 313 of SARA Title III and 40 CFR Part 372.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone depleters.

This material does not contain any Class 2 Ozone depleters.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous

Substances under the CWA.

None of the chemicals in this product are listed as Priority

Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants

under the CWA.

OSHA:

STATE

2-Propanol can be found on the following state right to know lists:

California, New Jersey, Pennsylvania, Minnesota, Massachusetts.

California Prop 65

California No Significant Risk Level:

None of the chemicals in this product are listed.

European/international Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: XI F

Risk Phrases:

R 11 Highly flammable.

R 36 Irritating to eyes.

R 67 Vapours may cause drowsiness and dizziness.

Safety Phrases:

S 7 Keep container tightly closed.

S 16 Keep away from sources of ignition - No

smoking.

S 24/25 Avoid contact with skin and eyes.

S 26 In case of contact with eyes, rinse immediately

with plenty of water and seek medical advice.

WGK (Water Danger/Protection)

CAS# 67-63-0: 1

Canada

CAS# 67-63-0 is listed on Canada's DSL List

Canadian WHMIS Classifications: B2, D2B

This product has been classified in accordance with the hazard

criteria of the Controlled Products Regulations and the MSDS

contains all of the information required by those regulations.

CAS# 67-63-0 is listed on Canada's Ingredient Disclosure List

Section 16 - Other Information

MSDS Creation Date:

7/27/1999

Revision #10 Date

8/17/2004

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.