

Material Safety Data Sheet

Isopropyl alcohol 70% in water

MSDS# 89530

Section 1 - Chemical Product and Company Identification

MSDS Name: Isopropyl alcohol 70% in water

Catalog Numbers:

AC613190040, AC613245000, A459-1, A459-20, A459-4, A459-500, NC9761180

Synonyms:

Isopropanol; Dimethylcarbinol; sec-Propyl alcohol; Rubbing alcohol; Petrolol; 1-Methylethanol; 1-Methylethyl alcohol; 2-Hydroxypropane; 2-Propyl alcohol; Isopropyl alcohol; Propan-2-ol; IPA; 2-Propanol.

Company Identification:

Fisher Scientific

One Reagent Lane  
 Fair Lawn, NJ 07410

For information in the US, call:

201-796-7100

Emergency Number US: 201-796-7100

CHEMTREC Phone Number, US:

800-424-9300

Section 2 - Composition, Information on Ingredients

CAS#: 67-63-0

Chemical Name: Isopropyl alcohol

INECS#: 200-661-7

Hazard Symbols: F XI

Risk Phrases: 11 36 67

CAS#: 7732-18-5

Chemical Name: Water

INECS#: 231-791-2

Hazard Symbols:

Risk Phrases:

Text for R-phrases: see Section 16

Hazard Symbols:

Risk Phrases:

11 36 67

Section 3 - Hazards Identification

Warning! Flammable liquid and vapor. Prolonged or repeated contact causes defatting of the skin with irritation, dryness, and cracking. May cause central nervous system depression. Aspiration hazard if swallowed. Can enter lungs and cause damage. Breathing vapors may cause drowsiness and dizziness. Causes eye and respiratory tract irritation.

Target Organs: Central nervous system, respiratory system, eyes,

skin.

Potential Health Effects

Eye: Produces irritation, characterized by a burning sensation, redness, tearing, inflammation, and possible corneal injury. May cause transient corneal injury.

Skin: May cause irritation with pain and stinging, especially if the skin is abraded. Isopropanol has a low potential to cause allergic skin reactions; however, rare cases of allergic contact dermatitis have been reported. May be absorbed through intact skin.

Ingestion: Causes gastrointestinal irritation with nausea, vomiting and diarrhea. May cause kidney damage. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal.

Inhalation: Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. May cause narcotic effects in high concentration. Causes upper respiratory tract irritation. Inhalation of vapors may cause drowsiness and dizziness.

Chronic: Prolonged or repeated skin contact may cause defatting and dermatitis.

Section 4 - First Aid Measures

Eyes: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical aid.

Skin: In case of contact, flush skin with plenty of water. Remove contaminated clothing and shoes. Get medical aid if irritation develops and persists. Wash clothing before reuse.

Ingestion:

RECEIVED DEC 05 2008

Potential for aspiration if swallowed. Get medical aid immediately. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs naturally, have victim lean forward.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical aid.

Notes to Physician:

Urine acetone test may be helpful in diagnosis. Hemodialysis should be considered in severe intoxication. Treat symptomatically and supportively.

Section 5 - Fire Fighting Measures

General Information:

As in any fire, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. Vapors may form an explosive mixture with air. Use water spray to keep fire-exposed containers cool. Flammable liquid and vapor. Vapors are heavier than air and may travel to a source of ignition and flash back. Vapors can spread along the ground and collect in low or confined areas.

Extinguishing Media:

Water may be ineffective. Do NOT use straight streams of water. For large fires, use dry chemical, carbon dioxide, alcohol-resistant foam, or water spray. For small fires, use carbon dioxide, dry chemical, dry sand, or alcohol-resistant foam. Cool containers with flooding quantities of water until well after fire is out.

Autoignition Temperature: 399 deg C ( 750.20 deg F)

Flash Point: 18 deg C ( 64.40 deg F)

Explosion Limits: Lower: 2.0 vol %

Explosion Limits: Upper: 12.7 @ 93.3&C

NFPA Rating:

health: 1; flammability: 3; instability: 0;

Section 6 - Accidental Release Measures

General Information:

Use proper personal protective equipment as indicated in Section 8.

Spills/Leaks:

Absorb spill with inert material (e.g. vermiculite, sand or earth), then place in suitable container. Use water spray to dilute spill to a non-flammable mixture. Clean up spills immediately, observing precautions in the Protective Equipment section. Remove all sources of ignition. Use a spark-proof tool. Provide ventilation. A vapor suppressing foam may be used to reduce vapors.

Section 7 - Handling and Storage

Handling:

Wash thoroughly after handling. Remove contaminated clothing and wash before reuse. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Avoid contact with eyes, skin, and clothing. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Take precautionary measures against static discharges. Keep container tightly closed. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Use only with adequate ventilation. Avoid breathing vapor or mist.

Storage:

Keep away from sources of ignition. Store in a tightly closed container. Keep from contact with oxidizing materials. Store in a cool, dry, well-ventilated area away from incompatible substances.

Section 8 - Exposure Controls, Personal Protection

Engineering Controls:

Use explosion-proof ventilation equipment. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Use adequate general or local exhaust ventilation to keep airborne concentrations below the permissible exposure limits.

Exposure Limits

Chemical Name	ACGIH	NIOSH	OSHA - Final PELs
Isopropyl alcohol	200 ppm; 400 ppm STEL	400 ppm TWA; 980 mg/m3 TWA 2000 ppm IDLH (10% LEL)	400 ppm TWA; 980 mg/m3 TWA
Water	none listed	none listed	none listed

OSHA Vacated PELs:

Isopropyl alcohol:

400 ppm TWA; 980 mg/m3 TWA

Water:

None listed

Personal Protective Equipment

Eyes:

Wear chemical splash goggles.

Skin:

Wear appropriate protective gloves to prevent skin exposure.

Clothing:

Wear appropriate protective clothing to prevent skin exposure.

Respirators:

A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements or European Standard EN 149 must be followed whenever workplace conditions warrant respirator use.

Section 9 - Physical and Chemical Properties

Physical State: Liquid  
Color: colorless  
Odor: alcohol-like  
pH: Not available  
Vapor Pressure: 33 mm Hg @ 20 deg C  
Vapor Density: 2.1 (Air=1)  
Evaporation Rate: 1.7 (n-butyl acetate=1)  
Viscosity: 2.27 mPas @ 20 deg C  
Boiling Point: 82 deg C @ 760 mm Hg ( 179.60&F)  
Freezing/Melting Point: -88 deg C ( -126.40&F)  
Decomposition Temperature: Not available  
Solubility in water: Miscible  
Specific Gravity/Density: 0.7850 (water=1)  
Molecular Formula: C3H8O  
Molecular Weight: 60.09

Section 10 - Stability and Reactivity

Chemical Stability:

Stable.

Conditions to Avoid:

Ignition sources, excess heat.

Incompatibilities with Other Materials

Strong oxidizing agents, strong acids, strong bases, amines, ammonia, ethylene oxide, isocyanates, acetaldehyde, chlorine, phosgene, Attacks some forms of plastics, rubbers, and coatings, aluminum at high temperatures.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information

RTECS#:

CAS# 67-63-0: NT8050000  
CAS# 7732-18-5: ZC0110000  
LD50/LC50:

RTECS: CAS# 67-63-0: Draize test, rabbit, eye: 100 mg Severe; Draize test, rabbit, eye: 10 mg Moderate; Draize test, rabbit, eye: 100 mg/24H Moderate; Draize test, rabbit, skin: 500 mg Mild; Inhalation, mouse: LC50 = 53000 mg/m3; Inhalation, rat: LC50 = 16000 ppm/8H; Inhalation, rat: LC50 = 72600 mg/m3; Oral, mouse: LD50 = 3600 mg/kg; Oral, mouse: LD50 = 3600 mg/kg; Oral, rabbit: LD50 = 6410 mg/kg; Oral, rat: LD50 = 5045 mg/kg; Oral, rat: LD50 = 5000 mg/kg; Skin, rabbit: LD50 = 12800 mg/kg; .

RTECS: CAS# 7732-18-5: Oral, rat: LD50 = >90 mL/kg; .

Carcinogenicity:

isopropyl alcohol -  
IARC: Group 3 (not classifiable)  
Water -

Not listed as a carcinogen by ACGIH, IARC, NTP, or CA Prop 65.

Epidemiology:

No information found

Teratogenicity:

A rat & rabbit developmental toxicity study showed no teratogenic effects at doses that were clearly maternally toxic. In a separate rat study, no evidence of developmental neurotoxicity was associated with gestational exposures to IPA up to 1200 mg/kg/d.

Reproductive:

See actual entry in RTECS for complete information.

Neurotoxicity:

In rats exposed to isopropanol by inhalation, acute neurotoxicity was noted at 1 and 6 hours at 5000 ppm, but only minimal effects were seen at 1500 ppm and the animals recovered within 5 hours. No toxicity was noted at 500 ppm.

Mutagenicity:

See actual entry in RTECS for complete information.

Other:

See actual entry in RTECS for complete information.

Section 12 - Ecological Information

Ecotoxicity:

Fish: Fathead Minnow: >1000 ppm; 96h; LC50Daphnia: >1000 ppm; 96h; LC50Fish: Gold orfe: 8970-9280 ppm; 48h; LC50

Section 13 - Disposal Considerations

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste.

US EPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

RCRA P-Series: None listed.

RCRA U-Series: None listed.

Section 14 - Transport Information

US DOT

Shipping Name: ISOPROPANOL  
Hazard Class: 3  
UN Number: UN1219  
Packing Group: II

Canada

Shipping Name: ISOPROPANOL  
Hazard Class: 3  
UN Number: UN1219  
Packing Group: II

Section 15 - Regulatory Information

US Federal

TSCA

CAS# 67-63-0 is listed on the TSCA Inventory.

CAS# 7732-18-5 is listed on the TSCA Inventory.

Health & Safety Reporting List

CAS# 67-63-0: Effective 12/15/86, Sunset 12/15/96

Chemical Test Rules

CAS# 67-63-0: 40 CFR 799.2325

Section 12b

None of the chemicals are listed under TSCA Section 12b.

TSCA Significant New Use Rule

None of the chemicals in this material have a SNUR under TSCA.

CERCLA Hazardous Substances and corresponding RQS

None of the chemicals in this material have an RQ.

SARA Section 302 Extremely Hazardous Substances

None of the chemicals in this product have a TPO.

SARA Codes

CAS # 67-63-0: acute, chronic, flammable.

Section 313

This material contains Isopropyl alcohol (CAS# 67-63-0, 70%) which is

subject to the reporting requirements of Section 313 of SARA Title

III and 40 CFR Part 372.

Clean Air Act:

This material does not contain any hazardous air pollutants.

This material does not contain any Class 1 Ozone Depletors.

This material does not contain any Class 2 Ozone Depletors.

Clean Water Act:

None of the chemicals in this product are listed as Hazardous

Substances under the CWA.

None of the chemicals in this product are listed as Priority

Pollutants under the CWA.

None of the chemicals in this product are listed as Toxic Pollutants

under the CWA.

OSHA:

STATE

Isopropyl alcohol can be found on the following state right to know

lists: California, New Jersey, Pennsylvania, Minnesota,

Massachusetts.

Water is not present on state lists from CA, PA, MN, MA, FL, or NJ.

California Prop 65

California No Significant Risk Level:

None of the chemicals in this product are listed.

European/International Regulations

European Labeling in Accordance with EC Directives

Hazard Symbols: XI F

Risk Phrases:

R 11 Highly flammable.  
R 36 Irritating to eyes.  
R 67 Vapours may cause drowsiness and dizziness.

Safety Phrases:

S 7 Keep container tightly closed.  
S 16 Keep away from sources of ignition - No smoking.  
S 24/25 Avoid contact with skin and eyes.  
S 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

WGK (Water Danger/Protection)

CAS# 67-63-0: 1  
CAS# 7732-18-5: Not available

Canada

CAS# 67-63-0 is listed on Canada's DSL List

CAS# 7732-18-5 is listed on Canada's DSL List

Canadian WHMIS Classifications: B2, D2B

This product has been classified in accordance with the hazard

criteria of the Controlled Products Regulations and the MSDS

contains all of the information required by those regulations.

CAS# 67-63-0 is listed on Canada's Ingredient Disclosure List

CAS# 7732-18-5 is not listed on Canada's Ingredient

Disclosure List.

Section 16 - Other Information

MSDS Creation Date:

7/27/1999

Revision #11 Date

2/18/2008

The information above is believed to be accurate and represents the

best information currently available to us. However, we make no

warranty of merchantability or any other warranty, express or

implied, with respect to such information, and we assume no liability

resulting from its use. Users should make their own investigations to

RECEIVED DEC 05 2003

DATE: 11/28/08 ACCT: 888235001 PAGE: 5  
INDEX: D83314739 CAT NO: A4591 PO NBR: CREDIT CARD

determine the suitability of the information for their particular purposes. In no event shall the company be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential, or exemplary damages howsoever arising, even if the company has been advised of the possibility of such damages.

---