MATERIAL SAFETY DATA SHEET

MANUFACTURER OR DISTRIBUTOR: M. Grumbacher, Inc.

Three Englehard Dr.

Cranbury NJ 08512

INFORMATION TELEPHONE NUMBER: 609-655-8282

EMERGENCY TELEPHONE NUMBER: 800-346-3278

----- SECTION I - PRODUCT IDENTIFICATION ------

PRODUCT NAME: JAPAN DRIER PRODUCT NO. 557

PRODUCT SIZES: 74 ML

PRODUCT CLASS: OIL LIQUID PAINTING MEDIUM

------ SECTION II - HAZARDOUS INGREDIENTS ---------

PEL/TLV MAX CAS# INGREDIENT (MG/M3) %WEIGHT NTP IARC PETROLEUM DISTILLATES N/A 65.8000 N N

----- SECTION III - PHYSICAL AND CHEMICAL CHARACTERISTICS ------

BOILING POINT: N/A N/A MELTING POINT:

V OR PRESSURE: N/A

SPECIFIC VAPOR DENSITY (AIR=1): N/A SPECIFIC GRAVITY: N/A SOLUBILITY IN WATER: N/A REACTIVITY IN WATER: NON-REACTIVE

APPEARANCE AND ODOR: CLEAR DARK YELLOW LIQUID WITH PETROLEUM ODOR.

----- SECTION IV - FIRE AND EXPLOSION INFORMATION ------

FLASH POINT (METHOD): 120°F TCC AUTOIGNITION TEMPERATURE: N/A EXPLOSION LIMITS IN AIR (% BY VOLUME): NOT EXPLOSIVE EXTINGUISHING MEDIA: NO SPECIAL MEDIA REQUIRED FIRE FIGHTING PROCEDURES: NO SPECIAL FIRE FIGHTING PROCEDURES REQUIRED UNUSUAL FIRE & EXPLOSION HAZARDS: COMBUSTIBLE.

HAZARDOUS POLYMERIZATION PRDUCTS: NONE STABILITY: STABLE CONDITIONS TO AVOID: NONE IMCOMPATIBILITY (MATERIALS TO AVOID): NONE HAZARDOUS DECOMPOSITION PRODUCTS: NONE

COMPANY: M. Grumbacher, Inc. PRODUCT: 557 ERAND NAME: JAPAN DRIER PERMISSIBLE EXPOSURE LEVEL: SEE SECTION II FOR COMPONENT PEL/TLVs PRIMARY ROUTES OF ENTRY: INHALATION, INGESTION, EYE, SKIN EFFECTS AND SYMPTOMS OF ACUTE EXPOSURE: EXPOSURE MAY RESULT IN IRRITATION OF THE EYES OR CHEST. MAY BE HARMFUL BY BREATHING VAPORS. EXPOSURE MAY RESULT IN NAUSEA, HEADACHE, CONFUSION OR INSTABILITY. EFFECTS AND SYMPTOMS OF CHRONIC EXPOSURE: NONE EXPECTED CARCINGEN LISTING: NTP: NO IARC: NO OSHA: NO SEE SECTION II FOR COMPONENTS AFFECTED MEDICAL CONDITIONS USUALLY AGGRAVATED BY OVER EXPOSURE TO THIS PRODUCT: NONE FIRST AID MEASURES: If symptoms occur, move to fresh air. If symptoms persist, see a physician. ----- SECTION VII - SPILL OR LEAK PROCEDURES --------PRECAUTIONS TO BE TAKEN DURING STORAGE AND HANDLING: Do not store or use near heat or flame. KEEP OUT OF REACH OF CHILDREN. STEPS TO BE TAKEN IN CASE A MATERIAL IS SPILLED: NO SPECIAL SPILL CEDURES REQUIRED. WASTE DISPOSAL METHOD: DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. ----- SECTION VIII - PROTECTIVE EQUIPMENT/CONTROL MEASURES ------RESPIRATORY PROTECTION AND SPECIAL VENTILATION REQUIREMENTS: Use exhaust ' fan to remove vapors and assure adequate cross ventilation. OTHER PROTECTIVE EQUIPMENT (GLOVES, GOGGLES, ETC): NONE REQUIRED

MORK/HYGIENE PRACTICES: Avoid prolonged contact with skin.

Form Completed by: Woodhall Stopford, MD, MSPH

last Updated: 04/07/92