

MATERIAL SAFETY DATA SHEET

MANUFACTURER'S NAME: Reichhold Chemicals, Inc.
 ADDRESS: 407 South Pace Blvd.
 Pensacola, Florida 32596-1433

NPCA Hazardous Materials
 Identification System

EMERGENCY/INFORMATION TELEPHONE NUMBER:
 DATE OF PREPARATION: December 1988 (supercedes May 1986) *JAN 25 1989*

Health	0
Flammability	1
Reactivity	0
Maximum Personal Protection	

SECTION I: PRODUCT IDENTIFICATION	
PRODUCT NAME:	K.V.O. LINSEED OIL
PRODUCT CODE NUMBER:	21322
PRODUCT CLASS:	Refined linseed oil

SECTION II: HAZARDOUS INGREDIENTS						
INGREDIENT	%	OCCUPATIONAL EXPOSURE LIMITS			LEL %	VAPOR PRESSURE
		ACGIH TLV TWA	ACGIH TLV STEL	OSHA PEL		
K.V.O. Linseed Oil (CAS No. 8001-26-1*) is not a hazardous material under current Department of Labor definitions.						

SECTION III: PHYSICAL DATA

BOILING RANGE: not applicable

VAPOR DENSITY: not applicable

HEAVIER THAN AIR

LIGHTER THAN AIR.

EVAPORATION RATE: not applicable

FASTER THAN ETHER

SLOWER THAN ETHER.

PERCENT VOLATILE BY VOLUME:

0%

WEIGHT PER GALLON: 7.7 lbs

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

FLAMMABILITY CLASSIFICATION:

OSHA - Combustible Liquid - Class IIIB
DOT - Not Restricted

FLASH POINT:

greater than 200°F (Closed Cup)

EXTINGUISHING MEDIA:

Water spray, dry chemical, foam, carbon dioxide.

UNUSUAL FIRE AND EXPLOSION HAZARDS: See Section VIII.

SPECIAL FIRE FIGHTING PROCEDURES: Water or foam may cause frothing if directed into containers of burning liquid. Fire fighters should wear protective clothing. Use water to keep fire-exposed containers cool.

SECTION V: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE:

ACUTE: None observed by inhalation.

CHRONIC: None reported.

OTHER HEALTH EFFECTS:

None reported.

EMERGENCY FIRST AID PROCEDURES: In eyes - flush with clean water for 15 minutes.
On skin - wash with soap and water and observe routine hygienic practices.

SECTION VI: REACTIVITY DATA**STABILITY:**

UNSTABLE

STABLE

HAZARDOUS POLYMERIZATION:

MAY OCCUR

WILL NOT OCCUR

HAZARDOUS DECOMPOSITION PRODUCTS: Usual products of combustion - carbon monoxide, carbon dioxide and possibly acrolein.

CONDITIONS TO AVOID:

Not applicable.

INCOMPATIBILITY (MATERIALS TO AVOID): Avoid contact with strong oxidizing agents.

SECTION VII: SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:**

Small spills may be picked up with absorbent material and transferred to containers. Large spills may be scooped up and put into containers or salvaged. See disposal precautions below.

WASTE DISPOSAL METHOD:

See other precautions below. Carefully incinerate or use secure landfill in accordance with local, state and federal regulations.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

RESPIRATORY PROTECTION: Not normally needed.

VENTILATION: Not applicable.

PROTECTIVE GLOVES: Neoprene rubber gloves

EYE PROTECTION: Goggles or side-shield spectacles

OTHER PROTECTIVE EQUIPMENT: Eye wash station should be available.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store away from high temperatures and flames. Do not breathe spray mist.

OTHER PRECAUTIONS: Avoid spontaneous combustion of contaminated rags and other easily ignitable accumulations (such as spray booth residues) by immediate immersion in water. Emptied containers may retain residues of product. Do not cut, puncture or weld on or near the container.

REICHHOLD BELIEVES THAT THE INFORMATION CONTAINED IN THIS MSDS IS CORRECT AS OF THIS DATE. HOWEVER, BECAUSE THE MATERIAL MAY BE USED UNDER CONDITIONS OVER WHICH REICHHOLD HAS NO CONTROL OR IN WAYS WE CANNOT ANTICIPATE, WE GIVE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ACCURACY OF THE INFORMATION AND ASSUME NO RESPONSIBILITY FOR ANY DAMAGE TO PERSON, PROPERTY OR BUSINESS ARISING FROM SUCH USE. MOREOVER, IT IS THE RESPONSIBILITY OF THE PURCHASER OR USER OF THIS MATERIAL TO ENSURE THAT IT IS PROPERLY AND SAFELY USED.