



The Clorox Company
7200 Johnson Drive
Pleasanton, California 94566
Tel. (415) 847-6100

Material Safety Data Sheet

CLOROX-HMIS	
HEALTH	2*
FLAMMABILITY	1
REACTIVITY	0
Personal Protection	E

I Chemical Identification														
NAME: KINGSFORD BRIQUETS		CAS no. N/A												
DESCRIPTION: BLACK SOLID CUBES, OORLESS		RTECS no. N/A												
Other Designations	Manufacturer	Emergency Procedure												
Charcoal Briquets	The Kingsford Company 1221 Broadway Oakland, CA 94612	Notify your Supervisor Call your local poison control center or Rocky Mountain Poison Center (303) 573-1014												
II Health Hazard Data		III Hazardous Ingredients												
<p>Dust may irritate eyes. Possible sensitizer.</p> <p>*Repeated (chronic) or prolonged overexposure to the dust may cause coughing, shortness of breath and occupational lung disease. No medical conditions are known to be aggravated by exposure to this product. Preliminary studies have linked wood dust to nasal cancer in furniture workers. Carpenters, sawmill and lumber mill workers do not appear to have this increased risk. Due to the packaging and probable use conditions the likelihood of any chronic effects are low. FIRST AID: EYE CONTACT: Flush eyes immediately with plenty of water. SKIN CONTACT: Wash exposed area with soap and water. INGESTION: Not an apparent hazard. INHALATION: If breathing problems develop, remove to fresh air.</p>		<table border="1"> <thead> <tr> <th>Ingredient</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Char dust</td> <td>varies</td> <td>*2 mg/m³ (Respirable dust)</td> </tr> <tr> <td>CAS# 16291-96-6</td> <td></td> <td></td> </tr> <tr> <td>Sawdust</td> <td>0.5-5%</td> <td>1 mg/m³ TLV-TWA</td> </tr> </tbody> </table> <p>*The Clorox Company recommends this Worker Exposure Limit based on the coal dust TLV established by ACGIH.</p> <p>None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen lists.</p> <p>Char dust is produced as a result of briquet breakage. The concentration will vary depending on the amount of breakage.</p>	Ingredient	Concentration	Worker Exposure Limit	Char dust	varies	*2 mg/m ³ (Respirable dust)	CAS# 16291-96-6			Sawdust	0.5-5%	1 mg/m ³ TLV-TWA
Ingredient	Concentration	Worker Exposure Limit												
Char dust	varies	*2 mg/m ³ (Respirable dust)												
CAS# 16291-96-6														
Sawdust	0.5-5%	1 mg/m ³ TLV-TWA												
IV Special Protection Information		V Special Precautions												
<p>Use adequate ventilation when burning this material.</p> <p>Hygienic Practices: In an occupational exposure wear safety glasses, gloves and a dust respirator.</p> <p>Engineering Controls: Use general ventilation to minimize exposure to dust.</p> <p>Work Practices: Avoid eye contact and inhalation of dust.</p>		<p>WARNING: Do not use for indoor heating or cooking unless ventilation is provided for exhausting fumes to outside. Toxic fumes may accumulate. Store away from open flames.</p>												
VI Spill or Leak Procedures		VII Reactivity Data												
<p>To avoid spillage and for better results, keep container closed when not in use.</p>		<p>Stable under normal use and storage conditions. Incomplete combustion may form carbon monoxide.</p>												
VIII Fire and Explosion Data		IX Physical Data												
<p>This product is a mixture of combustible materials. To extinguish fire use water spray, foam, dry chemical or carbon dioxide.</p>		<p>Melting Point----- > 3500°C Solubility in Water-----Insoluble Color/Form-----Black solid cubes</p>												