

AUG 08 1994

MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE 1  
MSDS NO. 1679

SECTION 1. MANUFACTURERS INFORMATION

MANUFACTURERS NAME  
W.M. BARR & COMPANY, INC.

ADDRESS  
2105 Channel Ave.  
Memphis, TN 38113

EMERGENCY TELEPHONE  
901-775-0100

EMERGENCY CONTACT  
W. M. BARR Technical Services

See Section 6 for additional Emergency Information

REVISED BY  
W. M. BARR MSDS Committee 7/20/1992

SECTION 2. PRODUCT INFORMATION

INVENTORY ITEM # GTP28

CHEMICAL FORMULA 1679

PRODUCT NAME KLEAN-STRIP TURPATINE

SECTION 3. INGREDIENTS/REGULATORY INFORMATION

INGREDIENT DESCRIPTION	PERCENT BY WEIGHT		CAS#	CARCINOGENICITY			
				NTP	ACGIH	OSHA	IARC
TERPENE THINNER	25-	30	65996-99-8	N	N	N	N
MINERAL SPIRITS	20-	25	N/A	N	N	N	N
**** ABOVE INGREDIENT CONSIST OF THE FOLLOWING ****							
STODDARD SOLVENT, TYPE I	95-	100	8052-41-3	N	N	N	N
AROMATIC PETROLEUM DISTILLATE	50-	55	64742-95-6	N	N	N	N
**** ABOVE INGREDIENT CONSIST OF THE FOLLOWING ****							
CUMENE	1-	5	98-82-8	N	N	N	N
TRIMETHYLBENZENE	30-	40	25551-13-7	N	N	N	N
XYLENE	5-	10	1330-20-7	N	N	N	N
HIGH FLASH NAPHTHA	50-	55	64742-95-6	N	N	N	N

EXPOSURE LIMITS/REGULATORY INFORMATION

INGREDIENT DESCRIPTION	REG.						
	AGCY.	U/M	TWA	STEL	CEIL	SKIN	PEL
TERPENE THINNER	ACGIH OSHA	PPM PPM	N/E N/E	N/E N/E	N/E N/E	N N	N/E N/E
PROPRIETARY MIXTURE OF TURPENE ISOMERS.							
MINERAL SPIRITS	ACGIH OSHA	PPM PPM	N/E N/E	N/E N/E	N/E N/E	N N	N/E N/E
EXXON RECOMMENDS AN OCCUPATIONAL EXPOSURE LIMIT OF 100 PPM TOTAL HYDROCARBON BASED ON COMPOSITION.							
STODDARD SOLVENT, TYPE I	ACGIH OSHA	PPM PPM	100.0 100.0	N/E N/E	N/E N/E	N N	N/E 500.0
AROMATIC PETROLEUM DISTILLATE	ACGIH OSHA	PPM PPM	N/E N/E	N/E N/E	N/E N/E	N N	N/E 100.0
OSHA PEL AS PROVIDED BY SUPPLIER.							
CUMENE	ACGIH OSHA	PPM PPM	50.0 50.0	N/E N/E	N/E N/E	Y Y	N/E 50.0

MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE  
MSDS NO. 1679<sup>2</sup>

SECTION 3. INGREDIENTS/REGULATORY INFORMATION  
(CONTINUED)

TRIMETHYLBENZENE	ACGIH PPM	25.0	N/E	N/E	N	N/E
	OSHA PPM	25.0	N/E	N/E	N	N/E
MAY CONTAIN 50% PSEUDOCUMENE, CAS# 95-63-6 AND 22.5% 1,3,5-TRIMETHYLENEBENZENE, CAS# 108-67-8.						
XYLENE	ACGIH PPM	100.0	150.0	N/E	N	N/E
	OSHA PPM	100.0	150.0	N/E	N	100.0
HIGH FLASH NAPHTHA	ACGIH PPM	N/E	N/E	N/E	N	N/E
	OSHA PPM	N/E	N/E	N/E	N	N/E

THE SUPPLIER RECOMMENDS AN EXPOSURE GUIDELINE OF 50 PPM, TLV.

The time weighted average (TWA) value described herein is a threshold limit value (TLV) as established by ACGIH. The permissible exposure limit (PEL) is a value established by OSHA.

SECTION 4. OTHER REGULATORY INFORMATION

CALIFORNIA (PROPOSITION #65)

Ingredients in this product are not listed on California's Prop 65 list: "Chemicals Known to the State to Cause Cancer or Reproductive Toxicity."

SEC. 313 SUPPLIER NOTIFICATION

The following information must be included in all MSDS that are copied and distributed for this material.

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40CFR 372):

INGREDIENT DESCRIPTION	PERCENT BY WEIGHT (UPPER LIMIT)	CAS#
CUMENE	2	98-82-8
1,2,4-TRIMETHYLBENZENE	1	95-63-6
XYLENE	5	1330-20-7

HAZARD COMMUNICATION STANDARD

This document is prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200). This MSDS contains thirteen (13) sections.

\*\*\*\*\*  
The following effects and/or symptoms are not expected to be experienced by persons who use this product properly and according to ALL instructions, precautions, and warnings; however, should the product user experience ANY questionable effects or symptoms, the product user should immediately seek medical attention.

SECTION 5. HAZARDS IDENTIFICATION

INHALATION ACUTE EXPOSURE EFFECTS

Vapor harmful. May cause dizziness, headache, watering of eyes, eye irritation, weakness, drowsiness, nausea, loss of coordination, irritation of respiratory tract, muscle twitches, depression of central nervous system, and fatigue. Severe overexposure may cause convulsions, unconsciousness, and death. Intentional misuse of this product by deliberately concentrating and inhaling can be harmful or fatal.

## MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE  
MSDS NO. 1679<sup>3</sup>-----  
SECTION 5. HAZARDS IDENTIFICATION  
(CONTINUED)  
-----**SKIN CONTACT ACUTE EXPOSURE EFFECTS**

May cause irritation, drying of skin, redness, burning, and cracking.

**EYE CONTACT ACUTE EXPOSURE EFFECTS**

May cause irritation and conjunctivitis of eyes.

**INGESTION ACUTE EXPOSURE EFFECTS**

Harmful or fatal if swallowed. May cause dizziness, nausea, headache, weakness, drowsiness, vomiting, irritation of digestive tract, loss of coordination, fatigue, muscle twitches, diarrhea, gastrointestinal irritation, unconsciousness, convulsions, and death.

**CHRONIC EXPOSURE EFFECTS**

Reports have associated repeated and prolonged overexposure to solvents with neurological and other physiological damage. May cause anemia, skin irritation, bone marrow damage, liver damage, and jaundice.

**MEDICAL CONDITIONS AGGRAVATED**

None known.

**PRIMARY ROUTE OF EXPOSURE**

Inhalation, ingestion, and dermal.

-----  
SECTION 6. FIRST AID MEASURES  
-----**INHALATION**

If user experiences breathing difficulty, move to air free of vapors. Administer oxygen or artificial respiration until medical assistance can be rendered.

**SKIN CONTACT**

Wash with soap and water.

**EYE CONTACT**

Flush with large quantities of water for at least 15 minutes. If irritation from contact persists, get medical attention.

**INGESTION**

DO NOT induce vomiting. Call your poison control center, hospital emergency room, or physician immediately.

**NOTE TO PHYSICIAN**This formula is registered with POISINDEX.  
Call your local poison control center for further information.-----  
SECTION 7. FIRE FIGHTING MEASURES  
-----

HAZARD RATING SOURCE	HMIS	NFPA
HEALTH	2	1
FLAMMABILITY	2	2
REACTIVITY	0	0
OTHER	G	NA

**FLASH METHOD**  
TCC

## MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE  
MSDS NO. 1679<sup>4</sup>-----  
SECTION 7. FIRE FIGHTING MEASURES  
(CONTINUED)  
-----FLASH POINT  
104.00 F 40.00 CLOWER EXPLOSION LIMIT  
1.00GENERAL COMMENTS  
OSHA FLAMMABILITY: Class IIEXTINGUISHING METHOD  
Use carbon dioxide, dry powder, or foam.FIRE FIGHTING PROCEDURES  
Self-contained respiratory protection should be provided for fire fighters fighting fires in buildings or confined areas. Storage containers exposed to fire should be kept cool with water spray to prevent pressure build-up. Stay away from heads of containers that have been exposed to intense heat or flame.FIRE AND EXPLOSION HAZARDS  
CAUTION! COMBUSTIBLE. KEEP AWAY FROM HEAT, SPARKS, FLAME AND ALL OTHER SOURCES OF IGNITION.-----  
SECTION 8. ACCIDENTAL RELEASE MEASURES  
-----CLEAN-UP  
Keep unnecessary people away; isolate hazard area and deny entry. Stay upwind, out of low areas, and ventilate closed spaces before entering. Shut off ignition sources; keep flares, smoking or flames out of hazard area. SMALL SPILLS: take up liquid with sand, earth or other noncombustible absorbent material and place in a plastic container where applicable. LARGE SPILLS: dike far ahead of spill for later disposal.

For transportation related spills contact Chemtrec at 1-800-424-9300 for emergency assistance.

WASTE DISPOSAL  
Dispose in accordance with applicable local, state and federal regulations.-----  
SECTION 9. HANDLING/STORAGE/TRANSPORTATION  
-----STORAGE  
Keep container tightly closed when not in use. Store in a cool, dry place. Do not store near flames or at elevated temperatures.HANDLING  
Read carefully all cautions and directions on product label before use. Since empty container retains residue, follow all label warnings even after container is empty. Dispose of empty container according to all regulations. Do not reuse this container.TRANSPORTATION  
For D.O.T. information, contact W.M. Barr Technical Service Department.

## MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE 5  
MSDS NO. 1679-----  
SECTION 10. EXPOSURE CONTROLS/PERSONAL PROTECTION  
-----**VENTILATION PROTECTION**

Use only with adequate ventilation to prevent build-up of vapors. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is inadequate. Leave area immediately.

**RESPIRATORY PROTECTION**

For OSHA controlled work place and other regular users - Use only with adequate ventilation under engineered air control systems designed to prevent exceeding appropriate TLV. For occasional use, where engineered air control is not feasible, use properly maintained and properly fitted NIOSH approved respirator for organic solvent vapors. A dust mask does not provide protection against vapors.

**SKIN PROTECTION**

Wear impermeable gloves. Gloves contaminated with product should be discarded. Promptly remove clothing that becomes soiled with product.

**EYE PROTECTION**

Safety glasses, chemical goggles or face shields are recommended to safeguard against potential eye contact, irritation, or injury. Contact lenses should not be worn while working with chemicals.

**OTHER PROTECTION**

Various application methods can dictate use of additional protective safety equipment, such as impermeable aprons, etc., to minimize exposure. A source of clean water should be available in the work area for flushing eyes and skin. Do not eat, drink, or smoke in the work area. Wash hands thoroughly after use. Before reuse, thoroughly clean any clothing or protective equipment that has been contaminated by prior use. Discard any clothing or other protective equipment that cannot be decontaminated, such as gloves or shoes.

-----  
SECTION 11. PHYSICAL AND CHEMICAL PROPERTIES  
-----

<b>VOLATILE %</b> 100.000 by weight	<b>BOILING POINT</b> GT 310.0 F 154.44 C <b>BOILING RANGE:</b> 310 F - 405 F
<b>VAPOR DENSITY (Air = 1.0)</b> Heavier than air	<b>EVAPORATION RATE</b> Slower than ether
<b>BULK DENSITY</b> 7.026 lbs/gal at 75 F	<b>PHOTOCHEMICALLY REACTIVE</b> YES

**MAX V.O.C.**  
862 grams per liter (excluding exempt solvents & water)

**MAX VAPOR PRESSURE**  
(of the V.O.C.) 2mm Hg at 20 degrees C

## MATERIAL SAFETY DATA SHEET

DATE PRINTED:  
00000000

ATTN: RISK MANAGEMENT

PAGE  
MSDS NO. 1679<sup>6</sup>-----  
SECTION 12. STABILITY AND REACTIVITY  
-----

## INCOMPATIBILITIES

Incompatible with strong oxidizing agents.

## DECOMPOSITION

Decomposition may produce carbon monoxide and carbon dioxide.

## POLYMERIZATION

Will not occur.

## STABILITY

Stable.

-----  
SECTION 13. ADDITIONAL INFORMATION  
-----

## IMPORTANT NOTE

The information contained herein is presented in good faith and believed to be accurate as of the effective date shown above. This information is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees. Any use of this data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

## LEGEND:

PPM = parts per million

MG/M3 = milligrams per cubic meter

N/E or NE = none established

GT = greater than

N/A or NA = not applicable

TCC = tag closed cup

TOC = tag open cup

PMCC = Pensky-Martens closed cup

IDLH = Immediately Dangerous to Life and Health

\*\*\*END OF MSDS\*\*\*