

MATERIAL SAFETY DATA SHEET
EASTMAN KODAK COMPANY

Date of Revision: 6/14/89

Kodak Accession Number: 427909

PRODUCT INFORMATION

Product Name: KODAK HC-110 Developer

Formula: Aqueous Mixture

Kodak Catalog Number(s): CAT 140 8962 - To Make 3 1/2 Gallons; CAT 140 8988
- To Make 2 Gallons

Solution Number: 4987

Kodak Hazard Rating Codes: R: 1 S: 2 F: 1 C: 0

Manufacturer/Supplier:

Eastman Kodak Company
343 State Street
Rochester, New York 14650
USA

For Emergency Information: (716) 722-5151

For other purposes, call the Marketing and Distribution Center in your area.

COMPONENT INFORMATION

	Weight Percent	CAS Number	Accession Number
Water	60-65	7732-18-5	035290
Diethanolamine-sulfur dioxide complex	40-45	63149-47-3	931981
*2-Aminoethanol	5-10	141-43-5	901597
Diethylene glycol	5-10	111-46-6	902041
*Hydroquinone**	8	123-31-9	900356

*Principal Hazardous Component(s)

**Chemical subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

PHYSICAL DATA

Appearance and Odor: Brown solution, amine odor
Boiling Point: GT 100 C (GT 212 F)
Vapor Pressure: ca. 11 mmHg @ 20 C
Evaporation Rate (n-butyl acetate = 1): Not Available
Vapor Density (Air = 1): ca. 2.1
Volatile Fraction by Weight: ca. 70 %
Specific Gravity (H2O = 1): 1.249
pH: approx 9.0
Solubility in Water (by Weight): Complete

GT = Greater than; LT = Less than

C-0070.100I
84-0346

=====
 FIRE AND EXPLOSION HAZARD
 =====

FLASH POINT: None

EXTINGUISHING MEDIA: Water spray, dry chemical, Carbon dioxide, "Alcohol" foam

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Fire or excessive heat may cause production of hazardous decomposition products.

 =====
 REACTIVITY DATA
 =====

STABILITY: Stable

INCOMPATIBILITY: Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: Combustion will produce carbon dioxide and probably carbon monoxide. Ammonia and oxides of sulfur and nitrogen may also be present.

CONDITIONS CONTRIBUTING TO HAZARDOUS POLYMERIZATION: Will not occur.

 =====
 TOXICOLOGICAL PROPERTIES
 =====

EXPOSURE LIMITS:

Component: Hydroquinone

ACGIH TLV: 2mg/m³ - TWA (ACGIH 1989 - 1990)

OSHA PEL: 2mg/m³ - TWA

Component: 2-aminoethanol

ACGIH TLV: 3 ppm - TWA; 6 ppm - STEL (ACGIH 1989 - 1990)

OSHA PEL: 3 ppm - TWA; 6 ppm - STEL

EXPOSURE EFFECTS:

Inhalation: Vapor may cause upper respiratory tract irritation

Eyes: May cause irritation. Vapor may cause eye irritation.

Skin: Prolonged or repeated skin contact may cause skin irritation. Repeated skin contact may result in an allergic skin reaction.

Ingestion: May be harmful if swallowed.

TOXICITY DATA:

TEST	SPECIES	RESULT (1)	CLASSIFICATION (2)
Oral LD50	Rat	GT 3200 mg/kg	Slightly toxic
Skin Irritation	Guinea Pig	Strong irritation	
Eye Irritation	Rabbit	Moderate irritation	
Skin Absorption	Guinea Pig	No evidence at 20 mL/kg	

 =====
 PROTECTION AND PREVENTIVE MEASURES
 =====

VENTILATION: Good general ventilation should be sufficient.

SKIN AND EYE PROTECTION: Protective gloves should be worn. Safety glasses with side shields should be worn. The routine use of a non-alkaline (acid) type of hand cleaner will help minimize the possibility of allergic skin reaction.

STORAGE AND DISPOSAL

SPECIAL STORAGE AND HANDLING PRECAUTIONS: Keep from contact with oxidizing materials.

SPILL, LEAK, AND DISPOSAL PROCEDURES: Flush material to acid-free sewer with large amounts of water. Discharge, treatment, or disposal may be subject to federal, state, or local laws.

FIRST AID

Inhalation: Remove to fresh air.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes and get medical attention.

Skin: Flush skin with plenty of soap and water.

Ingestion: If swallowed, induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

ENVIRONMENTAL EFFECTS DATA

This chemical formulation has not been tested for environmental effects.

TRANSPORTATION

For Transportation information regarding this product, please phone the Eastman Kodak Distribution Center nearest you: Rochester, NY (716) 588-9293; Oak Brook, IL (312) 954-6000; Chamblee, GA (404) 455-0123; Dallas, TX (214) 241-1611; Whittier, CA (213) 693-5222; Honolulu, HI (808) 833-1661.

REFERENCES

1. Unpublished data, Health and Environment Laboratories, Eastman Kodak Company, Rochester, NY.
2. Hodge, H.C. and Sterner, J.H., American Industrial Hygiene Association Quarterly, 10, 93(1949).

=====
PREPARATION INFORMATION
=====

Health and Environment Laboratories
Eastman Kodak Company
Rochester, New York 14652-3615
=====

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of the suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers.
=====

C-0070.100I
84-0346