



Innovative Signs & Safety Solutions

Home | Order Status | Register | View

Search Item Number

GO

1-800-4

Regulation Resource Site

On-Line Catalog | Site Home | MSDS | CFR | Safety Resources

MSDS Database

Search Resource Site All

GO

Most Popular in Hazard

- ▶ Software - Ma
- ▶ RTK Label Blar
- ▶ Diamond Pane
- ▶ Do-It-Yourself
- ▶ Panel Characte

Material Safety Data Sheet

Name KRYLON 1306 WORKABLE FIXATIF
Company SPRAYON PRODUCTS DIV SHERWIN-

MSDS bxqdw
FSC 8010

MSDS Safety Information

FSC: 8010
 NIIN: 00-401-0421
 MSDS Date: 08/20/1994
 MSDS Num: BXQDW
 Product ID: KRYLON 1306 WORKABLE FIXATIF
 MFN: 01
 Responsible Party
 Cage: 09800
 Name: SPRAYON PRODUCTS DIV SHERWIN-WILLIAMS CO
 Address: 31500 SOLON ROAD
 City: SOLON OH 44139-5000
 Info Phone Number: 800-777-2966
 Emergency Phone Number: 216-292-7400
 Review Ind: Y
 Published: Y

Fast F

- ▶ Confined Spac
- ▶ Lockout Check
- ▶ CFR - 1910 L
Fire Protection
- ▶ Asbestos Fact
- ▶ Traffic Signs
- ▶ Parking Signs
- ▶ Industrial Sign
- ▶ Tags

Contractor Summary

Cage: 26290
 Name: SAX ARTS ANDamp; CRAFTS SUB OF BEATRICE COMPANIES INC
 Address: 2405 S CALHOUN RD
 City: NEW BERLIN WI 53151
 Phone: 262-784-6880
 Cage: 09800
 Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.
 Address: 26300 FARGO AVENUE
 City: BEDFORD HEIGHTS OH 44146
 Phone: 216-292-7400 OR 216-595-8634

Item Description Information

Item Name: VARNISH
 Specification Number: A-A-665
 Type/Grade/Class: NONE
 Type of Container: UNKNOWN

Ingredients

Cas: 74-98-6
 RTECS #: TX2275000
 Name: PROPANE
 % Wt: 15
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 1000 PPM
 ACGIH TLV: ASPHYXIANT; 9495

 Cas: 75-28-5
 RTECS #: TZ4300000
 Name: ISOBUTANE
 % Wt: 15



Other REC Limits: NONE RECOMMENDED
 OSHA PEL: NOT ESTABLISHED
 ACGIH TLV: NOT ESTABLISHED

 Cas: 64742-89-8
 Name: V M ANDamp; P NAPHTHA
 % Wt: 22
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: NOT ESTABLISHED
 ACGIH TLV: NOT ESTABLISHED

 Cas: 64742-47-8
 RTECS #: OA5504000
 Name: PETROLEUM HYDROCARBON,
 % Wt: 2
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 5 MG/M3 (OIL MIST)
 ACGIH TLV: 5 MG/M3 (OIL MIST)

 Cas: 108-88-3
 RTECS #: XS5250000
 Name: TOLUENE (SARA 313) (CERCLA)
 % Wt: 13
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 200 PPM; Z-2
 ACGIH TLV: S, 50 PPM; 9495
 EPA Rpt Qty: 1000 LBS
 DOT Rpt Qty: 1000 LBS

 Cas: 100-41-4
 RTECS #: DA0700000
 Name: ETHYL BENZENE (SARA 313)
 % Wt: 3
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 100 PPM
 ACGIH TLV: 100 PPM/125STEL;9495
 EPA Rpt Qty: 1000 LBS
 DOT Rpt Qty: 1000 LBS

 Cas: 1330-20-7
 RTECS #: ZE2100000
 Name: XYLENES (O-,M-,P- ISOMERS) (SARA 313) (CERCLA)
 % Wt: 13
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 100 PPM
 ACGIH TLV: 100 PPM/150STEL;9495
 EPA Rpt Qty: 1000 LBS
 DOT Rpt Qty: 1000 LBS

 Cas: 67-64-1
 RTECS #: AL3150000
 Name: ACETONE (SARA 313) (CERCLA)
 % Wt: 11
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: 1000 PPM
 ACGIH TLV: 750PPM/1000STEL;9495
 EPA Rpt Qty: 5000 LBS
 DOT Rpt Qty: 5000 LBS

 RTECS #: 9999999VO
 Name: VOLATILE ORGANIC CONTENT = 92%
 % Wt: 92
 Other REC Limits: NONE RECOMMENDED
 OSHA PEL: NOT ESTABLISHED
 ACGIH TLV: NOT ESTABLISHED

Health Hazards Data

LD50 LC50 Mixture: PRODUCT'S LD50 (ORAL RAT) WAS NOT STATED
 Route Of Entry Inds - Inhalation: YES
 Skin: YES

Ingestion: NO
Carcinogenicity Inds - NTP: NO
IARC: NO
OSHA: NO
Effects of Exposure: ACUTE-IRRITATION TO EYES, SKIN ANDamp; REESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTREME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS ANDamp; POSSIBLY DEATH. CHRONIC-PROLONGED ANDamp;/OR REPEATED OVEREXPO SURE MAY CAUSE PERIPHERAL NEUROPATHY, ADVERSE EFFECTS TO LIVER, URINARY, BLOOD FORMING, CVS, CNS OR REPRODUCTIVE SYSTEMS
Explanation Of Carcinogenicity: NO INGREDIENT IN THESE PRODUCTS IS AN NTP, IARC OR OSHA LISTED CARCINOGEN. SOME MAY BE LISTED BY CALIFORNIA.
Signs And Symptions Of Overexposure: HEADACHE, DIZZINESS, NAUSEA ANDamp; LOSS OF COORDINATION ARE INDICATIONS OF EXCESSIVE EXPOSURE TO VAPORS OR SPRAY MIST.
Medical Cond Aggravated By Exposure: NONE GENERALLY RECOGNIZED.
First Aid: IF IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL ATTENTION.
EYE:FLUSH W/WATER FOR 15 MIN. SKIN:WASH W/SOAP ANDamp; WATER. REMOVE CONTAMINATED CLOTHING ANDamp; LAUNDER BEFORE REUSE. INHALED:REMOVE FROM EXPOSURE. A ID OR RESTORE BREATHING AS NEEDED. KEEPWARM ANDamp; QUIET.
SWALLOWED:GET IMMEDIATE MEDICAL ATTENTION.

Handling and Disposal

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. VENTILATE ANDamp; REMOVE W/INERT ABSORBENT.
Neutralizing Agent: MFR GAVE NO INFORMATION ON MSDS.
Waste Disposal Methods: WASTE FROM THESE PRODUCTS MAY BE HAZARDOUS UNDER RCRA (40CFR261) ANDamp; MUST BE TESTEDTO DETERMINE RCRA WASTE NUMBERS. DO NOT INCINERATE. DEPRESSURIZE CONTAINER. DISPOSE OF I/A/W FEDERAL, STATE ANDamp; LOCAL REG ULATIONS REGARDING POLLUTION.
Handling And Storage Precautions: CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ANDgt;120F, HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER. MAY BURST.
Other Precautions: INTENTIONAL MISUES BY DELIBERATEY CONCENTRATING ANDamp; INHALING THE CONTENTS CAN BE HARMFUL OR FATAL. CONTENTS EXTREMELY FLAMMABLE. KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. VAPORS WILL ACCUMULATE ANDamp; MAY IGN ITE EXPLOSIVELY. KEEP FROM CHILDREN.

Fire and Explosion Hazard Information

Flash Point Method: PMCC
Flash Point Text: ANDlt;0F,ANDlt;-18C
Lower Limits: 0.9
Upper Limits: 12.8
Extinguishing Media: CARBON DIOXIDE, DRY CHEMICAL OR FOAM.
Fire Fighting Procedures: USE FULL PROTECTIVE EQUIPMENT INCLUDING SCBA. WATER SPRAY MAY BE INEFFECTIVE, USE IT TO COOL CONTAINERS EXPOSED TO FIRE CONDIONS. USE OF FOG NOZZLES PREFERRED.
Unusual Fire/Explosion Hazard: ISOLATE FROM ALL IGNITION SOURCES. CONTAINERS MAY EXPLODE WHEN EXPOSED TO HEAT. OVEREXPOSURE TO DECOMPOSITION PRODUCTS MAY BE HEALTH HAZARD W/ DELAYED SYMPTOMS.

Control Measures

Respiratory Protection: IF EXPOSURE CANNOT BE CONTROLLED BELOW APPLICABLE LIMITS BY VENTILATION, USE AN ORGANIC VAPOR/PARTICULATE RESPIRATOR APPROVED BY NIOSH/MSHA. FOR SANDING OR ABRADING FILM, WEAR A DUST/MIST RESPIRATOR AP PROVED BY NIOSH/MSHA.
Ventilation: LOCAL EXHAUST PREFFERQABLE. USE MECHANICAL (GENERAL) VENTILATION IF EXPOSURES CAN BE MAINTAINED EXPOSURE LIMITS.
Protective Gloves: NONE REQUIRED FOR NORMAL APPLICATION
Eye Protection: SAFETY SPECTALSES W/SOLID SIDE SHIELDS
Other Protective Equipment: MFR GAVE NO INFORMATION ON MSDS.
Work Hygienic Practices: USE WITH ADEQUATE VENTILATION. AVOID BREATHING VAPOR AND SPRAY MIST. ACOID CONTAT W/SKIN AND EYES. WASH HANDS AFTER USING.
Supplemental Safety and Health: KEEP AREA VENTILATED. DO NOT SMOKE. EXTINGUISH ALL FLAMES, PILOT LIGHTS, HEATERS. TURN OFF STOVES, ELECTRIC APPLIANCES. THESE COATINGS MAY CONTAIN MATERIALS CLASSIFIED AS NUISANCE PARTICULATES WHICH M AY BE PRESENT AT HAZARDOUS LEVELS ONLY DURING SANDING OR ABRADING OF THE DRIED FILM.

Physical/Chemical Properties

HCC: V3
NRC/State LIC No: NONE
M.P/F.P Text: UNKNOWN
Decomp Text: UNKNOWN
Vapor Pres: SEE CAN
Vapor Density: ANDgt;1
Viscosity: UNKNOWN
Evaporation Rate ANDamp; Reference: gt;1 (ETHER)
Appearance and Odor: MFR GAVE NO INFORMATION ON MSDS.
Corrosion Rate: UNKNOWN

Reactivity Data

Stability Indicator: YES
Stability Condition To Avoid: NONE KNOWN.
Materials To Avoid: MFR GAVE NO INFORMATION ON MSDS.
Hazardous Decomposition Products: BY FIRE: CARBON DIOXIDE AND CARBON MONOXIDE.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: WILL NOT OCCUR.

Toxicological Information**Ecological Information****MSDS Transport Information****Regulatory Information****Other Information****Transportation Information**

Responsible Party Cage: 09800
Trans ID NO: 70644
Product ID: KRYLON 1306 WORKABLE FIXATIF
MSDS Prepared Date: 08/20/1994
Review Date: 08/31/1995
MFN: 1
Net Unit Weight: UNKNOWN
Multiple KIT Number: 0
Review IND: Y
Type Of Container: UNKNOWN
Additional Data: IF BEING SHIPPED W/I THE U.S., THIS PRODUCT MAY BE SHIPPED AS
A CONSUMER COMMODITY, ORM-D.

Detail DOT Information

DOT PSN Code: AGC
DOT Proper Shipping Name: AEROSOLS, FLAMMABLE,
DOT PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
Hazard Class: 2.1
UN ID Num: UN1950
Label: FLAMMABLE GAS
Special Provision: N82
Non Bulk Pack: NONE
Bulk Pack: NONE
Max Qty Pass: 75 KG
Max Qty Cargo: 150 KG
Vessel Stow Req: A
Water/Ship/Other Req: 40,48,85

Detail IMO Information

IMO PSN Code: AIY
IMO Proper Shipping Name: AEROSOL DISPENSERS ?
IMO PSN Modifier: ,WITH A CAPACITY OF 1000 CUBIC CM OR LESS
IMDG Page Number: 9022
UN Number: 1950
UN Hazard Class: 9?
IMO Packaging Group: -
Subsidiary Risk Label: -
EMS Number: 2-13

Detail IATA Information

IATA PSN Code: ALS
IATA UN ID Num: 1950
IATA Proper Shipping Name: AEROSOLS, FLAMMABLE
IATA PSN Modifier: (EACH NOT EXCEEDING 1 L CAPACITY)
IATA UN Class: 2.1
IATA Label: FLAMMABLE GAS
Packing Note Passenger: 203
Max Quant Pass: 75KG
Max Quant Cargo: 150KG
Packaging Note Cargo: 203

Detail AFI Information

AFI PSN Code: ALR
AFI Symbols: *
AFI Proper Shipping Name: AEROSOLS, FLAMMABLE, N.O.S.
AFI PSN Modifier: (EACH NOT EXCEEDING 1L CAPACITY)
AFI Hazard Class: 2.1
AFI UN ID NUM: UN1950
Special Provisions: P4
Back Pack Reference: A6.3

HAZCOM Label

Product ID: KRYLON 1306 WORKABLE FIXATIF
Cage: 09800
Company Name: SHERWIN-WILLIAMS DIVERSIFIED BRANDS, INC.
Street: 26300 FARGO AVENUE
City: BEDFORD HEIGHTS OH
Zipcode: 44146
Health Emergency Phone: 216-292-7400
Label Required IND: Y
Date Of Label Review: 08/31/1995
Status Code: C
MFG Label NO: NONE
Label Date: 08/31/1995
Year Procured: 1995
Origination Code: F
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: DANGER
Respiratory Protection IND: YES
Health Hazard: Slight
Contact Hazard: Slight
Fire Hazard: Severe
Reactivity Hazard: None
Hazard And Precautions: **TARGET-ORGANS:EYES,SKIN,RESPIRATORY SYSTEM,CNS,CVS,KIDNEYS,LIVER,BLOOD FORMING ANDamp; REPRODUCTIVE SYSTEMS**
ACUTE-IRRITATION TO EYES,SKIN ANDamp; RESPIRATORY SYSTEM. MAY CAUSE NERVOUS SYSTEM DEPRESSION. EXTRE ME OVEREXPOSURE MAY RESULT IN UNCONSCIOUSNESS ANDamp; POSSIBLY DEATH. CHRONIC-PROLONGED ANDamp;/OR REPEATED OVEREXPOSURE MAY CAUSE PERIPHERAL NEUROPATHY,ADVERSE EFFECTS TO LIVER,URINARY,BLOOD FORMING,CVS,CNS OR R EPRODUCTIVE SYSTEMS. CONTENTS UNDER PRESSURE. DO NOT PUNCTURE, INCINERATE, OR EXPOSE TO TEMPERATURE ANDgt;120F, HEAT FROM SUNLIGHT, RADIATORS, STOVES, HOT WATER. MAY BURST. IN CASE OF SPILL: ELIMINATE SOUR CES OF IGNITION. VENTILATE ANDamp; REMOVE W/ABSORBENT.

Disclaimer

(provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever expressly or implied warrants, states, or intends said information to have any application, use or viability by or to any person or persons outside the Department of Defense nor any person or persons contracting with any instrumentality of the United States of America and disclaims all liability for such use. Any person utilizing this instruction who is not a military or civilian employee of the United States of America should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation regardless of similarity to a corresponding Department of Defense or other government situation.

[About](#) | [Contact emedco](#) | [Catalog Request](#)
[Jobs](#) | [Links](#) | [Privacy Statement](#)

©Copyri
800-442-36
FAX 800-344-25